

H-1

**Stormwater Intake
Form & Priority
Development Project
Stormwater Quality
Management Plan**

This page intentionally left blank.



**CITY OF ENCINITAS
STORMWATER INTAKE FORM AND PRIORITY DEVELOPMENT PROJECT
STORMWATER QUALITY MANAGEMENT PLAN (SWQMP)**

FOR:

TORREY CREST

CASE NO: MULTI -004309-2021; SUB-004310-2021; DR-004311-2021;
CDPNF-004312-2021 / CPP-004313-2021; SRVRQST-004316-2021

1220 – 1240 MELBA ROAD, 1190 ISLAND VIEW LANE
ENCINITAS, CA 92024

APN: 259-180-09, -10, -16, & -33-00; 259-181-02, -03, & -04-00

PREPARED BY:

TYLER G LAWSON
PASCO, LARET, SUITER & ASSOCIATES
535 N. HWY 101, SUITE A
SOLANA BEACH, CA 92075
PH: (858) 259-8212

PREPARED FOR:

TORREY PACIFIC CORPORATION
1106 SECOND STREET #115
ENCINITAS, CA 92024
PH: (760) 942-3256

DATE OF SWQMP:

2/26/2024

REVISION #7



TENTATIVE MAP PREPARED BY:

TYLER G LAWSON
PASCO, LARET, SUITER & ASSOCIATES
1911 SAN DIEGO AVENUE, SUITE 100
SAN DIEGO, CA 92110
PH: (858) 259-8212

TABLE OF CONTENTS

PREPARER'S CERTIFICATION.....	3
PROJECT OWNER'S CERTIFICATION.....	4
SUBMITTAL RECORD	5
PROJECT IDENTIFICATION.....	6
DETERMINATION OF PROJECT STATUS AND REQUIREMENTS	6
SITE INFORMATION CHECKLIST.....	9
SOURCE CONTROL BMP CHECKLIST	19
SITE DESIGN BMP CHECKLIST	20
PDP STRUCTURAL BMPS	21
STRUCTURAL BMP SUMMARY INFORMATION	22
ATTACHMENT 1 - BACKUP FOR PDP POLLUTANT CONTROL BMPS	23
ATTACHMENT 2 - BACKUP FOR PDP HYDROMODIFICATION CONTROL MEASURES	26
ATTACHMENT 3 - STRUCTURAL BMP MAINTENANCE INFORMATION	28
ATTACHMENT 4 - COPY OF PLAN SHEETS SHOWING PERMANENT STORM WATER BMPS	30

PREPARER'S CERTIFICATION

I hereby declare that I am the Engineer in Responsible Charge of design of storm water best management practices (BMPs) for this project, and that I have exercised responsible charge over the design of the BMPs as defined in Section 6703 of the Business and Professions Code, and that the design is consistent with the Priority Development Project (PDP) requirements of the City of Encinitas BMP Design Manual, which is a design manual for compliance with local City of Encinitas and regional MS4 Permit (California Regional Water Quality Control Board San Diego Region Order No. R9-2015-0100) requirements for storm water management.

I have read and understand that the City Engineer has adopted minimum requirements for managing urban runoff, including storm water, from land development activities, as described in the BMP Design Manual. I certify that this PDP SWQMP has been completed to the best of my ability and accurately reflects the project being proposed and the applicable BMPs proposed to minimize the potentially negative impacts of this project's land development activities on water quality. I understand and acknowledge that the plan check review of this PDP Storm Water Quality Management Plan (SWQMP) by the City Engineer is confined to a review and does not relieve me, as the Engineer in Responsible Charge of design of storm water BMPs for this project, of my responsibilities for project design.

 PE #80356

Engineer of Work's Signature, PE Number

Engineer's Seal

Tyler G Lawson

Print Name

Pasco, Laret, Suiter, & Associates

Company

February 26, 2024

Date



PROJECT OWNER'S CERTIFICATION

This PDP SWQMP has been prepared for TORREY PACIFIC CORPORATION by PASCO, LARET, SUITER & ASSOCIATES. The PDP SWQMP is intended to comply with the PDP requirements of the City of Encinitas BMP Design Manual, which is a design manual for compliance with local City of Encinitas and regional MS4 Permit (California Regional Water Quality Control Board San Diego Region Order No. R9-2015-0100) requirements for storm water management.

The undersigned, while it owns the subject property, is responsible for the implementation of the provisions of this plan. Once the undersigned transfers its interests in the property, its successor-in-interest shall bear the aforementioned responsibility to implement the best management practices (BMPs) described within this plan, including ensuring on-going operation and maintenance of structural BMPs. A signed copy of this document shall be available on the subject property into perpetuity.

Project Owner's Signature

Dan Staver

Print Name

Torrey Pacific Corporation

Company

Date

SUBMITTAL RECORD

Use this table to keep a record of submittals of this PDP SWQMP. Each time the PDP SWQMP is re-submitted, provide the date and status of the project. In the fourth column, summarize the changes that have been made or indicate if response to plancheck comments is included. When applicable, insert response to plancheck comments behind this page.

Submittal Number	Date	Project Status	Summary of Changes
1	1/7/21	☒ Preliminary Design / Planning/ CEQA ☐ Final Design	Initial Submittal
2	7/26/21	☒ Preliminary Design / Planning/ CEQA ☐ Final Design	Resubmittal, revised 4 DMA's / BMP's to a single DMA / BMP
3	3/22/22	☒ Preliminary Design / Planning/ CEQA ☐ Final Design	Resubmittal
4	3/7/23	☒ Preliminary Design / Planning/ CEQA ☐ Final Design	Resubmittal, Revised 3 DMA's / 2 BMP's
5	10/26/23	☒ Preliminary Design / Planning/ CEQA Final Design	Resubmittal
6	2/26/24	☒ Preliminary Design / Planning/ CEQA Final Design	Resubmittal

PROJECT IDENTIFICATION

Project/Applicant Name: Torrey Crest / Torrey Pacific Corporation	
Permit/Application Number: MULTI -004309-2021	Date: October 26, 2023
Site Address: 1220 – 1240 Melba Rd / 1190 Island View Ln	APN: 259-180-09, -10, -16, & -33-00; 259-181-02, -03, & -04-00
Scope of work/project description: Project proposes demolition of all existing onsite improvements and construction of 30x new single-family detached homes plus one proposed ADU, new private road with onstreet parking, and miscellaneous surface, grading, and utility improvements typical of this type of development.	

DETERMINATION OF PROJECT STATUS AND REQUIREMENTS

This form will identify permanent, post construction BMP requirements. Refer to City of Encinitas Stormwater BMP Design Manual for guidance.			
Step 1: Is the project a "development project"? Development projects are defined as "construction, rehabilitation, redevelopment, or reconstruction of any public or private projects". See Section 1.3 and Table 1-2 of the manual for guidance. For example, interior remodels, roof replacements, and electrical and plumbing work are not development projects.		☒ Yes	Go to Step 2.
		☐ No	Stop. Permanent BMP requirements do not apply. No SWQMP will be required. Provide discussion below.
If "No", provide discussion / justification explaining why the project is <u>not</u> a "development project":			
Step 2: Complete questions below for Project Type Determination. The project is (select one): ☐ New Development ☒ Redevelopment			
The total proposed, newly created and/or replaced impervious area is: _____ <u>174,610</u> _____ ft ²			
Is the project in any of the following categories, (a) through (f) below?			
Yes ☒	No ☐	(a)	New development projects or redevelopment projects that create and/or replaced 10,000 square feet or more of impervious surfaces (collectively over the entire project site). This includes commercial, industrial, residential, mixed-use, and public development projects.
Yes ☒	No ☐	(b)	Redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site on an existing site of 10,000 square feet or more of impervious surfaces). This includes commercial, industrial, residential, mixed-use, and public development projects.
Yes ☐	No ☒	(c)	New and redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site), and support one or more of the following uses: (i) Restaurants. This category is defined as a facility that sells prepared foods and drinks for consumption, including stationary lunch counters and

			refreshment stands selling prepared foods and drinks for immediate consumption (SIC code 5812). (ii) Hillside development projects. This category includes development on any natural slope that is twenty-five percent or greater. (iii) Parking lots. This category is defined as a land area or facility for the temporary parking or storage of motor vehicles used personally, for business, or for commerce. (iv) Streets, roads, highways, freeways, and driveways. This category is defined as any paved impervious surface used for the transportation of automobiles, trucks, motorcycles, and other vehicles.
Yes ☐	No ☒	(d)	New or redevelopment projects that create and/or replace 2,500 square feet or more of impervious surface (collectively over the entire project site), and discharge directly to an Environmentally Sensitive Area (ESA). "Discharge directly to" includes flow that is conveyed overland a distance of 200 feet or less from the project to the ESA, or conveyed in a pipe or open channel any distance as an isolated flow from the project to the ESA (i.e. not commingled with flows from adjacent lands). <u>Note: ESAs are areas that include but are not limited to all Clean Water Act Section 303(d) impaired water bodies; areas designated as Areas of Special Biological Significance by the State Water Board and SDRWQCB; State Water Quality Protected Areas; water bodies designated with the RARE beneficial use by the State Water Board and SDRWQCB; and any other equivalent environmentally sensitive areas which have been identified by the Copermittees. See manual Section 1.4.2 for additional guidance.</u>
Yes ☐	No ☒	(e)	New development projects, or redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface, that support one or more of the following uses: (i) Automotive repair shops. This category is defined as a facility that is categorized in any one of the following SIC codes: 5013, 5014, 5541, 7532-7534, or 7536-7539. (ii) Retail gasoline outlets. This category includes retail gasoline outlets that meet the following criteria: (a) 5,000 square feet or more or (b) a projected Average Daily Traffic of 100 or more vehicles per day.
Yes ☒	No ☐	(f)	New or redevelopment projects that result in the disturbance of one or more acres of land and are expected to generate pollutants post construction. <i>Note: See manual Section 1.4.2 for additional guidance.</i>
Does the project meet the definition of one or more of the PDP categories (a) through (f) listed above? ☒ Yes – The project is a <u>Priority Development Project</u>, the applicant shall provide PDP Post Construction BMPs and <i>continue to Step 3</i>. ☐ No – The project is a <u>Standard or Basic Project</u>. <i>Stop here and complete the "City of Encinitas Stormwater Intake Form for All Developments and Standard Projects SWQMP"</i>.			
The following is for <u>redevelopment PDPs</u> only: The area of existing (pre-project) impervious area at the project site is: <u>39,852</u> ft² (A) The total proposed newly created or replaced impervious area is: <u>174,610</u> ft² (B) Percent impervious surface created or replaced (B/A)*100: <u>438</u> % The percent impervious surface created or replaced is (select one based on the above calculation): ☐ Less than or equal to fifty percent (50%) – only new and/or replaced impervious areas are considered PDP subject to treatment and HMP criteria OR ☒ Greater than fifty percent (50%) – the entire site is a PDP; treatment and HMP criteria apply to entire site regardless of whether it is replaced			

Step 3 (PDPs only): Do hydromodification control requirements apply? See Section 1.6 of the BMP Design Manual for guidance.	☒ Yes	PDP structural BMPs required for pollutant control (Chapter 5) and hydromodification control (Chapter 6). Go to Step 4.
	☐ No	PDP structural BMPs required for pollutant control (Chapter 5) only. Provide brief discussion of exemption to hydromodification control below. Go to "Site Information Checklist"
Discussion / justification if hydromodification control requirements do <u>not</u> apply:		
Step 4 (PDPs subject to treatment and hydromodification controls): Does protection of critical coarse sediment yield areas apply based on review of City of Encinitas Potential Critical Coarse Sediment Yield Area Map? See Section 6.2 of the BMP Design Manual for guidance.	☐ Yes	Management measures required for protection of critical coarse sediment yield areas (Chapter 6.2). Go to "Site Information Checklist"
	☒ No	Management measures not required for protection of critical coarse sediment yield areas. Provide brief discussion below. Go to "Site Information Checklist"
Discussion / justification if management measures <u>not</u> required for protection of critical coarse sediment yield areas: Project site does not contain any potential Critical Coarse Sediment Yield Areas per the City of Encinitas Potential Critical Coarse Sediment Yield Area Map in the City's BMP Design Manual. However, project site contains one small triangle located toward the NE corner of the property as seen on the City's GIS. This area identified is not a potential CCSYA and is not subject to management measures for protection of critical coarse sediment yield areas – see discussion included on Page 15 of this report for additional analysis and determination.		

SITE INFORMATION CHECKLIST

Project's Watershed (Complete Hydrologic Unit, Area, and Subarea Name with Numeric Identifier)	Carlsbad Hydrologic Unit, San Marcos Creek Hydrologic Area, Batiquitos Lagoon Sub-Area (905.41) & Escondido Creek Hydrologic Area (904.61)
Parcel Area (Total area of Assessor's Parcel(s) associated with the project)	_ 6.65 _ Acres (_ 289,479 _ Square Feet)
Area to be Disturbed by the Project (Project Area)	_ 6.28 _ Acres (_ 273,457 _ Square Feet)
Project Proposed Impervious Area (Subset of Project Area)	_ 4.01 _ Acres (_ 174,610 _ Square Feet)
Project Proposed Pervious Area (Subset of Project Area)	_ 2.27 _ Acres (_ 98,847 _ Square Feet)
Note: Proposed Impervious Area + Proposed Pervious Area = Area to be Disturbed by the Project. This may be less than the Parcel Area.	
Description of Existing Site Condition	
Current status of the site (select all that apply): ☒ Existing development ☒ Previously graded but not built out ☐ Demolition completed without new construction ☐ Agricultural or other non-impervious use ☐ Vacant, undeveloped/natural Description / Additional Information: The site consists of existing residences, both in use and vacant, as well as driveways and miscellaneous hardscape and landscape improvements typical of the surrounding area and properties, including manufactured slopes and vegetative cover. A portion of the property is also currently undeveloped.	
Existing Land Cover includes (select all that apply): ☒ Vegetative Cover ☒ Non-Vegetated Pervious Areas ☒ Impervious Areas Description / Additional Information: Existing site consists of multiple structures and residences. Existing impervious areas consist of asphalt driveways and miscellaneous structures. Vegetative cover includes landscaped areas and planting on previously manufactured slopes.	
Underlying soil belongs to Hydrologic Soil Group (select all that apply): ☐ NRCS Type A ☐ NRCS Type B ☐ NRCS Type C ☒ NRCS Type D (Per site investigation performed by Geocon, Inc.)	

Approximate Depth to Groundwater (GW):

- ☐ GW Depth < 5 feet
- ☐ 5 feet < GW Depth < 10 feet
- ☐ 10 feet < GW Depth < 20 feet
- ☒ GW Depth > 20 feet

Existing Natural Hydrologic Features (select all that apply):

- ☐ Watercourses
- ☐ Seeps
- ☐ Springs
- ☐ Wetlands
- ☒ None

Description / Additional Information:

Description of Existing Site Drainage Patterns

How is storm water runoff conveyed from the site? At a minimum, this description should answer:

- 1) Is existing drainage conveyance natural or urban?
- 2) Is runoff from offsite conveyed through the site? If yes, quantify all offsite drainage areas, design flows, and locations where offsite flows enter the project site, and summarize how such flows are conveyed through the site.
- 3) Provide details regarding existing project site drainage conveyance network, including any existing storm drains, concrete channels, swales, detention facilities, storm water treatment facilities, natural or constructed channels. And
- 4) Identify all discharge locations from the existing project site along with a summary of conveyance system size and capacity for each of the discharge locations. Provide summary of the pre-project drainage areas and design flows to each of the existing runoff discharge locations.

Describe existing site drainage patterns:

The site itself contains 34 feet of elevation change within the proposed disturbed area. An existing single-family residence and structures toward the center-north portion of the property sit on the property's high point, with drainage falling away in all directions from this location. Existing drainage can be considered urban but runoff primarily drains via sheet flow as there do not appear to be any existing onsite storm drain.

While the site appears to ultimately discharge to two major watersheds and receiving bodies, runoff in the existing condition discharges from the property from 5 main locations (Drainage basins EX-1 through -5). The two discharge locations that eventually are routed to Moonlight Beach are Drainage basins EX-1 and EX-2. Drainage basin EX-1 discharges from the southwest corner of the property to Melba Road, where it continues west past the intersection of Balour Drive to a low spot at the intersection of Melba Road and Evergreen Drive near Ocean Knoll Elementary. From here, it is routed northwest through the canyon north, eventually reaching infrastructure in Encinitas Boulevard. Drainage basin EX-2 appears to leave the site from the northwest and along Island View Lane (heading west to Balour Drive). Once in Balour Drive, it is routed north to an existing curb inlet west of Oak Crest Middle School. The portion of the subject property under Island View Lane, a 15-ft x 690-ft parcel, is undisturbed by the project and has been excluded from this analysis. Runoff leaving to the west along both Melba Road and Island View Lane continue downstream towards Encinitas Boulevard, ultimately draining to the Pacific Ocean via Moonlight State Beach.

The remaining discharge locations from the property (EX-3, EX-4, and EX-5) are ultimately routed to San Marcos Creek and the Batiquitos Lagoon. Drainage basin EX-3 discharges to the northeast corner of the site towards Witham Road into an existing brow ditch within a public drainage easement. The ditch drains to the north through neighboring properties before outletting via an 18" storm drain connected to a curb outlet in a water line easement to the Witham Road curb face, where it further continues north to a storm drain inlet at Witham and Beechtree Drive. Drainage basin EX-4 discharges in a similar situation at the northeast corner, but south of the existing drainage ditch, where it travels through the adjacent properties, heads south on Witham Road and east on Crest Drive, and enters a curb inlet at the Hickoryhill Drive intersection. Lastly, basin EX-5 discharges east of the property onto adjacent lots and eventually makes its way down to Crest Drive to confluence with basin EX-4. Runoff leaving the site to the northeast towards Witham Road as well as the drainage reaching Crest Drive eventually reaches storm drain infrastructure at the intersection of Encinitas Boulevard with N. El Camino Real. This system ultimately continues to route drainage north to an outlet to the natural Encinitas Creek channel on the north side of Garden View Lane. This channel then eventually discharges into San Marcos Creek, a tributary of the Batiquitos Lagoon.

For continued discussion, see sheet 17 of 29.

Description of Proposed Site Development
Project Description / Proposed Land Use and/or Activities: Project proposes demolition of all existing onsite improvements and construction of 30-lot single-family residential detached homes plus one ADU with new private road, and miscellaneous surface, grading, storm water and utility improvements to support the new homes.
List/describe proposed impervious features of the project (e.g., buildings, roadways, parking lots, courtyards, athletic courts, other impervious features): Proposed impervious features of the project include the building footprints and roof areas, private road pavement, concrete sidewalk, driveways, and private walkways / porches.
List/describe proposed pervious features of the project (e.g., landscape areas): Pervious features of the project include graded slopes, landscape areas around the building footprint on each lot, proposed trees where shown on the project landscape plan, and centrally located biofiltration basin for storm water treatment.
Does the project include grading and changes to site topography? ☒ Yes ☐ No Description / Additional Information: Retaining walls and site grading are proposed to accommodate the new lots and to construct buildable pads. The site generally will continue to slope up from Melba Road to a high point located near the center of the property. The proposed site layout will have the lots south of the high point drain toward a BMP in the southeastern corner of the site. The lots north of the high point will drain to a BMP in the northwest corner. The project proposes ~22,000 CY of cut and ~6,500 CY of fill for ~15,500 CY of export, along with remedial grading.

Description of Proposed Site Drainage Patterns

Does the project include changes to site drainage (e.g., installation of new storm water conveyance systems)?

☒ Yes

☐ No

If yes, provide details regarding the proposed project site drainage conveyance network, including storm drains, concrete channels, swales, detention facilities, storm water treatment facilities, natural or constructed channels, and the method for conveying offsite flows through or around the proposed project site. Identify all discharge locations from the proposed project site along with a summary of the conveyance system size and capacity for each of the discharge locations. Provide a summary of pre- and post-project drainage areas and design flows to each of the runoff discharge locations. Reference the drainage study for detailed calculations.

Describe proposed site drainage patterns:

The project site can be consolidated into two major drainage basins in the proposed condition. The majority of runoff from EX-5 will be routed towards Melba Road to minimize cross-lot drainage onto neighboring properties as much as feasible. A small (less than a tenth of an acre) self-mitigating area will remain in EX-5 as part of PR-1. Within EX-1, runoff from 1250 Melba Road – delineated as OFF-1 will be conveyed directly to the Melba Road curb face, by passing the site and any treatment. A small self-mitigating area that drains offsite in the rear yard of Lot 1 to accommodate existing topography around two large Torrey Pine trees will also remain as a part of PR-1. Basin PR-1 will be comprised of the onsite portion of EX-1 and the majority of EX-5.

Basin EX-2 drains toward Island View Lane where no existing storm drain infrastructure exist, runoff sheet flows through the adjacent lots. A small (less than a tenth of an acre) self-mitigating area will remain in EX-2, post project PR-2. For the case of basin EX-3 draining offsite to a brow ditch located within a public drainage easement off the northeast corner of the property, it was the strong recommendation of City of Encinitas engineering staff to prevent any proposed water from continuing to discharge into this conveyance system. Section 6.201 of the City of Encinitas Engineering Design Manual (EDM) provides the City Engineer discretion to eliminate existing cross-lot drainage if an alternate solution is feasible. A small self-mitigating area that drains offsite from EX-3 will remain as PR-3. This public drainage easement and ditch run through the rear yards of several properties along Witham Road, and present access and maintenance challenges for the City of Encinitas Public Works Department to ensure proper drainage and conveyance over the long term. In the existing condition, it is already prone to flooding due to poor maintenance of the channel. Similarly, EX-4 drains offsite in the northwest corner, but runoff drains south of the existing brow ditch. In the existing condition runoff sheet flows through adjacent lots until runoff reaches Witham Road. To improve the existing cross lot drainage conditions, runoff will be routed toward northwest corner. Basin PR-4 will be comprised of EX-2, the majority of EX-3 and all of EX-4.

For continued discussion, see sheet 18 of 31.

Identification and Narrative of Receiving Water and Pollutants of Concern			
Describe flow path of storm water from the project site discharge location(s), through urban storm conveyance systems as applicable, to receiving creeks, rivers, and lagoons as applicable, and ultimate discharge to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable): Storm water leaving a majority of the site will enter the existing public storm drain system eventually in Encinitas Blvd. This system will eventually discharge into Moonlight State Beach and ultimately the Pacific Ocean west of Coast Highway 101. The remainder of the site will discharge from the northeast of the project and heads northeast toward El Camino Real. Eventually, the storm drain system outlets to the natural Encinitas creek channel on the north side of Garden View Lane, which conveys to Batiquitos Lagoon via San Marcos Creek.			
List any 303(d) impaired water bodies within the path of storm water from the project site to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable), identify the pollutant(s)/stressor(s) causing impairment, and identify any TMDLs and/or Highest Priority Pollutants from the WQIP for the impaired water bodies:			
303(d) Impaired Water Body	Pollutant(s)/Stressor(s)	TMDLs / WQIP Highest Priority Pollutant	
Cottonwood Creek (outlet)	Trash	Indicator Bacteria	
	Indicator Bacteria		
Pacific Ocean			
Identification of Project Site Pollutants* *Identification of project site pollutants is only required if flow-thru treatment BMPs are implemented onsite in lieu of retention or biofiltration BMPs (note the project must also participate in an alternative compliance program unless prior lawful approval to meet earlier PDP requirements is demonstrated)			
Identify pollutants expected from the project site based on all proposed use(s) of the site (see BMP Design Manual Appendix B.6):			
Pollutant	Not Applicable to the Project Site	Expected from the Project Site	Also a Receiving Water Pollutant of Concern
Sediment	x		
Nutrients	x		
Heavy Metals	x		
Organic Compounds	x		
Trash & Debris	x		
Oxygen Demanding Substances	x		
Oil & Grease	x		
Bacteria & Viruses	x		
Pesticides	x		

Hydromodification Management Requirements

Do hydromodification management requirements apply (see Section 1.6 of the BMP Design Manual)?

- ☒ Yes, hydromodification management flow control structural BMPs required.
- ☐ No, the project will discharge runoff directly to existing underground storm drains discharging directly to water storage reservoirs, lakes, enclosed embayments, or the Pacific Ocean.
- ☐ No, the project will discharge runoff directly to conveyance channels whose bed and bank are concrete-lined all the way from the point of discharge to water storage reservoirs, lakes, enclosed embayments, or the Pacific Ocean.
- ☐ No, the project will discharge runoff directly to an area identified as appropriate for an exemption by the WMAA for the watershed in which the project resides.

Description / Additional Information (to be provided if a 'No' answer has been selected above):

Critical Coarse Sediment Yield Areas*

*This section only required if hydromodification management requirements apply

Based on the maps provided within the WMAA, do potential critical coarse sediment yield areas exist within the project drainage boundaries?

- ☒ Yes
- ☐ No, no critical coarse sediment yield areas to be protected based on WMAA maps

If yes, have any of the optional analyses presented in Section 6.2 of the BMP Design Manual been performed?

- ☒ 6.2.1 Verification of Geomorphic Landscape Units (GLUs) Onsite
- ☐ 6.2.2 Downstream Systems Sensitivity to Coarse Sediment
- ☐ 6.2.3 Optional Additional Analysis of Potential Critical Coarse Sediment Yield Areas Onsite
- ☐ No optional analyses performed, the project will avoid critical coarse sediment yield areas identified based on WMAA maps

If optional analyses were performed, what was the final result?

- ☒ No critical coarse sediment yield areas to be protected based on verification of GLUs onsite
- ☐ Critical coarse sediment yield areas exist but additional analysis has determined that protection is not required. Documentation attached in Attachment 2.b of the SWQMP.
- ☐ Critical coarse sediment yield areas exist and require protection. The project will implement management measures described in Sections 6.2.4 and 6.2.5 as applicable, and the areas are identified on the SWQMP Exhibit.

Discussion / Additional Information:

Area identified on City's GIS map is not a potential Critical Coarse Sediment Yield Area. See discussion provided on Page 17 of 31 of this report.

Flow Control for Post-Project Runoff*

*This section only required if hydromodification management requirements apply

List and describe point(s) of compliance (POCs) for flow control for hydromodification management (see Section 6.3.1). For each POC, provide a POC identification name or number correlating to the project's HMP Exhibit and a receiving channel identification name or number correlating to the project's HMP Exhibit.

There are (2) point of compliance for flow control / hydromodification management leaving the subject property; POC-1 is located at the southwest corner of the property entering the Melba Road right-of-way. POC-2 is located at the northeast corner of the property discharging to Witham Road. Refer to the project's DMA and HMP exhibit for location.

Has a geomorphic assessment been performed for the receiving channel(s)?

☒ No, the low flow threshold is 0.1Q2 (default low flow threshold)

☐ Yes, the result is low flow threshold 0.1Q2

☐ Yes, the result is low flow threshold 0.3Q2

☐ Yes, the result is low flow threshold 0.5Q2

If a geomorphic assessment has been performed, provide title, date, and preparer:

Channel assessment has not been performed for project site. Thus, low-flow threshold of 0.1Q2 is assumed for the project.

Discussion / Additional Information: (optional)

Other Site Requirements and Constraints

When applicable, list other site requirements or constraints that will influence storm water management design, such as zoning requirements including setbacks and open space, or local codes governing minimum street width, sidewalk construction, allowable pavement types, and drainage requirements.

There are multiple site constraints that have influence on the storm water management design as well as the overall laying out of the site plan. First, as it relates to storm water, the project geotechnical engineer has identified low infiltration rates for the underlying topsoils, preventing any further infiltration in the post-project condition as part of the storm water strategy. See further discussion of BMP strategy, implementation, including the proposed storage system to comply with hydromodification low-flow requirements.

Optional Additional Information or Continuation of Previous Sections As Needed

Description of Existing Site Drainage Patterns

Existing drainage Basin EX-1, discharging from the southwest corner of the project site, has an area of approximately 3.32 acres and has a peak flow rate of 8.46 cfs. Existing drainage basin EX-2, discharging from the northwest corner of the project site has an area of approximately 0.75 acres and has a peak flow rate of 2.02 cfs. Existing drainage basin EX-3, discharging from the northeast corner of the project site, has an area of approximately 1.00 acres and a peak flow rate of 2.23 cfs. Existing drainage basin EX-4, discharging from the northeast corner of the project site, has an area of approximately 0.65 acres and a peak flow rate of 1.58 cfs. Existing drainage basin EX-5, discharging from the east of the project site, has an area of approximately 0.96 acres and a peak flow rate of 2.59 cfs. Refer to project Hydrology Report / Drainage Study prepared by Pasco, Laret, Suiter & Associates under separate cover for additional information.

Description of Proposed Site Drainage Patterns

The two onsite HMP-sized flow-control biofiltration detention basin and BMP system ("Basin") provides pollutant control as well as hydromodification management and mitigation of the 100-year, 6-hour storm event peak flow rate. Basin PR-1 and PR-4 will serve to capture, treat, and detain storm water and is composed of a cross-section of an engineered soil, storage layer, and hydraulic mulch on the surface. Runoff from higher frequency, lower intensity storm events will first be filtered through the Basin section to the storage layer that connects into the 36" x 36" emergency outlet brooks box.

During higher intensity storm events, water will pond on the surface of the Basin, and enter an overflow catch basin that will route water to the surface of Melba Road or Witham Road. Similar to the existing condition, runoff leaving from the southwest corner of the site continues downstream, entering existing public storm drain infrastructure and eventually reaching storm drain improvements in Encinitas Boulevard north of St. John School before outletting in Moonlight State Beach. Basin EX-5 in the existing condition was excluded from the drainage analysis for PR-1 to ensure discharge leaving the property to Melba Road and ultimately drainage to Moonlight State Beach is mitigated to the peak flow draining to that watershed determined in the pre-development condition. Runoff leaving the site from the northeast corner will outlet onto Witham Road drain south towards Crest Drive the continues to drain to the east until runoff reaches an existing curb inlet at the intersection of Crest Drive and Hickoryhill Drive. Basin EX-2 in the existing condition was excluded from the drainage analysis in PR-4 to ensure discharge leaving the property to Witham Road, confluencing in the public buried storm drain infrastructure at the intersection of Encinitas Boulevard and N El Camino Real and ultimately draining to San Marcos Creek is mitigated to the peak flow draining to that watershed determined in the pre-development condition.

The total unmitigated, undetained peak flow rate for the 100-year, 6-hour storm event generated for the analyzed drainage area is 24.29 cfs. Based on the analysis included in this report, the proposed onsite detention facilities accommodate the increase in peak runoff generated in the proposed condition, mitigating peak flows to below pre-developed conditions. The site has been designed and graded in a way to minimize earthwork to the greatest extent feasible and maintain historic drainage patterns. Water leaving the subject property will continue to do so from the same points of discharge as in the existing condition. Refer to project Hydrology Report / Drainage Study prepared by Pasco, Laret, Suiter & Associates under separate cover for additional information.

This space provided for additional information or continuation of information from previous sections as needed.

Discussion of Critical Coarse Sediment Yield Areas

Priority Development Projects (PDPs) must satisfy critical coarse sediment yield area (CCSYA) requirements as addressed in Appendix H of the City of Encinitas BMP Design Manual.

Regional-level mapping of potential critical coarse sediment yield areas was prepared using regional data sets included from the Regional WMAA.

A small portion of the site was identified on the City of Encinitas' GIS as containing a potential Critical Coarse Sediment Yield Area (PCCSYA). Per Section 6.2.1 of the City of Encinitas BMP Design Manual, "GLU's (Geomorphic Landscape Units) are areas with a combination of open (undeveloped) land cover, high relative sediment production based on a normalized revised universal soil loss equation analysis, and coarse-grained geologic material (material that is expected to produce greater than 50% sand when weathered)."

However, per Appendix H of the City of Encinitas BMP Design Manual, the "regional data set .. may not conform to all site conditions, or does not reflect changes to particular areas that have occurred since the underlying data was developed. This means slopes, geology, or land cover at the project site can be mischaracterized in the regional data set."

Consistent with the City of Encinitas BMP Design Manual section 6.2 and Appendix H, a detailed project-level verification of site specific GLU's was conducted. None of the GLU's listed in Table 6-1 of the BMP manual are present, as the area in question does not contain a combination of slope, geology, and land cover as listed in Table 6-1 (slope in this area is less than 10%). Thus, the area identified on the City's GIS are Potential CCSYA's that become non-Critical Coarse Sediment Yield Areas. Thus, there are no critical coarse sediment yield areas to be protected based on verification of GLUs onsite.

Discussion of Green Streets Design Standards

SOURCE CONTROL BMP CHECKLIST

All development projects must implement source control BMPs SC-1 through SC-6 where applicable and feasible. See Chapter 4 and Appendix E of the manual for information to implement source control BMPs shown in this checklist.

Answer each category below pursuant to the following.

- "Yes" means the project will implement the source control BMP as described in Chapter 4 and/or Appendix E of the manual. Discussion / justification is not required.
- "No" means the BMP is applicable to the project but it is not feasible to implement. Discussion / justification must be provided.
- "N/A" means the BMP is not applicable at the project site because the project does not include the feature that is addressed by the BMP (e.g., the project has no outdoor materials storage areas). Discussion / justification may be provided.

Source Control Requirement	Applied?		
SC-1 Prevention of Illicit Discharges into the MS4	☒ Yes	☐ No	☐ N/A
SC-2 Storm Drain Stenciling or Signage	☒ Yes	☐ No	☐ N/A
SC-3 Protect Outdoor Materials Storage Areas from Rainfall, Run-On, Runoff, and Wind Dispersal	☐ Yes	☐ No	☒ N/A
SC-4 Protect Materials Stored in Outdoor Work Areas from Rainfall, Run-On, Runoff, and Wind Dispersal	☐ Yes	☐ No	☒ N/A
SC-5 Protect Trash Storage Areas from Rainfall, Run-On, Runoff, and Wind Dispersal	☐ Yes	☐ No	☒ N/A
SC-6 Additional BMPs Based on Potential Sources of Runoff Pollutants (must answer for each source listed below)			
☐ Onsite storm drain inlets	☒ Yes	☐ No	☐ N/A
☐ Interior floor drains and elevator shaft sump pumps drain to sewer	☒ Yes	☐ No	☐ N/A
☐ Interior parking garages drain to sewer	☒ Yes	☐ No	☐ N/A
☐ Need for future indoor & structural pest control	☐ Yes	☐ No	☒ N/A
☐ Landscape/outdoor pesticide use	☒ Yes	☐ No	☐ N/A
☐ Pools, spas, ponds, decorative fountains, and other water features	☒ Yes	☐ No	☐ N/A
☐ Food service	☐ Yes	☐ No	☒ N/A
☐ Refuse/Trash areas must be covered	☒ Yes	☐ No	☐ N/A
☐ Industrial processes	☐ Yes	☐ No	☒ N/A
☐ Outdoor storage of equipment or materials must be covered	☐ Yes	☐ No	☒ N/A
☐ Vehicle and equipment cleaning	☐ Yes	☐ No	☒ N/A
☐ Vehicle/equipment repair and maintenance	☐ Yes	☐ No	☒ N/A
☐ Fuel dispensing areas	☐ Yes	☐ No	☒ N/A
☐ Loading docks	☐ Yes	☐ No	☒ N/A
☐ Fire sprinkler test water	☐ Yes	☐ No	☒ N/A
☐ Miscellaneous drain or wash water	☒ Yes	☐ No	☒ N/A
☐ Plazas, sidewalks, and parking lots	☐ Yes	☐ No	☐ N/A
	☐ Yes	☐ No	☒ N/A

Discussion / justification if SC-1 through SC-6 not implemented. Justification must be provided for ALL "No" answers shown above.

Project has no permanent outdoor materials storage areas or materials stored in outdoor work areas.
Project proposes pool equipment structure that will be covered.

SITE DESIGN BMP CHECKLIST

All development projects must implement site design BMPs SD-1 through SD-8 where applicable and feasible. See Chapter 4 and Appendix E of the manual for information to implement site design BMPs shown in this checklist.

Answer each category below pursuant to the following.

- "Yes" means the project will implement the site design BMP as described in Chapter 4 and/or Appendix E of the manual. Discussion / justification is not required.
- "No" means the BMP is applicable to the project but it is not feasible to implement. Discussion / justification must be provided.
- "N/A" means the BMP is not applicable at the project site because the project does not include the feature that is addressed by the BMP (e.g., the project site has no existing natural areas to conserve). Discussion / justification may be provided.

Source Control Requirement	Applied?		
SD-1 Maintain Natural Drainage Pathways and Hydrologic Features	☒ Yes	☐ No	☐ N/A
SD-2 Conserve Natural Areas, Soils, and Vegetation	☒ Yes	☐ No	☐ N/A
SD-3 Minimize Impervious Area	☒ Yes	☐ No	☐ N/A
SD-4 Minimize Soil Compaction	☐ Yes	☒ No	☐ N/A
SD-5 Impervious Area Dispersion - Directly Connected Impervious Areas (e.g. roof downspouts connected to street) are not allowed	☒ Yes	☐ No	☐ N/A
SD-6 Runoff Collection	☒ Yes	☐ No	☐ N/A
SD-7 Landscaping with Native or Drought Tolerant Species	☒ Yes	☐ No	☐ N/A
SD-8 Harvesting and Using Precipitation	☐ Yes	☒ No	☐ N/A

Discussion / justification if SD-1 through SD-8 not implemented. Justification must be provided for ALL "No" answers shown above.

SD-4: Minimizing soil compaction will be implemented to the greatest extent feasible, but will not occur under building footprints.

Project proposed to mass grade entire site, as well as develop and landscape. A full landscape plan is proposed to create appropriately landscaped areas.

SD-8: Harvesting and reuse deemed infeasible for this site

PDP STRUCTURAL BMPs

All PDPs must implement structural BMPs for storm water pollutant control (see Chapter 5 of the BMP Design Manual). Selection of PDP structural BMPs for storm water pollutant control must be based on the selection process described in Chapter 5. PDPs subject to hydromodification management requirements must also implement structural BMPs for flow control for hydromodification management (see Chapter 6 of the BMP Design Manual). Both storm water pollutant control and flow control for hydromodification management can be achieved within the same structural BMP(s).

PDP structural BMPs must be verified by the local jurisdiction at the completion of construction. This may include requiring the project owner or project owner's representative and engineer of record to certify construction of the structural BMPs (see Section 1.12 of the BMP Design Manual). PDP structural BMPs must be maintained into perpetuity (see Section 7 of the BMP Design Manual). The local jurisdiction will confirm the maintenance annually.

Use this section to provide narrative description of the general strategy for structural BMP implementation at the project site in the box below. Then complete the PDP structural BMP summary information sheet (page 3 of this form) for each structural BMP within the project (copy the BMP summary information page as many times as needed to provide summary information for each individual structural BMP).

Describe the general strategy for structural BMP implementation at the site. This information must describe how the steps for selecting and designing storm water pollutant control BMPs presented in Section 5.1 of the BMP Design Manual were followed, and the results (type of BMPs selected). For projects requiring hydromodification flow control BMPs, indicate whether pollutant control and flow control BMPs are integrated or separate.

The structural BMP chosen for this project is a biofiltration basin with impermeable liner (BF-1). After an initial site investigation and infiltration testing of the project topsoil / Very Old Paralic Deposits (Qvop) layer, the project geotechnical engineer identified low infiltration characteristics of the underlying soils, and recommended a "No Infiltration" condition along with using a liner for all BMP facilities.

PR-1 has a proposed structural BMP system consisting of a pre-treatment biofiltration basin with impermeable liner (BF-1), and a gravel storage layer. PR-4 has a proposed structural BMP system consisting of a pre-treatment biofiltration basin with impermeable liner (BF-1) and a proprietary StormTrap storage layer. Refer to Attachment 2d for additional details. The system will integrate both pollutant control measures with flow control for hydromodification management. The biofiltration pre-treatment basins have been sized to provide a minimum surface area of 3.0% of the contributing area times adjusted runoff factor draining to it to comply with water quality requirements per Appendix B of the City of Encinitas BMP Design Manual. There are no site design BMP's proposed for the project for which the runoff factor can be adjusted.

The basin, and detention storage system has been sized to demonstrate compliance with HMP requirements using the Environmental Protection Agency's (EPA) Storm Water Management Model (SWMM), including using the no infiltration.

STRUCTURAL BMP SUMMARY INFORMATION

Copy this page as necessary to provide information on each individual proposed structural BMP

Structural BMP ID No: BF-1	DMA No: 1 / DMA A
Construction Plan Sheet No: Civil Design Review / CDP Plan Sheets 4-7	
Type of structural BMP: ☐ Retention by harvest and use (HU-1) ☐ Retention by infiltration basin (INF-1) ☐ Retention by bioretention (INF-2) ☐ Retention by permeable pavement (INF-3) ☐ Partial retention by biofiltration with partial retention (PR-1) ☒ Biofiltration (BF-1) ☐ Biofiltration with Nutrient Sensitive Media Design (BF-2) ☐ Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F ☐ Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below) ☐ Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below) ☐ Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below) ☐ Detention pond or vault for hydromodification management ☒ Other (describe in discussion section below)	
Purpose: ☐ Pollutant control only ☐ Hydromodification control only ☒ Combined pollutant control and hydromodification control ☐ Pre-treatment/forebay for another structural BMP ☐ Other (describe in discussion section below)	
Who will inspect and certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms required by the City Engineer (See Section 1.12 of the BMP Design Manual)	Tyler G Lawson Associate Principal Pasco, Laret, Suiter & Associates
Who will be the final owner of this BMP?	Torrey Pacific Corporation / HOA
Who will maintain this BMP into perpetuity?	Torrey Pacific Corporation / HOA
What is the funding mechanism for maintenance?	Torrey Pacific Corporation / HOA
Discussion (as needed): The Homeowner's Association created with the new lots will be responsible for the maintenance of storm water facilities into perpetuity, as required by the City. The proposed structural BMP system consists of a pre-treatment biofiltration basin, with a gravel detention storage layer. Refer to Attachment 2d for additional details.	

STRUCTURAL BMP SUMMARY INFORMATION

Copy this page as necessary to provide information on each individual proposed structural BMP

Structural BMP ID No: BF-1	DMA No: 2 / DMA B
Construction Plan Sheet No: Civil Design Review / CDP Plan Sheets 4-7	
Type of structural BMP: ☐ Retention by harvest and use (HU-1) ☐ Retention by infiltration basin (INF-1) ☐ Retention by bioretention (INF-2) ☐ Retention by permeable pavement (INF-3) ☐ Partial retention by biofiltration with partial retention (PR-1) ☒ Biofiltration (BF-1) ☐ Biofiltration with Nutrient Sensitive Media Design (BF-2) ☐ Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F ☐ Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below) ☐ Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below) ☐ Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below) ☐ Detention pond or vault for hydromodification management ☒ Other (describe in discussion section below)	
Purpose: ☐ Pollutant control only ☐ Hydromodification control only ☒ Combined pollutant control and hydromodification control ☐ Pre-treatment/forebay for another structural BMP ☐ Other (describe in discussion section below)	
Who will inspect and certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms required by the City Engineer (See Section 1.12 of the BMP Design Manual)	Tyler G Lawson Associate Principal Pasco, Laret, Suiter & Associates
Who will be the final owner of this BMP?	Torrey Pacific Corporation / HOA
Who will maintain this BMP into perpetuity?	Torrey Pacific Corporation / HOA
What is the funding mechanism for maintenance?	Torrey Pacific Corporation / HOA
Discussion (as needed): The Homeowner's Association created with the new lots will be responsible for the maintenance of storm water facilities into perpetuity, as required by the City. The proposed structural BMP system consists of a pre-treatment biofiltration basin, proprietary StormTrap (or equivalent) detention storage system. Refer to Attachment 2d for additional details.	

ATTACHMENT 1 - BACKUP FOR PDP POLLUTANT CONTROL BMPS

This is the cover sheet for Attachment 1.

Indicate which items are included behind this cover sheet:

Attachment	Contents	Checklist
Attachment 1a	DMA Exhibit (Required) See DMA Exhibit Checklist on the back of this Attachment cover sheet.	☒ Included
Attachment 1b	Tabular Summary of DMAs Showing DMA ID matching DMA Exhibit, DMA Area, and DMA Type (Required)* *Provide table in this Attachment OR on DMA Exhibit in Attachment 1a	☒ Included on DMA Exhibit in Attachment 1a ☐ Included as Attachment 1b, separate from DMA Exhibit
Attachment 1c	Form I-7, Harvest and Use Feasibility Screening Checklist (Required unless the entire project will use infiltration BMPs) Refer to Appendix B.3-1 of the BMP Design Manual to complete Form I-7.	☒ Included ☐ Not included because the entire project will use infiltration BMPs
Attachment 1d	Form I-8, Categorization of Infiltration Feasibility Condition (Required unless the project will use harvest and use BMPs) Refer to Appendices C and D of the BMP Design Manual to complete Form I-8.	☒ Included ☐ Not included because the entire project will use harvest and use BMPs
Attachment 1e	Pollutant Control BMP Design Worksheets / Calculations (Required) Refer to Appendices B and E of the BMP Design Manual for structural pollutant control BMP design guidelines	☒ Included

Use this checklist to ensure the required information has been included on the DMA Exhibit:

The DMA Exhibit must identify:

- ☒ Underlying hydrologic soil group
- ☒ Approximate depth to groundwater
- ☐ Existing natural hydrologic features (watercourses, seeps, springs, wetlands)
- ☒ Critical coarse sediment yield areas to be protected
- ☒ Existing topography and impervious areas
- ☒ Existing and proposed site drainage network and connections to drainage offsite
- ☒ Proposed demolition
- ☒ Proposed grading
- ☒ Proposed impervious features
- ☒ Proposed design features and surface treatments used to minimize imperviousness
- ☒ Drainage management area (DMA) boundaries, DMA ID numbers, and DMA areas (square footage or acreage), and DMA type (i.e., drains to BMP, self-retaining, or self-mitigating)
- ☒ Potential pollutant source areas and corresponding required source controls (see Chapter 4, Appendix E.1, and Form I-3B)
- ☒ Structural BMPs (identify location, type of BMP, and size/detail)

ATTACHMENT 2 - BACKUP FOR PDP HYDROMODIFICATION CONTROL MEASURES

This is the cover sheet for Attachment 2.

- ☐ Mark this box if this attachment is not included because the project is exempt from PDP hydromodification management requirements.

Indicate which items are included behind this cover sheet:

Attachment	Contents	Checklist
Attachment 2a	Hydromodification Management Exhibit (Required)	☒ Included See Hydromodification Management Exhibit Checklist on the back of this Attachment cover sheet.
Attachment 2b	Management of Critical Coarse Sediment Yield Areas (WMAA Exhibit is required, additional analyses are optional) See Section 6.2 of the BMP Design Manual.	☒ Exhibit showing project drainage boundaries marked on WMAA Critical Coarse Sediment Yield Area Map (Required) Optional analyses for Critical Coarse Sediment Yield Area Determination ☐ 6.2.1 Verification of Geomorphic Landscape Units Onsite ☐ 6.2.2 Downstream Systems Sensitivity to Coarse Sediment ☐ 6.2.3 Optional Additional Analysis of Potential Critical Coarse Sediment Yield Areas Onsite
Attachment 2c	Geomorphic Assessment of Receiving Channels (Optional) See Section 6.3.4 of the BMP Design Manual.	☐ Not performed ☒ Included ☐ Submitted as separate stand-alone document
Attachment 2d	Flow Control Facility Design, including Structural BMP Drawdown Calculations and Overflow Design Summary (Required) See Chapter 6 and Appendix G of the BMP Design Manual	☐ Included ☒ Submitted as separate stand-alone document
Attachment 2e	Vector Control Plan (Required when structural BMPs will not drain in 96 hours)	☐ Included ☒ Not required because BMPs will drain in less than 96 hours

Use this checklist to ensure the required information has been included on the Hydromodification Management Exhibit:

The Hydromodification Management Exhibit must identify:

- ☒ Underlying hydrologic soil group
- ☒ Approximate depth to groundwater
- ☐ Existing natural hydrologic features (watercourses, seeps, springs, wetlands)
- ☒ Critical coarse sediment yield areas to be protected
- ☒ Existing topography
- ☒ Existing and proposed site drainage network and connections to drainage offsite
- ☒ Proposed grading
- ☒ Proposed impervious features
- ☒ Proposed design features and surface treatments used to minimize imperviousness
- ☒ Point(s) of Compliance (POC) for Hydromodification Management
- ☒ Existing and proposed drainage boundary and drainage area to each POC (when necessary, create separate exhibits for pre-development and post-project conditions)
- ☒ Structural BMPs for hydromodification management (identify location, type of BMP, and size/detail)

ATTACHMENT 3 - STRUCTURAL BMP MAINTENANCE INFORMATION

This is the cover sheet for Attachment 3.

Indicate which items are included behind this cover sheet:

Attachment	Contents	Checklist
Attachment 3a	Structural BMP Maintenance Thresholds and Actions (Required)	☒ Included See Structural BMP Maintenance Information Checklist on the back of this Attachment cover sheet.
Attachment 3b	Draft Maintenance Agreement (when applicable)	☐ Included ☐ Not Applicable

Use this checklist to ensure the required information has been included in the Structural BMP Maintenance Information Attachment:

☐ **Preliminary Design / Planning / CEQA level submittal:**

Attachment 3a must identify:

- ☐ Typical maintenance indicators and actions for proposed structural BMP(s) based on Section 7.7 of the BMP Design Manual

Attachment 3b is not required for preliminary design / planning / CEQA level submittal.

☐ **Final Design level submittal:**

Attachment 3a must identify:

- ☐ Specific maintenance indicators and actions for proposed structural BMP(s). This shall be based on Section 7.7 of the BMP Design Manual and enhanced to reflect actual proposed components of the structural BMP(s)
- ☐ How to access the structural BMP(s) to inspect and perform maintenance
- ☐ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
- ☐ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
- ☐ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
- ☐ Recommended equipment to perform maintenance
- ☐ When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management

Attachment 3b: For private entity operation and maintenance, Attachment 3b shall include a draft maintenance agreement in the local jurisdiction's standard format (PDP applicant to contact the City Engineer to obtain the current maintenance agreement forms).


ATTACHMENT 4 - COPY OF PLAN SHEETS SHOWING PERMANENT STORM WATER BMPS

This is the cover sheet for Attachment 4.

Use this checklist to ensure the required information has been included on the plans:

The plans must identify:

- ☐ Structural BMP(s) with ID numbers matching Form I-6 Summary of PDP Structural BMPs
- ☐ The grading and drainage design shown on the plans must be consistent with the delineation of DMAs shown on the DMA exhibit
- ☐ Details and specifications for construction of structural BMP(s)
- ☐ Signage indicating the location and boundary of structural BMP(s) as required by the [City Engineer]
- ☐ How to access the structural BMP(s) to inspect and perform maintenance
- ☐ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
- ☐ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
- ☐ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
- ☐ Recommended equipment to perform maintenance
- ☐ When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management
- ☐ Include landscaping plan sheets showing vegetation requirements for vegetated structural BMP(s)
- ☐ All BMPs must be fully dimensioned on the plans
- ☐ When proprietary BMPs are used, site-specific cross section with outflow, inflow, and model number shall be provided. Photocopies of general brochures are not acceptable.



PLAN VIEW - DRAINAGE MANAGEMENT AREA EXHIBIT

SCALE: 1" = 20' HORIZONTAL

GROUNDWATER INFORMATION

GROUNDWATER NOT ENCOUNTERED DURING SITE INVESTIGATION, AND EXPECTED AT DEPTHS GREATER THAN 50 FEET BELOW EXISTING GRADES PER "STORM WATER MANAGEMENT INVESTIGATION" PREPARED BY GEOCON, INC. DATED 1/8/21

COARSE SEDIMENT YIELD

NO CRITICAL COARSE SEDIMENT YIELD AREAS TO BE PROTECTED ONSITE OR UPSTREAM OF SUBJECT PROPERTY. REFER TO DISCUSSION IN PRIORITY DEVELOPMENT PROJECT SWQMP PREPARED BY PASCO, LARET, SUITER & ASSOCIATES

SELF-MITIGATING DMA - DMA V

TOTAL BASIN SIZE	=	70 SF (0.002 AC)
SELF-MITIGATING IMPERVIOUS AREA	=	0 SF
% IMPERVIOUS	=	0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

SELF-MITIGATING DMA - DMA X

TOTAL BASIN SIZE	=	811 SF (0.019 AC)
SELF-MITIGATING IMPERVIOUS AREA	=	0 SF
% IMPERVIOUS	=	0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

SELF-MITIGATING DMA - DMA Y

TOTAL BASIN SIZE	=	843 SF (0.019 AC)
SELF-MITIGATING IMPERVIOUS AREA	=	0 SF
% IMPERVIOUS	=	0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

SELF-MITIGATING DMA - DMA Z

TOTAL BASIN SIZE	=	2,943 SF (0.067 AC)
SELF-MITIGATING IMPERVIOUS AREA	=	0 SF
% IMPERVIOUS	=	0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

LEGEND

PROPERTY BOUNDARY	---
CENTERLINE OF ROAD	---
RIGHT-OF-WAY	---
ADJACENT PROPERTY LINE	---
EXISTING CONTOUR LINE	---
PROPOSED CONTOUR LINE	---
DMA DRAINAGE BASIN BOUNDARY	---
PROPOSED / REMOVED AND REPLACED IMPERVIOUS AREA WITHIN DISTURBED AREA OF SITE	---
BMP / BIOFILTRATION BASIN AREA	---
SELF-MITIGATING AREA PER BMP DESIGN MANUAL SECTION 5.2.1	---

PROJECT SITE AREA CALCULATIONS

TOTAL GROSS SITE AREA	289,479 SF (6.646 AC)
AREA DISTURBED BY PROJECT	273,457 SF (6.278 AC)
EXISTING IMPERVIOUS AREA	39,852 SF (0.915 AC)
EXISTING PERVIOUS AREA	231,129 SF (5.306 AC)
TOTAL DMA AREA (DMA A)	153,962 SF (3.53 AC)
TOTAL DMA AREA (DMA B)	114,153 SF (2.62 AC)
TOTAL DMA AREA (DMA C)	432 SF (0.001 AC)
TOTAL DMA AREA (DMA D)	243 SF (0.006 AC)
TOTAL SELF-MITIGATING DMA AREAS	4,667 SF (0.11 AC)
TOTAL PROPOSED IMPERVIOUS AREA	151,866 SF (3.48 AC)
**15% LOT HARDSCAPE CONTINGENCY	22,744 SF (0.52 AC)
ASSUMED TOTAL IMPERVIOUS AREA	174,610 SF (4.01 AC)
TOTAL PROPOSED PERVIOUS AREA	98,847 SF (2.27 AC)
**15% FUTURE LOT HARDSCAPE CONTINGENCY BASED ON ROOF AREA AND PRIVATE WALKWAYS / PATIOS, EXCLUSIVE OF PRIVATE ROAD, SIDEWALK, AND PRIVATE DRIVEWAYS; RESULTS IN 500 SF OF FUTURE HARDSCAPE ALLOTTED TO EACH LOT	

SELF-RETAINING DMA - DMA C

TOTAL BASIN SIZE	=	432 SF (0.010 AC)
SELF-RETAINING IMPERVIOUS AREA	=	432 SF
RATIO OF DMA AREA TO PERV. PAVEMENT AREA	=	1:1

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-RETAINING PERVIOUS PAVEMENT DMAS THAT RETAIN RUNOFF TO A LEVEL DETERMINED TO CONSTITUTE FULL RETENTION OF THE ENTIRE DCV. PERVIOUS PAVEMENTS THAT HAVE A RATIO OF 1:1 OR LESS FOR TOTAL DRAINAGE AREA TO AREA OF PERVIOUS PAVEMENTS CAN BE CONSIDERED SELF-RETAINING.

DE MINIMIS DMA - DMA D

TOTAL BASIN SIZE	=	243 SF (0.006 AC)
------------------	---	-------------------


SECTION 5.2.2 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR DE MINIMIS AREAS THAT ARE LESS THAN 250 SF AND ALL DE MINIMIS AREAS FOR THE SITE ARE LESS THAN 2 PERCENT OF THE TOTAL REMOVED OR REPLACED IMPERVIOUS AREA

SOIL TYPE INFORMATION

SOIL: TYPE D SOILS FOR VERY OLD PARALIC DEPOSITS TOPSOIL PER "STORM WATER MANAGEMENT INVESTIGATION" REPORT PREPARED BY GEOCON, INC. DATED 7/16/21; (TYPE B HYDROLOGIC SOILS PER WEB SOIL SURVEY APPLICATION AVAILABLE THROUGH UNITED STATES DEPARTMENT OF AGRICULTURE)


TREATMENT CONTROL BMPS

BIOFILTRATION WITH IMPERVIOUS LINER BF-1



ATTACHMENT 1A
DRAINAGE MANAGEMENT AREA EXHIBIT
1220-1240 MELBA ROAD
CITY OF ENCINITAS

PLSA
PLSAENGINEERING.COM



DMA A - AREA CALCULATIONS

IMPERVIOUS AREA	(BUILDING / ROOF)	60,371 SF
	(DRIVEWAYS)	7,466 SF
	(LOT HARDSCAPE)	3,353 SF
	(PRIVATE DRIVE/WALKWAY)	19,074 SF
	(**15% FUTURE CONTINGENCY)	13,540 SF
	TOTAL	103,804 SF

PERVIOUS AREA	(LANDSCAPED AREA)	57,688 SF
	(BIOFILTRATION BASIN)	6,010 SF
	(15% FUTURE CONTINGENCY)	-13,540 SF
	TOTAL	50,158 SF

TOTAL BASIN AREA 153,962 SF

% IMPERVIOUS AREA 67.4%

**15% FUTURE LOT HARDSCAPE CONTINGENCY
BASED ON ROOF AREA AND PRIVATE WALKWAYS /
PATIOS, EXCLUSIVE OF PRIVATE ROAD, SIDEWALK,
AND PRIVATE DRIVEWAYS

DMA B - AREA CALCULATIONS

IMPERVIOUS AREA	(BUILDING / ROOF)	35,580 SF
	(DRIVEWAYS)	9,905 SF
	(LOT HARDSCAPE)	1,296 SF
	(PRIVATE DRIVE/WALKWAY)	13,188 SF
	(**15% FUTURE CONTINGENCY)	9,220 SF
	TOTAL	70,887 SF

PERVIOUS AREA	(LANDSCAPED AREA)	48,789 SF
	(BIOFILTRATION BASIN)	3,030 SF
	(15% FUTURE CONTINGENCY)	-8,783 SF
	TOTAL	42,999 SF

TOTAL BASIN AREA 113,286 SF

% IMPERVIOUS AREA 52.4%

DMA TABLE - TREATMENT (BASIN A)					
AREA NAME	AREA (SF)	POST-PROJECT SURFACE TYPE	SURFACE RUNOFF FACTOR	ADJUSTMENT FACTOR	AREA X ADJUSTED RUNOFF (SF)
A1	2069	LOT 1 ROOF	0.9	1	1862
A2	215	LOT 1 DRIVEWAY	0.9	1	194
A3	117	LOT 1 HARDSCAPE	0.9	1	105
A4	3366	LOT 2 ROOF	0.9	1	3029
A5	453	LOT 2 DRIVEWAY	0.9	1	408
A6	70	LOT 2 HARDSCAPE	0.9	1	63
A7	2942	LOT 3 ROOF	0.9	1	2648
A8	494	LOT 3 DRIVEWAY	0.9	1	445
A9	357	LOT 3 HARDSCAPE	0.9	1	321
A10	3611	LOT 4 ROOF	0.9	1	3250
A11	684	LOT 4 DRIVEWAY	0.9	1	616
A12	55	LOT 4 HARDSCAPE	0.9	1	50
A13	3235	LOT 5 ROOF	0.9	1	2912
A14	426	LOT 5 DRIVEWAY	0.9	1	383
A15	168	LOT 5 HARDSCAPE	0.9	1	151
A16	4169	LOT 6 ROOF	0.9	1	3752
A17	279	LOT 6 DRIVEWAY	0.9	1	251
A18	115	LOT 6 HARDSCAPE	0.9	1	104
A19	3419	LOT 7 ROOF	0.9	1	3077
A20	266	LOT 7 DRIVEWAY	0.9	1	239
A21	194	LOT 7 HARDSCAPE	0.9	1	175
A22	4169	LOT 8 ROOF	0.9	1	3752
A23	288	LOT 8 DRIVEWAY	0.9	1	259
A24	115	LOT 8 HARDSCAPE	0.9	1	104
A25	3177	LOT 9 ROOF	0.9	1	2859
A26	270	LOT 9 DRIVEWAY	0.9	1	243
A27	290	LOT 9 HARDSCAPE	0.9	1	261
A28	3177	LOT 22 ROOF	0.9	1	2859
A29	485	LOT 22 DRIVEWAY	0.9	1	437
A30	290	LOT 22 HARDSCAPE	0.9	1	261
A31	4245	LOT 23 ROOF	0.9	1	3821
A32	433	LOT 23 DRIVEWAY	0.9	1	390
A33	203	LOT 23 HARDSCAPE	0.9	1	183
A34	3235	LOT 24 ROOF	0.9	1	2912
A35	526	LOT 24 DRIVEWAY	0.9	1	473
A36	168	LOT 24 HARDSCAPE	0.9	1	151
A37	4179	LOT 25 ROOF	0.9	1	3761
A38	444	LOT 25 DRIVEWAY	0.9	1	400
A39	117	LOT 25 HARDSCAPE	0.9	1	105
A40	3418	LOT 26 ROOF	0.9	1	3076
A41	486	LOT 26 DRIVEWAY	0.9	1	437
A42	208	LOT 26 HARDSCAPE	0.9	1	187
A43	2292	LOT 27 ROOF	0.9	1	2063
A44	354	LOT 27 DRIVEWAY	0.9	1	319
A45	450	LOT 27 HARDSCAPE	0.9	1	405
A46	3693	LOT 28 ROOF	0.9	1	3324
A47	347	LOT 28 DRIVEWAY	0.9	1	312
A48	79	LOT 28 HARDSCAPE	0.9	1	71
A49	2944	LOT 29 ROOF	0.9	1	2650
A50	640	LOT 29 DRIVEWAY	0.9	1	576
A51	357	LOT 29 HARDSCAPE	0.9	1	321
A52	3031	LOT 30 ROOF	0.9	1	2728
A53	376	LOT 30 DRIVEWAY	0.9	1	338
A54	0	LOT 30 HARDSCAPE	0.9	1	0
A55	4008	WALKWAY	0.9	1	3607
A56	15066	PRIVATE DRIVE	0.9	1	13559
A57	6010	BMP D	0.3	1	1803
A58	57688	LANDSCAPE	0.3	1	17306
TOTAL					100347

TOTAL DMA SIZE = 100,347 SF
ADD 15% HARDSCAPE CONTINGENCY = 9,204 SF * 0.9 - 9,204 SF * 0.3
ADJUSTED DMA SIZE = 105,869 SF

IMP. SIZING FACTOR = 0.03 (FOR BIOFILTRATION BMPS)
MIN. AREA REQUIRED = 0.03 * 105,869 SF = 3,176 SF

**610 SF PROPOSED > 3,176 SF REQUIRED;
THEREFORE STANDARD BIOFILTRATION MINIMUM AREA REQUIREMENTS MET**

DMA A - DCV CALCULATIONS

AREA TRIBUTARY TO BMP (A) = 153,962 SF / 3.53 AC

TOTAL DMA SIZE (C_x*A_x) = 105,869 SF
WEIGHTED RUNOFF FACTOR (C_x) = 0.74
85TH PERCENTILE RAINFALL DEPTH (d) = 0.54 INCHES

DCV (C_x*d*A³.630) = 4,764 CU. FT.

DMA TABLE - TREATMENT (BASIN B)					
AREA NAME	AREA (SF)	POST-PROJECT SURFACE TYPE	SURFACE RUNOFF FACTOR	ADJUSTMENT FACTOR	AREA X ADJUSTED RUNOFF (SF)
B1	3366	LOT10 ROOF	0.9	1	3029
B2	1742	LOOT 10 DRIVEWAY	0.9	1	1568
B3	70	LOT 10 HARDSCAPE	0.9	1	63
B4	3544	LOT 11 ROOF	0.9	1	3190
B5	1304	LOT 11 DRIVEWAY	0.9	1	1174
B6	0	LOT 11 HARDSCAPE	0.9	1	0
B7	2942	LOT 12 ROOF	0.9	1	2648
B8	869	LOT 12 DRIVEWAY	0.9	1	773
B9	357	LOT 12 HARDSCAPE	0.9	1	321
B10	3025	LOT 13 ROOF	0.9	1	2723
B11	463	LOT 13 DRIVEWAY	0.9	1	417
B12	0	LOT 13 HARDSCAPE	0.9	1	0
B13	2942	LOT 14 ROOF	0.9	1	2648
B14	784	LOT 14 DRIVEWAY	0.9	1	706
B15	357	LOT 14 HARDSCAPE	0.9	1	321
B16	2438	LOT 15 ROOF	0.9	1	2194
B17	366	LOT 15 DRIVEWAY	0.9	1	329
B18	0	LOT 15 HARDSCAPE	0.9	1	0
B19	3031	LOT 16 ROOF	0.9	1	2728
B20	425	LOT 16 DRIVEWAY	0.9	1	383
B21	0	LOT 16 HARDSCAPE	0.9	1	0
B22	1472	LOT 17 ROOF	0.9	1	1325
B23	567	LOT 17 DRIVEWAY	0.9	1	510
B24	0	LOT 17 HARDSCAPE	0.9	1	0
B25	3544	LOT 18 ROOF	0.9	1	3190
B26	1235	LOT 18 DRIVEWAY	0.9	1	1112
B27	0	LOT 18 HARDSCAPE	0.9	1	0
B28	3544	LOT 19 ROOF	0.9	1	3190
B29	861	LOT 19 DRIVEWAY	0.9	1	775
B30	0	LOT 19 HARDSCAPE	0.9	1	0
B31	3047	LOT 20 ROOF	0.9	1	2742
B32	834	LOT 20 DRIVEWAY	0.9	1	751
B33	357	LOT 20 HARDSCAPE	0.9	1	321
B34	2507	LOT 21 ROOF	0.9	1	2256
B35	465	LOT 21 DRIVEWAY	0.9	1	419
B36	225	LOT 21 HARDSCAPE	0.9	1	203
B37	1498	WALKWAY	0.9	1	1348
B38	13188	PRIVATE DRIVE	0.9	1	11869
B39	3030	BMP D	0.3	1	909
B40	48897	LANDSCAPE	0.3	1	14669
TOTAL					70801

TOTAL DMA SIZE = 70,866 SF
ADD 15% HARDSCAPE CONTINGENCY = 8,783 SF * 0.9 - 8,783 SF * 0.3
ADJUSTED DMA SIZE = 76,136 SF

IMP. SIZING FACTOR = 0.03 (FOR BIOFILTRATION BMPS)
MIN. AREA REQUIRED = 0.03 * 76,136 SF = 2,284 SF


**3,030 SF PROPOSED > 2,284 SF REQUIRED;
THEREFORE STANDARD BIOFILTRATION MINIMUM AREA REQUIREMENTS MET**

DMA B - DCV CALCULATIONS

AREA TRIBUTARY TO BMP (A) = 113,286 SF SF / 2.60 AC


TOTAL DMA SIZE (C_x*A_x) = 76,136 SF
WEIGHTED RUNOFF FACTOR (C_x) = 0.65
85TH PERCENTILE RAINFALL DEPTH (d) = 0.54 INCHES

DCV (C_x*d*A³.630) = 3,426 CU. FT.




NOTE:
-ALL AGGREGATE MUST BE CLEANWASHED AND FREE OF FINES (SAND, SILT, ETC.)
-THE PAVERS SHALL NOT BE SEALED ONCE THE VOID FILLER HAS BEEN ADDED
-EACH COURSE SHALL BE VIBRATORY COMPACTED BEFORE PLACEMENT OF NEXT COURSE
-NO IMPERVIOUS LINER OR FILTER FABRIC IS TO BE USED
-SPECIAL APPROVAL REQUIRED FOR USE IN HIGHLY EXPANSIVE SOIL-SUBDRAIN MAY BE REQUIRED

TYPICAL DETAIL - PERVIOUS PAVERS
NOT TO SCALE




TYPICAL SECTION - BIOFILTRATION BASIN A
NOT TO SCALE

'BIOFILTRATION' 'ENGINEERED SOIL' LAYER SHALL BE
EVENLY MIXED COMPOSITION OF WASHED SAND,
SANDY LOAM TOPSOIL, AND HUMIC COMPOST. THE MIX
SHALL CONTAIN 65% SAND, 20% TOPSOIL, AND 15%
COMPOST OR HARDWOOD MULCH IN ACCORDANCE
WITH COUNTY OF SAN DIEGO LID BIOSWALE MEDIA



TYPICAL DETAIL - FLOW CONTROL ORIFICE PLATE
NOT TO SCALE



TYPICAL SECTION - BIOFILTRATION BASIN B
NOT TO SCALE

ATTACHMENT 1B
DRAINAGE MANAGEMENT AREA CALCS
1220-1240 MELBA ROAD
CITY OF ENCINITAS

Harvest and Use Feasibility Checklist		Form I-7
1. Is there a demand for harvested water (check all that apply) at the project site that is reliably present during the wet season? ☒ Toilet and urinal flushing ☒ Landscape irrigation ☐ Other: _____		
2. If there is a demand; estimate the anticipated average wet season demand over a period of 36 hours. Guidance for planning level demand calculations for toilet/urinal flushing and landscape irrigation is provided in Section B.3.2. Toilet & Urinal Demand -> 9.3 Gal / resident Landscape Demand -> 1,470 Gal / irrigated acre moderate water use 9.3 gal/day x (0.13368 cu ft/gal) x (1.5 days) = 1.86 cu ft / person over 36 hrs 30 units x 4.0 people/unit x (1.86 cu ft / person = 36 hr) = 223 cu ft / 36 hrs (toilet/urinal flushing) 3.09 ac irrigated x 1,470 gal / ac - 36 hr x 0.13368 cu ft / gal = 607 cu ft / 36 hrs (landscaping) Total = 223 cu ft + 607 cu ft = 830 cu ft		
3. Calculate the DCV using worksheet B-2.1. DCV = <u>7,811</u> (cubic feet) Total		
3a. Is the 36 hour demand greater than or equal to the DCV? ☐ Yes / ☒ No ⇒ ↓	3b. Is the 36 hour demand greater than 0.25DCV but less than the full DCV? ☐ Yes / ☒ No ⇒ ↓	3c. Is the 36 hour demand less than 0.25DCV? ☒ Yes ↓
Harvest and use appears to be feasible. Conduct more detailed evaluation and sizing calculations to confirm that DCV can be used at an adequate rate to meet drawdown criteria.	Harvest and use may be feasible. Conduct more detailed evaluation and sizing calculations to determine feasibility. Harvest and use may only be able to be used for a portion of the site, or (optionally) the storage may need to be upsized to meet long term capture targets while draining in longer than 36 hours.	Harvest and use is considered to be infeasible.
Is harvest and use feasible based on further evaluation? ☐ Yes, refer to Appendix E to select and size harvest and use BMPs. ☒ No, select alternate BMPs.		

Categorization of Infiltration Feasibility Condition		Worksheet C.4-1	
Part 1 - Full Infiltration Feasibility Screening Criteria Would infiltration of the full design volume be feasible from a physical perspective without any undesirable consequences that cannot be reasonably mitigated?			
Criteria	Screening Question	Yes	No
1	Is the estimated reliable infiltration rate below proposed facility locations greater than 0.5 inches per hour? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2 and Appendix D.		X
Provide basis: Based on the USGS Soil Survey, the property possesses Hydrologic Soil Group D classifications and an infiltration rate of less than 0.5 inches per hour. We performed 4 infiltration tests in two areas of the site within the underlying Very Old Paralic Deposits. The results indicate an average rate of 0.003 inches per hour (with an applied factor of safety of 2). Therefore, full infiltration is considered infeasible at the site.			
2	Can infiltration greater than 0.5 inches per hour be allowed without increasing risk of geotechnical hazards (slope stability, groundwater mounding, utilities, or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of		X
Provide basis: Infiltration should not be allowed in areas of the site which would negatively affect the adjacent properties and improvements or the existing sloping conditions on the site. Infiltration would cause seepage and erosion on the existing slopes if it were allowed. Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.			

Worksheet C.4-1 Page 2 of 4

Criteria	Screening Question	Yes	No
3	Can infiltration greater than 0.5 inches per hour be allowed without increasing risk of groundwater contamination (shallow water table, storm water pollutants or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.	X	
Provide basis: We anticipate that groundwater is present at depths of greater than 50 feet. Therefore, infiltration due to groundwater elevations would be considered feasible. Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.			
4	Can infiltration greater than 0.5 inches per hour be allowed without causing potential water balance issues such as change of seasonality of ephemeral streams or increased discharge of contaminated groundwater to surface waters? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.	X	
Provide basis: A shallow groundwater table does not exist within 10 feet of the proposed grades and we are not aware of any wells within 100 feet of the site. Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.			
Part 1 Result*	If all answers to rows 1 - 4 are “Yes” a full infiltration design is potentially feasible. The feasibility screening category is Full Infiltration If any answer from row 1-4 is “No”, infiltration may be possible to some extent but would not generally be feasible or desirable to achieve a “full infiltration” design. Proceed to Part 2	No Infiltration	

***To be completed using gathered site information and best professional judgment considering the definition of MEP in the MS4 Permit. Additional testing and/or studies may be required by the City to substantiate findings.**

Worksheet C.4-1 Page 3 of 4

Part 2 – Partial Infiltration vs. No Infiltration Feasibility Screening Criteria

Would infiltration of water in any appreciable amount be physically feasible without any negative consequences that cannot be reasonably mitigated?

Criteria	Screening Question	Yes	No
5	Do soil and geologic conditions allow for infiltration in any appreciable rate or volume? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2 and Appendix D.		X

Provide basis:

Based on the USGS Soil Survey, the property possesses Hydrologic Soil Group D classifications and an infiltration rate of less than 0.5 inches per hour. We performed 4 infiltration tests in two areas of the site within the underlying Very Old Paralac Deposits. The results indicate an average rate of 0.003 inches per hour (with an applied factor of safety of 2). Therefore, full infiltration is considered infeasible at the site.

6	Can Infiltration in any appreciable quantity be allowed without increasing risk of geotechnical hazards (slope stability, groundwater mounding, utilities, or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2.		X
---	---	--	---

Provide basis:

Infiltration should not be allowed in areas of the site which would negatively affect the adjacent properties and improvements or the existing sloping conditions on the site. Infiltration would cause seepage and erosion on the existing slopes if it were allowed.

Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.

Worksheet C.4-1 Page 4 of 4

Criteria	Screening Question	Yes	No
7	Can Infiltration in any appreciable quantity be allowed without posing significant risk for groundwater related concerns (shallow water table, storm water pollutants or other factors)? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.	X	
Provide basis: We anticipate that groundwater is present at depths of greater than 50 feet. Therefore, infiltration due to groundwater elevations would be considered feasible. Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.			
8	Can infiltration be allowed without violating downstream water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.	X	
Provide basis: We did not provide a study regarding water rights. However, these rights are not typical in the San Diego County area. Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.			
Part 2 Result*	If all answers from row 1-4 are yes then partial infiltration design is potentially feasible. The feasibility screening category is Partial Infiltration. If any answer from row 5-8 is no, then infiltration of any volume is considered to be infeasible within the drainage area. The feasibility screening category is No Infiltration.	No Infiltration	

***To be completed using gathered site information and best professional judgment considering the definition of MEP in the MS4 Permit. Additional testing and/or studies may be required by the City to substantiate findings.**

Appendix B: Storm Water Pollutant Control Hydrologic Calculations and Sizing Methods

Worksheet B.2-1. DCV

DMA A

Design Capture Volume		Worksheet B-2.1		
1	85 th percentile 24-hr storm depth from Figure B.1-1	d=	0.54	inches
2	Area tributary to BMP (s)	A=	3.53	acres
3	Area weighted runoff factor (estimate using Appendix B.1.1 and B.2.1)	C=	0.74	unitless
4	Street trees volume reduction	TCV=	0	cubic-feet
5	Rain barrels volume reduction	RCV=	0	cubic-feet
6	Calculate DCV = (3630 x C x d x A) – TCV - RCV	DCV=	4,764	cubic-feet

AREA TRIBUTARY TO BMP (A) = 153,962 SF / 3.53 AC

TOTAL DMA SIZE (C_x*A_x) = 105,869 SF

WEIGHTED RUNOFF FACTOR (C_x) = 0.74

85TH PERCENTILE RAINFALL DEPTH (d) = 0.54 INCHES

DCV (C*d*A*3,630) = 4,764 CU. FT.

Appendix B: Storm Water Pollutant Control Hydrologic Calculations and Sizing Methods

Worksheet B.2-1. DCV

Design Capture Volume		Worksheet B-2.1		
1	85 th percentile 24-hr storm depth from Figure B.1-1	d=	0.54	inches
2	Area tributary to BMP (s)	A=	2.60	acres
3	Area weighted runoff factor (estimate using Appendix B.1.1 and B.2.1)	C=	0.65	unitless
4	Street trees volume reduction	TCV=	0	cubic-feet
5	Rain barrels volume reduction	RCV=	0	cubic-feet
6	Calculate DCV = (3630 x C x d x A) – TCV - RCV	DCV=	3,426	cubic-feet

$$\text{AREA TRIBUTARY TO BMP (A)} = 113,286 \text{ SF SF} / 2.60 \text{ AC}$$

$$\text{TOTAL DMA SIZE (C} \times \text{A} \times \text{d)} = 76,136 \text{ SF}$$

$$\text{WEIGHTED RUNOFF FACTOR (C} \times \text{d)} = 0.65$$

$$\text{85TH PERCENTILE RAINFALL DEPTH (d)} = 0.54 \text{ INCHES}$$

$$\text{DCV (C} \times \text{d} \times \text{A} \times 3,630) = 3,426 \text{ CU. FT.}$$

Worksheet B.5-1: Simple Sizing Method for Biofiltration BMPs			DMA 1
Simple Sizing Method for Biofiltration BMPs		Worksheet B.5-1	
1	Remaining DCV after implementing retention BMPs	4764	cubic-feet
Partial Retention			
2	Infiltration rate from Worksheet D.5-1 if partial infiltration is feasible	0	in/hr
3	allowable drawdown time for aggregate storage below the underdrain	36	hours
4	Depth of runoff that can be infiltrated [Line 2 x Line 3]	0	inches
5	Aggregate pore space	0.4	in/in
6	Required depth of gravel below the underdrain [Line 4 / Line 5]	0	inches
7	Assumed surface area of biofiltration BMP	6010	sq-ft
8	Media Retained pore space	0.2	in/in
9	Volume retained by BMP [Line 4 + (Line 12 x Line 8)/12] x Line 7	1803	cubic-feet
10	DCV that requires biofiltration [Line 1 - Line 9]	2961	cubic-feet
BMP Parameters			
11	Surface Ponding [6in minimum, 12 inch maximum]	16	inches
12	Media Thickness [18 inches minimum]	18	inches
13	Aggregate Storage Above underdrain invert (12 inches typical) - use 0 inches for sizing if the aggregate is not over the entire bottom surface area	30	inches
14	Media available pore space	0.2	in/in
15	Media filtration rate to be used for sizing	5	in/hr
Baseline Calculations			
16	Allowable Routing Time for Sizing	6	hours
17	Depth filtered during storm [Line 15 x Line 16]	30	inches
18	Depth of detention storage [line 11 + (Line 12 Line 14) + (Line 13 x Line 5)]	31.6	inches
19	Total Depth Treated [Line 17 + Line 18]	37.6	inches
Option 1 - Biofilter 1.5 times the DVC			
20	Required biofiltrated volume [1.5 x Line 10]	4441.5	cubic-feet
21	Required Footprint [Line 20 / Line 19] x 12	1418	sq-ft
Option 2 - Store 0.75 of the remaining DCV in pores and ponding			
22	Required Storage (surface + pores) Volume [0.75 x Line 10]	2221	cubic-feet
23	Required Footprint [Line 22 / Line 18] x 12	538	sq-ft
Footprint of the BMP			
24	Area draining to the BMP	153962	sq-ft
25	Adjusted Runoff Factor for drainage area (Refere to Appendix B.1 and B.2)	0.74	
26	Minimum BMP Footprint [Line 24 x Line 25 X 0.03]	3418	sq-ft
27	Footprint of the BMP = Maximum(minimum(Line 21, Line 23), Line 26)	3418	sq-ft

Worksheet B.5-1: Simple Sizing Method for Biofiltration BMPs			DMA 2
Simple Sizing Method for Biofiltration BMPs		Worksheet B.5-1	
1	Remaining DCV after implementing retention BMPs	3426	cubic-feet
Partial Retention			
2	Infiltration rate from Worksheet D.5-1 if partial infiltration is feasible	0	in/hr
3	allowable drawdown time for aggregate storage below the underdrain	36	hours
4	Depth of runoff that can be infiltrated [Line 2 x Line 3]	0	inches
5	Aggregate pore space	0.4	in/in
6	Required depth of gravel below the underdrain [Line 4 / Line 5]	0	inches
7	Assumed surface area of biofiltration BMP	3030	sq-ft
8	Media Retained pore space	0.2	in/in
9	Volume retained by BMP [Line 4 + (Line 12 x Line 8)/12] x Line 7	909	cubic-feet
10	DCV that requires biofiltration [Line 1 - Line 9]	2517	cubic-feet
BMP Parameters			
11	Surface Ponding [6in minimum, 12 inch maximum]	18	inches
12	Media Thickness [18 inches minimum]	18	inches
13	Aggregate Storage Above underdrain invert (12 inches typical) - use 0 inches for sizing if the aggregate is not over the entire bottom surface area	15	inches
14	Media available pore space	0.2	in/in
15	Media filtration rate to be used for sizing	5	in/hr
Baseline Calculations			
16	Allowable Routing Time for Sizing	6	hours
17	Depth filtered during storm [Line 15 x Line 16]	30	inches
18	Depth of detention storage [line 11 + (Line 12 Line 14) + (Line 13 x Line 5)]	27.6	inches
19	Total Depth Treated [Line 17 + Line 18]	33.6	inches
Option 1 - Biofilter 1.5 times the DVC			
20	Required biofiltrated volume [1.5 x Line 10]	3775.5	cubic-feet
21	Required Footprint [Line 20 / Line 19] x 12	1348	sq-ft
Option 2 - Store 0.75 of the remaining DCV in pores and ponding			
22	Required Storage (surface + pores) Volume [0.75 x Line 10]	1888	cubic-feet
23	Required Footprint [Line 22 / Line 18] x 12	586	sq-ft
Footprint of the BMP			
24	Area draining to the BMP	113286	sq-ft
25	Adjusted Runoff Factor for drainage area (Refere to Appendix B.1 and B.2)	0.65	
26	Minimum BMP Footprint [Line 24 x Line 25 X 0.03]	2209	sq-ft
27	Footprint of the BMP = Maximum(minimum(Line 21, Line 23), Line 26)	2209	sq-ft

E.12 BF-1 Biofiltration



Location: 43rd Street and Logan Avenue, San Diego, California

MS4 Permit Category

Biofiltration

Manual Category

Biofiltration

Applicable Performance Standard

Pollutant Control

Flow Control

Primary Benefits

Treatment

Volume Reduction (Incidental)

Peak Flow Attenuation (Optional)


Description

Biofiltration (Bioretention with underdrain) facilities are vegetated surface water systems that filter water through vegetation, and soil or engineered media prior to discharge via underdrain or overflow to the downstream conveyance system. Bioretention with underdrain facilities are commonly incorporated into the site within parking lot landscaping, along roadsides, and in open spaces. Because these types of facilities have limited or no infiltration, they are typically designed to provide enough hydraulic head to move flows through the underdrain connection to the storm drain system. Treatment is achieved through filtration, sedimentation, sorption, biochemical processes and plant uptake.


Typical bioretention with underdrain components include:

- Inflow distribution mechanisms (e.g, perimeter flow spreader or filter strips)
- Energy dissipation mechanism for concentrated inflows (e.g., splash blocks or riprap)
- Shallow surface ponding for captured flows
- Side slope and basin bottom vegetation selected based on expected climate and ponding depth
- Non-floating mulch layer (Optional)
- Media layer (planting mix or engineered media) capable of supporting vegetation growth
- Filter course layer consisting of aggregate to prevent the migration of fines into uncompacted native soils or the aggregate storage layer
- Aggregate storage layer with underdrain(s)
- Impermeable liner or uncompacted native soils at the bottom of the facility

- Overflow structure



PLAN
NOT TO SCALE



SECTION A-A'
NOT TO SCALE

Typical plan and Section view of a Biofiltration BMP

Design Adaptations for Project Goals

Biofiltration Treatment BMP for stormwater pollutant control. The system is lined or un-lined to provide incidental infiltration, and an underdrain is provided at the bottom to carry away filtered runoff. This configuration is considered to provide biofiltration treatment via flow through the media layer. Storage provided above the underdrain within surface ponding, media, and aggregate storage is considered included in the biofiltration treatment volume. Saturated storage within the aggregate storage layer can be added to this design by raising the underdrain above the bottom of the aggregate storage layer or via an internal weir structure designed to maintain a specific water level elevation.

Integrated stormwater flow control and pollutant control configuration. The system can be designed to provide flow rate and duration control by primarily providing increased surface ponding and/or having a deeper aggregate storage layer above the underdrain. This will allow for significant detention storage, which can be controlled via inclusion of an outlet structure at the downstream end of the underdrain.

Design Criteria and Considerations

Bioretention with underdrain must meet the following design criteria. Deviations from the below criteria may be approved at the discretion of the City Engineer if it is determined to be appropriate:

<i>Siting and Design</i>	<i>Intent/Rationale</i>
☐ Placement observes geotechnical recommendations regarding potential hazards (e.g., slope stability, landslides, liquefaction zones) and setbacks (e.g., slopes, foundations, utilities).	Must not negatively impact existing site geotechnical concerns.
☐ An impermeable liner or other hydraulic restriction layer is included if site constraints indicate that infiltration or lateral flows should not be allowed.	Lining prevents stormwater from impacting groundwater and/or sensitive environmental or geotechnical features. Incidental infiltration, when allowable, can aid in pollutant removal and groundwater recharge.
☐ Contributing tributary area shall be ≤ 5 acres (≤ 1 acre preferred).	Bigger BMPs require additional design features for proper performance. Contributing tributary area greater than 5 acres may be allowed at the discretion of the City Engineer if the following conditions are met: 1) incorporate design features (e.g. flow spreaders) to

<i>Siting and Design</i>	<i>Intent/Rationale</i>
	minimizing short circuiting of flows in the BMP and 2) incorporate additional design features requested by the City Engineer for proper performance of the regional BMP.
☐ Finish grade of the facility is $\leq 2\%$.	Flatter surfaces reduce erosion and channelization within the facility.
<i>Surface Ponding</i>	
☐ Surface ponding is limited to a 24-hour drawdown time.	Surface ponding limited to 24 hour for plant health.
☐ Surface ponding depth is ≥ 6 and ≤ 12 inches.	Surface ponding capacity lowers subsurface storage requirements. Deep surface ponding raises safety concerns.
	Surface ponding depth greater than 12 inches (for additional pollutant control or surface outlet structures or flow-control orifices) may be allowed at the discretion of the City Engineer if the following conditions are met: 1) surface ponding depth drawdown time is less than 24 hours; and 2) safety issues and fencing requirements are considered (typically ponding greater than 18" will require a fence and/or flatter side slopes) and 3) potential for elevated clogging risk is considered.
☐ A minimum of 2 inches of freeboard is provided.	Freeboard provides room for head over overflow structures and minimizes risk of uncontrolled surface discharge.
☐ Side slopes are stabilized with vegetation and are = 3H:1V or shallower.	Gentler side slopes are safer, less prone to erosion, able to establish vegetation more quickly and easier to maintain.
<i>Vegetation</i>	
☐ Plantings are suitable for the climate and expected ponding depth. A plant list to aid in selection can be found in Appendix E.20.	Plants suited to the climate and ponding depth are more likely to survive.

<i>Siting and Design</i>	<i>Intent/Rationale</i>
☐ An irrigation system with a connection to water supply should be provided as needed.	Seasonal irrigation might be needed to keep plants healthy.
<i>Mulch (Optional or Mandatory – Dependent on jurisdiction)</i>	
☐ A minimum of 3 inches of well-aged, shredded hardwood mulch that has been stockpiled or stored for at least 12 months is provided.	Mulch will suppress weeds and maintain moisture for plant growth. Aging mulch kills pathogens and weed seeds and allows the beneficial microbes to multiply.
<i>Media Layer</i>	
☐ Media maintains a minimum filtration rate of 5 in/hr over lifetime of facility. An initial filtration rate of 8 to 12 in/hr is recommended to allow for clogging over time; the initial filtration rate should not exceed 12 inches per hour.	A filtration rate of at least 5 inches per hour allows soil to drain between events. The initial rate should be higher than long term target rate to account for clogging over time. However an excessively high initial rate can have a negative impact on treatment performance, therefore an upper limit is needed.
☐ Media is a minimum 18 inches deep, meeting either of these two media specifications: City of San Diego Low Impact Development Design Manual (page B-18) (July 2011, unless superseded by more recent edition) or County of San Diego Low Impact Development Handbook: Appendix G -Bioretention Soil Specification (June 2014, unless superseded by more recent edition). Alternatively, for proprietary designs and custom media mixes not meeting the media specifications contained in the City or County LID Manual, the media meets the pollutant treatment performance criteria in Section F.1.	A deep media layer provides additional filtration and supports plants with deeper roots. Standard specifications shall be followed. For non-standard or proprietary designs, compliance with F.1 ensures that adequate treatment performance will be provided.
☐ Media surface area is 3% of contributing area times adjusted runoff factor or greater.	Greater surface area to tributary area ratios: a) maximizes volume retention as required by the MS4 Permit and b) decrease loading rates per square foot and therefore increase longevity. Adjusted runoff factor is to account for site design BMPs implemented upstream of the BMP (such as rain barrels,

<i>Siting and Design</i>	<i>Intent/Rationale</i>
☐ Where receiving waters are impaired or have a TMDL for nutrients, the system is designed with nutrient sensitive media design (see fact sheet BF-2).	impervious area dispersion, etc.). Refer to Appendix B.2 guidance. Use Worksheet B.5-1 Line 26 to estimate the minimum surface area required per this criteria. Potential for pollutant export is partly a function of media composition; media design must minimize potential for export of nutrients, particularly where receiving waters are impaired for nutrients.
<i>Filter Course Layer</i>	
☐ A filter course is used to prevent migration of fines through layers of the facility. Filter fabric is not used.	Migration of media can cause clogging of the aggregate storage layer void spaces or subgrade. Filter fabric is more likely to clog.
☐ Filter course is washed and free of fines.	Washing aggregate will help eliminate fines that could clog the facility and impede infiltration.
☐ Filter course calculations assessing suitability for particle migration prevention have been completed.	Gradation relationship between layers can evaluate factors (e.g., bridging, permeability, and uniformity) to determine if particle sizing is appropriate or if an intermediate layer is needed.
<i>Aggregate Storage Layer</i>	
☐ Class 2 Permeable per Caltrans specification 68-1.025 is recommended for the storage layer. Washed, open-graded crushed rock may be used, however a 4-6 inch washed pea gravel filter course layer at the top of the crushed rock is required.	Washing aggregate will help eliminate fines that could clog the aggregate storage layer void spaces or subgrade.
☐ The depth of aggregate provided (12-inch typical) and storage layer configuration is adequate for providing conveyance for underdrain flows to the outlet structure.	Proper storage layer configuration and underdrain placement will minimize facility drawdown time.
<i>Inflow, Underdrain, and Outflow Structures</i>	
☐ Inflow, underdrains and outflow structures are accessible for inspection and maintenance.	Maintenance will prevent clogging and ensure proper operation of the flow

<i>Siting and Design</i>	<i>Intent/Rationale</i>
	control structures.
☐ Inflow velocities are limited to 3 ft/s or less or use energy dissipation methods. (e.g., riprap, level spreader) for concentrated inflows.	High inflow velocities can cause erosion, scour and/or channeling.
☐ Curb cut inlets are at least 12 inches wide, have a 4-6 inch reveal (drop) and an apron and energy dissipation as needed.	Inlets must not restrict flow and apron prevents blockage from vegetation as it grows in. Energy dissipation prevents erosion.
☐ Underdrain outlet elevation should be a minimum of 3 inches above the bottom elevation of the aggregate storage layer.	A minimal separation from subgrade or the liner lessens the risk of fines entering the underdrain and can improve hydraulic performance by allowing perforations to remain unblocked.
☐ Minimum underdrain diameter is 6 inches.	Smaller diameter underdrains are prone to clogging.
☐ Underdrains are made of slotted, PVC pipe conforming to ASTM D 3034 or equivalent or corrugated, HDPE pipe conforming to AASHTO 252M or equivalent.	Slotted underdrains provide greater intake capacity, clog resistant drainage, and reduced entrance velocity into the pipe, thereby reducing the chances of solids migration.
☐ An underdrain cleanout with a minimum 6-inch diameter and lockable cap is placed every 250 to 300 feet as required based on underdrain length.	Properly spaced cleanouts will facilitate underdrain maintenance.
☐ Overflow is safely conveyed to a downstream storm drain system or discharge point. Size overflow structure to pass 100-year peak flow for on-line infiltration basins and water quality peak flow for off-line basins.	Planning for overflow lessens the risk of property damage due to flooding.

Conceptual Design and Sizing Approach for Stormwater Pollutant Control Only

To design bioretention with underdrain for stormwater pollutant control only (no flow control required), the following steps should be taken:

1. Verify that siting and design criteria have been met, including placement requirements, contributing tributary area, maximum side and finish grade slopes, and the recommended media surface area tributary ratio.
2. Calculate the DCV per Appendix B based on expected site design runoff for tributary areas.

3. Use the sizing worksheet presented in Appendix B.5 to size biofiltration BMPs.

Conceptual Design and Sizing Approach when Stormwater Flow Control is Applicable

Control of flow rates and/or durations will typically require significant surface ponding and/or aggregate storage volumes, and therefore the following steps should be taken prior to determination of stormwater pollutant control design. Pre-development and allowable post-project flow rates and durations should be determined as discussed in Chapter 6 of the manual.

1. Verify that siting and design criteria have been met, including placement requirements, contributing tributary area, maximum side and finish grade slopes, and the recommended media surface area tributary ratio.
2. Iteratively determine the facility footprint area, surface ponding and/or aggregate storage layer depth required to provide detention storage to reduce flow rates and durations to allowable limits. Flow rates and durations can be controlled from detention storage by altering outlet structure orifice size(s) and/or water control levels. Multi-level orifices can be used within an outlet structure to control the full range of flows.
3. If bioretention with underdrain cannot fully provide the flow rate and duration control required by this manual, an upstream or downstream structure with significant storage volume such as an underground vault can be used to provide remaining controls.
4. After bioretention with underdrain has been designed to meet flow control requirements, calculations must be completed to verify if stormwater pollutant control requirements to treat the DCV have been met.

ATTACHMENT 2 - BACKUP FOR PDP HYDROMODIFICATION CONTROL MEASURES

This is the cover sheet for Attachment 2.

- ☐ Mark this box if this attachment is not included because the project is exempt from PDP hydromodification management requirements.

Indicate which items are included behind this cover sheet:

Attachment	Contents	Checklist
Attachment 2a	Hydromodification Management Exhibit (Required)	☒ Included See Hydromodification Management Exhibit Checklist on the back of this Attachment cover sheet.
Attachment 2b	Management of Critical Coarse Sediment Yield Areas (WMAA Exhibit is required, additional analyses are optional) See Section 6.2 of the BMP Design Manual.	☒ Exhibit showing project drainage boundaries marked on WMAA Critical Coarse Sediment Yield Area Map (Required) Optional analyses for Critical Coarse Sediment Yield Area Determination ☐ 6.2.1 Verification of Geomorphic Landscape Units Onsite ☐ 6.2.2 Downstream Systems Sensitivity to Coarse Sediment ☐ 6.2.3 Optional Additional Analysis of Potential Critical Coarse Sediment Yield Areas Onsite
Attachment 2c	Geomorphic Assessment of Receiving Channels (Optional) See Section 6.3.4 of the BMP Design Manual.	☐ Not performed ☒ Included ☐ Submitted as separate stand-alone document
Attachment 2d	Flow Control Facility Design, including Structural BMP Drawdown Calculations and Overflow Design Summary (Required) See Chapter 6 and Appendix G of the BMP Design Manual	☐ Included ☒ Submitted as separate stand-alone document
Attachment 2e	Vector Control Plan (Required when structural BMPs will not drain in 96 hours)	☐ Included ☒ Not required because BMPs will drain in less than 96 hours

Use this checklist to ensure the required information has been included on the Hydromodification Management Exhibit:

The Hydromodification Management Exhibit must identify:

- ☒ Underlying hydrologic soil group
- ☒ Approximate depth to groundwater
- ☐ Existing natural hydrologic features (watercourses, seeps, springs, wetlands)
- ☒ Critical coarse sediment yield areas to be protected
- ☒ Existing topography
- ☒ Existing and proposed site drainage network and connections to drainage offsite
- ☒ Proposed grading
- ☒ Proposed impervious features
- ☒ Proposed design features and surface treatments used to minimize imperviousness
- ☒ Point(s) of Compliance (POC) for Hydromodification Management
- ☒ Existing and proposed drainage boundary and drainage area to each POC (when necessary, create separate exhibits for pre-development and post-project conditions)
- ☒ Structural BMPs for hydromodification management (identify location, type of BMP, and size/detail)

MATCHLINE: SEE SHEET 2 FOR CONTINUATION



PLAN VIEW - HYDROMODIFICATION EXHIBIT

SCALE: 1" = 20' HORIZONTAL

GROUNDWATER INFORMATION

GROUNDWATER NOT ENCOUNTERED DURING SITE INVESTIGATION. AND EXPECTED AT DEPTHS GREATER THAN 50 FEET BELOW EXISTING GRADES PER "STORM WATER MANAGEMENT INVESTIGATION" PREPARED BY GEOCON, INC. DATED 1/8/21

COARSE SEDIMENT YIELD

NO CRITICAL COARSE SEDIMENT YIELD AREAS TO BE PROTECTED ONSITE OR UPSTREAM OF SUBJECT PROPERTY. REFER TO DISCUSSION IN PRIORITY DEVELOPMENT PROJECT SWQMP PREPARED BY PASCO, LARET, SUITER & ASSOCIATES

SELF-MITIGATING DMA - DMA W

TOTAL BASIN SIZE = 184 SF (0.004 AC)
 SELF-MITIGATING IMPERVIOUS AREA = 0 SF
 % IMPERVIOUS = 0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

SELF-MITIGATING DMA - DMA X

TOTAL BASIN SIZE = 811 SF (0.019 AC)
 SELF-MITIGATING IMPERVIOUS AREA = 0 SF
 % IMPERVIOUS = 0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

SELF-MITIGATING DMA - DMA Y

TOTAL BASIN SIZE = 843 SF (0.019 AC)
 SELF-MITIGATING IMPERVIOUS AREA = 0 SF
 % IMPERVIOUS = 0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

SELF-MITIGATING DMA - DMA Z

TOTAL BASIN SIZE = 2,943 SF (0.067 AC)
 SELF-MITIGATING IMPERVIOUS AREA = 0 SF
 % IMPERVIOUS = 0.0%

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-MITIGATING DMA AREAS THAT DRAIN DIRECTLY OFFSITE OR TO THE PUBLIC STORM DRAIN SYSTEM, WITH INCIDENTAL IMPERVIOUS AREAS THAT ARE LESS THAN 5% OF THE SELF-MITIGATING AREA.

LEGEND

PROPERTY BOUNDARY	---
CENTERLINE OF ROAD	---
RIGHT-OF-WAY	---
ADJACENT PROPERTY LINE	---
EXISTING CONTOUR LINE	---
PROPOSED CONTOUR LINE	---
DMA DRAINAGE BASIN BOUNDARY	---
PROPOSED / REMOVED AND REPLACED IMPERVIOUS AREA WITHIN DISTURBED AREA OF SITE	---
BMP / BIOFILTRATION BASIN AREA	---
SELF-MITIGATING AREA PER BMP DESIGN MANUAL SECTION 5.2.1	---
POINT OF COMPLIANCE	---

PROJECT SITE AREA CALCULATIONS

TOTAL GROSS SITE AREA	289,479 SF (6.646 AC)
AREA DISTURBED BY PROJECT	273,457 SF (6.278 AC)
EXISTING IMPERVIOUS AREA	39,852 SF (0.915 AC)
EXISTING PERVIOUS AREA	231,129 SF (5.306 AC)
TOTAL DMA AREA (DMA A)	153,962 SF (3.53 AC)
TOTAL DMA AREA (DMA B)	114,153 SF (2.62 AC)
TOTAL DMA AREA (DMA C)	432 SF (0.001 AC)
TOTAL DMA AREA (DMA D)	243 SF (0.006 AC)
TOTAL SELF-MITIGATING DMA AREAS	4,667 SF (0.11 AC)
TOTAL PROPOSED IMPERVIOUS AREA	151,866 SF (3.48 AC)
**15% LOT HARDSCAPE CONTINGENCY	22,744 SF (0.52 AC)
ASSUMED TOTAL IMPERVIOUS AREA	174,610 SF (4.01 AC)
TOTAL PROPOSED PERVIOUS AREA	98,847 SF (2.27 AC)
**15% FUTURE LOT HARDSCAPE CONTINGENCY BASED ON ROOF AREA AND PRIVATE WALKWAYS / PATIOS, EXCLUSIVE OF PRIVATE ROAD, SIDEWALK, AND PRIVATE DRIVEWAYS; RESULTS IN 500 SF OF FUTURE HARDSCAPE ALLOTTED TO EACH LOT	

SELF-RETAINING DMA - DMA C

TOTAL BASIN SIZE	= 432 SF (0.010 AC)
SELF-RETAINING IMPERVIOUS AREA	= 432 SF
RATIO OF DMA AREA TO PERV. PAVEMENT AREA	= 1:1

SECTION 5.2.1 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR SELF-RETAINING PERVIOUS PAVEMENT DMAS THAT RETAIN RUNOFF TO A LEVEL DETERMINED TO CONSTITUTE FULL RETENTION OF THE ENTIRE DCV. PERVIOUS PAVEMENTS THAT HAVE A RATIO OF 1:1 OR LESS FOR TOTAL DRAINAGE AREA TO AREA OF PERVIOUS PAVEMENTS CAN BE CONSIDERED SELF-RETAINING.

DE MINIMIS DMA - DMA D

TOTAL BASIN SIZE	= 243 SF (0.006 AC)
------------------	---------------------


SECTION 5.2.2 OF CITY OF ENCINITAS BMP DESIGN MANUAL ALLOWS FOR DE MINIMIS AREAS THAT ARE LESS THAN 250 SF AND ALL DE MINIMIS AREAS FOR THE SITE ARE LESS THAN 2 PERCENT OF THE TOTAL REMOVED OR REPLACED IMPERVIOUS AREA

SOIL TYPE INFORMATION


SOIL: TYPE D SOILS FOR VERY OLD PARALIC DEPOSITS TOPSOIL PER "STORM WATER MANAGEMENT INVESTIGATION" REPORT PREPARED BY GEOCON, INC. DATED 7/16/21; (TYPE B HYDROLOGIC SOILS PER WEB SOIL SURVEY APPLICATION AVAILABLE THROUGH UNITED STATES DEPARTMENT OF AGRICULTURE)


TREATMENT CONTROL BMPs

BIOFILTRATION WITH IMPERVIOUS LINER	BF-1
-------------------------------------	------




ATTACHMENT 2a
 HYDROMODIFICATION EXHIBIT
 1220-1240 MELBA ROAD
 CITY OF ENCINITAS






TYPICAL SECTION - BIOFILTRATION BASIN A
NOT TO SCALE

*BIOFILTRATION "ENGINEERED SOIL" LAYER SHALL BE EVENLY MIXED COMPOSITION OF WASHED SAND, SANDY LOAM TOPSOIL, AND HUMIC COMPOST. THE MIX SHALL CONTAIN 65% SAND, 20% TOPSOIL, AND 15% COMPOST OR HARDWOOD MULCH IN ACCORDANCE WITH COUNTY OF SAN DIEGO LID BIOSWALE MEDIA




NOTE:
-ALL AGGREGATE MUST BE CLEANWASHED AND FREE OF FINES (SAND, SILT, ETC.)
-THE PAVERS SHALL NOT BE SEALED ONCE THE VOID FILLER HAS BEEN ADDED
-EACH COURSE SHALL BE VIBRATORY COMPACTED BEFORE PLACEMENT OF NEXT COURSE
-NO IMPERVIOUS LINER OR FILTER FABRIC IS TO BE USED
-SPECIAL APPROVAL REQUIRED FOR USE IN HIGHLY EXPANSIVE SOIL-SUBDRAIN MAY BE REQUIRED

TYPICAL DETAIL - PERVIOUS PAVERS
NOT TO SCALE



TYPICAL DETAIL - FLOW CONTROL ORIFICE PLATE
NOT TO SCALE



TYPICAL SECTION - BIOFILTRATION BASIN B
NOT TO SCALE

*BIOFILTRATION "ENGINEERED SOIL" LAYER SHALL BE EVENLY MIXED COMPOSITION OF WASHED SAND, SANDY LOAM TOPSOIL, AND HUMIC COMPOST. THE MIX SHALL CONTAIN 65% SAND, 20% TOPSOIL, AND 15% COMPOST OR HARDWOOD MULCH IN ACCORDANCE WITH COUNTY OF SAN DIEGO LID BIOSWALE MEDIA

ATTACHMENT 2a
DRAINAGE MANAGEMENT AREA CALCS
1220-1240 MELBA ROAD
CITY OF ENCINITAS

Attachment 2d.1 – SWMM / Hydromodification Analysis Discussion

DRAFT

SWMM / Hydromodification Analysis / Discussion

2d.2.1 Hydromodification Analysis

To satisfy the requirements of the MS4 Permit, a hydromodification management strategy has been developed for the project based on the Final Hydromodification Management Plan dated March 2011 (Final HMP). A continuous simulation model, the Storm Water Management Model (SWMM) version 5.1 by the Environmental Protection Agency (EPA) was selected to size mitigation measures. The SWMM model is capable of modeling hydromodification management facilities to mitigate the effects of increased runoff from the post-development conditions and use changes that may cause negative impacts (i.e. erosion) to downstream channels.

2d.2.2 Hydromodification Criteria

Pursuant to the MS4 Permit, post-development runoff conditions (flow rates and durations) must not exceed pre-development runoff conditions by more than 10% (for the range of flows that result in increased potential for erosion, or degraded instream habitat downstream of the project. Based on the Final HMP:

- For flow rates between the pre-project lower threshold (10%, 30%, or 50%) of the pre-project 2-year runoff event ($0.1Q_2$, $0.3Q_2$, or $0.5Q_2$) to the pre-project 10-year event (Q_{10}), the post-project discharge rates and durations may not deviate above the pre-project rates and durations by more than 10% over more than 10% of the length of the flow duration curve.

A channel screening analysis may be performed to determine a larger lower flow threshold. However, at this time a low flow threshold of $0.1Q_2$ (high susceptibility) is assumed for erosion of the downstream channel.

5.1.2 SWMM Model Development

SWMM is a rainfall-runoff model used for single event or continuous simulation of runoff quantity from primarily urban areas. SWMM calculates and routes runoff based on user-specified input including precipitation data, subcatchment characteristics, soil data, routing information, and BMP configuration. SWMM is capable of modeling various hydrologic processes including but not limited to time-varying precipitation, evaporation, storage, infiltration, and retention LID facilities.

5.1.3 SWMM Input

A pre-development and post-development model were created using the following global information:

Parameter	Input	Source
Precipitation	Oceanside Rainfall Data	Project Clean Water
Evaporation	Encinitas ETo Zone Data	CIMIS ETo Zones Map
Soils	B	Field Infiltration / Testing Methods

Each HMP flow-control biofiltration facility consists of a basin with surface area square footage per plan, 18 inches of engineered soil and as well as a storage layer consisting of gravel or Permavoid, along with an impermeable liner to prevent infiltration. Runoff generated during high-frequency, low-intensity storm events will be biofiltered through the engineered soil and gravel layers, then collected in a series of small PVC drainpipes and directed to an emergency overflow / outlet structure located in the biofiltration basin. Runoff will be mitigated into the outlet structure via a restrictor plate with an HMP low-flow orifice, restricting flow to meet hydromodification management requirements. In larger storm events, runoff not filtered through the engineered soil and gravel layers will be conveyed via an overflow outlet structure consisting of a 3-foot by 3-foot grate located on top of the catch basin. Runoff conveyed via the outlet structure will bypass the soil layers and be conveyed directly to a proposed 12-inch PVC drainpipe to direct discharge offsite. Refer to Attachment 2d.2 of this Storm Water Quality Management Plan (SWQMP) for a general cross-section of the HMP biofiltration basin and additional results of the hydromodification management compliance analysis.

Each HMP biofiltration basin has been designed to comply with both pollutant control and hydromodification management criteria. The HMP biofiltration portion in the SWMM model is specified as an “LID Control” within the “Subcatchment” to define the ponding depth, bioretention soil layer, gravel layer, and low flow orifice restrictor.

5.1.4 SWMM Processing and Output

The HMP sizing was determined assuming a completely pervious existing site condition. The pre-development project $0.1Q_2$ and Q_{10} were determined to be 0.025 cfs and 0.493 cfs, respectively for POC-1, 0.058 cfs and 1.12 cfs for POC-2, and 0.13 cfs and 2.52 cfs for POC-3. After routing through each HMP biofiltration basin, the post-development, mitigated project $0.1Q_2$ and Q_{10} were determined to be 0.002 cfs and 0.345 cfs, respectively for POC-1, 0.005 cfs and 0.94 cfs for POC-2, and 0.05 cfs and 2.11 cfs for POC-3. Additional information and data from the SWMM model including input files, rain gage and evaporation data, and flow duration and frequency curves are included hereon.

5.2 Storm Water Pollutant Control

To meet the requirements of the MS4 Permit, the HMP biofiltration facility is designed to treat onsite storm water pollutants contained in the volume of runoff from a 24-hour, 85th percentile storm event by slowly infiltrating runoff through an engineered soil layer and gravel layer.

5.2.1 Numeric Sizing Requirements for Pollutant Control BMPs

Pursuant to the MS4 Permit, Pollutant Control BMPs shall be designed to retain onsite pollutants contained in the post-development Design Capture Volume (DCV). The DCV is the volume of runoff resulting from the 24-hour, 85th percentile storm event. The DCV calculations for the project are located in Attachment 1 of the project’s Storm Water Quality Management Plan (SWQMP). The Pollutant Control BMP proposed for the project is a biofiltration basin. Each proposed HMP biofiltration basin does not provide infiltration, therefore pursuant to the MS4 Permit and Appendix B.5 of the BMP Design Manual, each HMP biofiltration basin is designed to biofilter 1.5 times the DCV or store 0.75 times the DCV in pores and ponding.

Attachment 2d.2 – Additional SWMM Support Documentation

DRAFT

[TITLE]
;;Project Title/Notes
3086 Staver Melba
Pre-Development Condition

[OPTIONS]
;;Option Value
FLOW_UNITS CFS
INFILTRATION GREEN AMPT
FLOW_ROUTING KINWAVE
LINK_OFFSETS DEPTH
MIN_SLOPE 0
ALLOW_PONDING NO
SKIP_STEADY_STATE NO

START_DATE 08/28/1951
START_TIME 05:00:00
REPORT_START_DATE 08/28/1951
REPORT_START_TIME 05:00:00
END_DATE 05/23/2008
END_TIME 23:00:00
SWEEP_START 01/01
SWEEP_END 12/31
DRY_DAYS 0
REPORT_STEP 01:00:00
WET_STEP 00:15:00
DRY_STEP 04:00:00
ROUTING_STEP 0:01:00
RULE_STEP 00:00:00

INERTIAL_DAMPING PARTIAL
NORMAL_FLOW_LIMITED BOTH
FORCE_MAIN_EQUATION H-W
VARIABLE_STEP 0.75
LENGTHENING_STEP 0
MIN_SURFAREA 12.557
MAX_TRIALS 8
HEAD_TOLERANCE 0.005
SYS_FLOW_TOL 5
LAT_FLOW_TOL 5
MINIMUM_STEP 0.5
THREADS 1

[EVAPORATION]
;;Data Source Parameters
;;-----
MONTHLY .06 .08 .11 .15 17 .19 .19 .18 .15 .11 .08 .06
DRY_ONLY YES

[RAINGAGES]

```

;;Name      Format      Interval SCF      Source
;;-----
OCEANSIDE   INTENSITY 1:00      1.0      TIMESERIES OCEANSIDE

[SUBCATCHMENTS]
;;Name      Rain Gage      Outlet      Area      %Imperv      Width      %Slope      CurbLen      SnowPack
;;-----
DMA-A       OCEANSIDE      POC-1      2.92      0      560      6      0
DMA-B       OCEANSIDE      POC-2      2.6      0      399      5.5      0

[SUBAREAS]
;;Subcatchment      N-Imperv      N-Perv      S-Imperv      S-Perv      PctZero      RouteTo      PctRouted
;;-----
DMA-A       0.012      0.08      0.05      0.1      25      OUTLET
DMA-B       0.012      0.08      0.05      0.1      25      OUTLET

[INFILTRATION]
;;Subcatchment      Param1      Param2      Param3      Param4      Param5
;;-----
DMA-A       9      0.025      0.33      7      0
DMA-B       9      0.025      0.33      7      0

[OUTFALLS]
;;Name      Elevation      Type      Stage Data      Gated      Route To
;;-----
;Basin 200
POC-1       0      FREE      NO
POC-2       0      FREE      NO

[TIMESERIES]
;;Name      Date      Time      Value
;;-----
OCEANSIDE   FILE "Rainfall_data\oceanside.dat"

[REPORT]
;;Reporting Options
SUBCATCHMENTS ALL
NODES ALL
LINKS ALL

[TAGS]

[MAP]
DIMENSIONS -905.312 0.000 10000.000 10000.000
Units      None

[COORDINATES]
;;Node      X-Coord      Y-Coord
;;-----
POC-1       -836.352      5783.905

```

POC-2 501.045 5898.837

[VERTICES]

;;Link	X-Coord	Y-Coord
;;-----		

[Polygons]

;;Subcatchment	X-Coord	Y-Coord
;;-----		

DMA-A	-805.007	7507.893
DMA-B	542.839	7539.239

[SYMBOLS]

;;Gage	X-Coord	Y-Coord
;;-----		

OCEANSIDE	-18.514	8498.329
-----------	---------	----------

DRAFT

[TITLE]
;;Project Title/Notes
3086 Staver Melba
Post-Project Condition

[OPTIONS]
;;Option Value
FLOW_UNITS CFS
INFILTRATION GREEN_AMPT
FLOW_ROUTING KINWAVE
LINK_OFFSETS DEPTH
MIN_SLOPE 0
ALLOW_PONDING NO
SKIP_STEADY_STATE NO

START_DATE 08/28/1951
START_TIME 05:00:00
REPORT_START_DATE 08/28/1951
REPORT_START_TIME 05:00:00
END_DATE 05/23/2008
END_TIME 23:00:00
SWEEP_START 01/01
SWEEP_END 12/31
DRY_DAYS 0
REPORT_STEP 01:00:00
WET_STEP 00:15:00
DRY_STEP 04:00:00
ROUTING_STEP 0:01:00
RULE_STEP 00:00:00

INERTIAL_DAMPING PARTIAL
NORMAL_FLOW_LIMITED BOTH
FORCE_MAIN_EQUATION H-W
VARIABLE_STEP 0.75
LENGTHENING_STEP 0
MIN_SURFAREA 12.557
MAX_TRIALS 8
HEAD_TOLERANCE 0.005
SYS_FLOW_TOL 5
LAT_FLOW_TOL 5
MINIMUM_STEP 0.5
THREADS 1

[EVAPORATION]
;;Data Source Parameters
;;-----
MONTHLY .06 .08 .11 .15 17 .19 .19 .18 .15 .11 .08 .06
DRY_ONLY YES

[RAINGAGES]
;;Name Format Interval SCF Source

```

;;-----
OCEANSIDE      INTENSITY 1:00      1.0      TIMESERIES OCEANSIDE

```

[SUBCATCHMENTS]

```

;;Name      Rain Gage      Outlet      Area      %Imperv      Width      %Slope      CurbLen      SnowPack
;;-----
DMA-A      OCEANSIDE      BMP-A      3.392      70      2081      4      0
DMA-Z      OCEANSIDE      POC-1      0.067      0      117      13      0
BMP-A      OCEANSIDE      DIV-A      0.13797      0      120      0      0
DMA-B      OCEANSIDE      BMP-B      2.53      64      2205      3      0
BMP-B      OCEANSIDE      DIV-B      0.06956      0      61      0      0
DMA-V      OCEANSIDE      POC-2      0.022      0      192      50      0

```

[SUBAREAS]

```

;;Subcatchment      N-Imperv      N-Perv      S-Imperv      S-Perv      PctZero      RouteTo      PctRouted
;;-----
DMA-A      0.012      0.06      0.05      0.1      25      OUTLET
DMA-Z      0.012      0.06      0.05      0.1      25      OUTLET
BMP-A      0.012      0.06      0.05      0.1      25      OUTLET
DMA-B      0.012      0.06      0.05      0.1      25      OUTLET
BMP-B      0.012      0.06      0.05      0.1      25      OUTLET
DMA-V      0.012      0.06      0.05      0.1      25      OUTLET

```

[INFILTRATION]

```

;;Subcatchment      Param1      Param2      Param3      Param4      Param5
;;-----
DMA-A      9      0.019      0.33      7      0
DMA-Z      9      0.019      0.33      7      0
BMP-A      9      0.025      0.33      7      0
DMA-B      9      0.019      0.33      7      0
BMP-B      9      0.025      0.33      7      0
DMA-V      9      0.019      0.33      7      0

```

[LID_CONTROLS]

```

;;Name      Type/Layer      Parameters
;;-----
BMP-A      BC
BMP-A      SURFACE      6      0      0      0      5
BMP-A      SOIL      21      0.4      0.2      0.1      5      5      1.5
BMP-A      STORAGE      33      0.67      0      0      NO
BMP-A      DRAIN      0.1541      0.5      3      6      0      0

BMP-B      BC
BMP-B      SURFACE      6      0      0      0      5
BMP-B      SOIL      21      0.4      0.2      0.1      5      5      1.5
BMP-B      STORAGE      78      0.99      0      0      NO
BMP-B      DRAIN      0.3148      0.5      3      6      0      0

```

[LID_USAGE]

```

;;Subcatchment      LID Process      Number      Area      Width      InitSat      FromImp      ToPerv      RptFile      DrainTo
FromPerv

```

```

;;-----
BMP-A      BMP-A      1      6009.97  0      0      100      0      *      *
0
BMP-B      BMP-B      1      3030.03  0      0      100      0      *      *
0

[OUTFALLS]
;;Name      Elevation  Type      Stage Data      Gated      Route To
;;-----
POC-1      0      FREE      NO
POC-2      0      FREE      NO

[DIVIDERS]
;;Name      Elevation  Diverted Link      Type      Parameters
;;-----
DIV-B      0      BYPASS-B      CUTOFF      0.224      0      0      0      0
DIV-A      0      BYPASS-A      CUTOFF      0.164      0      0      0      0

[STORAGE]
;;Name      Elev.      MaxDepth  InitDepth  Shape      Curve Type/Params      SurDepth  Fevap      Psi      Ksat      IMD
;;-----
STOR-B      0      1.5      0      TABULAR      STOR-B      0      0
STOR-A      0      1.5      0      TABULAR      STOR-A      0      0

[CONDUITS]
;;Name      From Node      To Node      Length      Roughness  InOffset      OutOffset      InitFlow      MaxFlow
;;-----
BYPASS-B      DIV-B      STOR-B      400      0.01      0      0      0      0
LOWFLOW-B      DIV-B      POC-2      400      0.01      0      0      0      0
LOWFLOW-A      DIV-A      POC-1      400      0.01      0      0      0      0
BYPASS-A      DIV-A      STOR-A      400      0.01      0      0      0      0

[OUTLETS]
;;Name      From Node      To Node      Offset      Type      QTable/Qcoeff      Qexpon      Gated
;;-----
OUTLET-A      STOR-A      POC-1      0      TABULAR/DEPTH      OUTLET-A      NO
OUTLET-B      STOR-B      POC-2      0      TABULAR/DEPTH      OUTLET-B      NO

[XSECTIONS]
;;Link      Shape      Geom1      Geom2      Geom3      Geom4      Barrels      Culvert
;;-----
BYPASS-B      DUMMY      0      0      0      0      1
LOWFLOW-B      DUMMY      0      0      0      0      1
LOWFLOW-A      DUMMY      0      0      0      0      1
BYPASS-A      DUMMY      0      0      0      0      1

[CURVES]
;;Name      Type      X-Value      Y-Value
;;-----
OUTLET-A      Rating      0      0

```

OUTLET-A	0.05	0.11
OUTLET-A	0.1	0.32
OUTLET-A	0.15	0.59
OUTLET-A	0.2	0.91
OUTLET-A	0.25	1.27
OUTLET-A	0.3	1.56
OUTLET-A	0.35	1.78
OUTLET-A	0.4	1.98
OUTLET-A	0.45	2.16
OUTLET-A	0.5	2.32
OUTLET-A	0.55	2.55
OUTLET-A	0.6	2.83
OUTLET-A	0.65	3.14
OUTLET-A	0.7	3.47
OUTLET-A	0.75	3.83
OUTLET-A	0.8	4.2
OUTLET-A	0.85	4.6
OUTLET-A	0.9	4.87
OUTLET-A	0.95	5.07
OUTLET-A	1	5.26
OUTLET-A	1.05	5.7
OUTLET-A	1.1	6.35
OUTLET-A	1.15	7.13
OUTLET-A	1.2	8.01
OUTLET-A	1.25	9.43
OUTLET-A	1.3	11.29
OUTLET-A	1.35	13.46
OUTLET-A	1.4	15.89
OUTLET-A	1.45	18.55
OUTLET-A	1.5	20.4

;		
OUTLET-B	Rating	0
OUTLET-B		0.05
OUTLET-B		0.1
OUTLET-B		0.15
OUTLET-B		0.2
OUTLET-B		0.25
OUTLET-B		0.3
OUTLET-B		0.35
OUTLET-B		0.4
OUTLET-B		0.45
OUTLET-B		0.5
OUTLET-B		0.55
OUTLET-B		0.6
OUTLET-B		0.65
OUTLET-B		0.7
OUTLET-B		0.75
OUTLET-B		0.8
OUTLET-B		0.85
OUTLET-B		0.9
OUTLET-B		0.95

DRAFT

DRAFT

OUTLET-B		1	2.79
OUTLET-B		1.05	2.8
OUTLET-B		1.1	2.81
OUTLET-B		1.15	2.81
OUTLET-B		1.2	2.82
OUTLET-B		1.25	2.83
OUTLET-B		1.3	3.93
OUTLET-B		1.35	5.95
OUTLET-B		1.4	8.55
OUTLET-B		1.45	11.63
OUTLET-B		1.5	15.13

```

;
STOR-A      Storage  0      6010
STOR-A      Storage  1.5    6010
;
STOR-B      Storage  0      3030
STOR-B      Storage  1.5    3030

```

```

[TIMESERIES]
;;Name      Date      Time      Value
;;-----
OCEANSIDE   FILE "Rainfall_data\oceanside.dat"

```

```

[REPORT]
;;Reporting Options
SUBCATCHMENTS ALL
NODES ALL
LINKS ALL

```

```

[TAGS]

```

```

[MAP]
DIMENSIONS -3453.124 0.000 10000.000 10173.475
Units      None

```

```

[COORDINATES]
;;Node      X-Coord      Y-Coord
;;-----
POC-1       -657.277      1115.023
POC-2       2515.806      1263.225
DIV-B       2530.844      4082.924
DIV-A       -563.380      3955.399
STOR-B      4888.152      4063.285
STOR-A      -3055.920      3917.502

```

```

[VERTICES]
;;Link      X-Coord      Y-Coord
;;-----

```

```

[Polygons]
;;Subcatchment X-Coord      Y-Coord

```

```

;;-----
DMA-A      -773.639      8123.209
DMA-Z      -2672.441     1165.476
BMP-A      -680.751     5950.704
DMA-B      2425.575     8203.445
BMP-B      2455.652     6052.954
DMA-V      4561.027     1406.090

;;Storage Node  X-Coord      Y-Coord
;;-----
STOR-B      4888.152     4063.285
STOR-A      -3055.920     3917.502

[SYMBOLS]
;;Gage      X-Coord      Y-Coord
;;-----
OCEANSIDE   718.531     9575.849

```

DRAFT

SWMM OUTPUT REPORT

PRE-DEVELOPMENT CONDITION

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

3086 Staver Melba
Pre-Development Condition*****
Analysis Options

Flow Units CFS
Process Models:
 Rainfall/Runoff YES
 RDII NO
 Snowmelt NO
 Groundwater NO
 Flow Routing NO
 Water Quality NO
Infiltration Method GREEN_AMPT
Starting Date 08/28/1951 05:00:00
Ending Date 05/23/2008 23:00:00
Antecedent Dry Days 0.0
Report Time Step 01:00:00
Wet Time Step 00:15:00
Dry Time Step 04:00:00

*****	Volume	Depth
Runoff Quantity Continuity	acre-feet	inches
*****	-----	-----
Total Precipitation	310.541	675.090
Evaporation Loss	5.942	12.917
Infiltration Loss	242.540	527.262
Surface Runoff	68.293	148.463
Final Storage	0.000	0.000
Continuity Error (%)	-2.007	

*****	Volume	Volume
Flow Routing Continuity	acre-feet	10^6 gal
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	68.293	22.254
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	68.293	22.254
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.000	

SWMM OUTPUT REPORT

PRE-DEVELOPMENT CONDITION

Subcatchment Runoff Summary

Subcatchment	Total Precip in	Total Runon in	Total Evap in	Total Infil in	Imperv Runoff in	Perv Runoff in	Total Runoff in	Total Runoff 10^6 gal	Peak Runoff CFS	Runoff Coeff
DMA-A	675.09	0.00	12.91	526.34	0.00	149.59	149.59	11.86	3.29	0.222
DMA-B	675.09	0.00	12.93	528.29	0.00	147.19	147.19	10.39	2.92	0.218

Analysis begun on: Fri Jan 5 10:21:33 2024
Analysis ended on: Fri Jan 5 10:21:49 2024
Total elapsed time: 00:00:16

SWMM OUTPUT REPORT

POST-PROJECT CONDITION

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.2 (Build 5.2.4)

3086 Staver Melba
Post-Project Condition
WARNING 04: minimum elevation drop used for Conduit BYPASS-B
WARNING 04: minimum elevation drop used for Conduit LOWFLOW-B
WARNING 04: minimum elevation drop used for Conduit LOWFLOW-A
WARNING 04: minimum elevation drop used for Conduit BYPASS-A

Analysis Options

Flow Units CFS

Process Models:

Rainfall/Runoff YES
RDII NO
Snowmelt NO
Groundwater NO
Flow Routing YES
Ponding Allowed NO
Water Quality NO
Infiltration Method GREEN_AMPT
Flow Routing Method KINWAVE
Starting Date 08/28/1951 05:00:00
Ending Date 05/23/2008 23:00:00
Antecedent Dry Days 0.0
Report Time Step 01:00:00
Wet Time Step 00:15:00
Dry Time Step 04:00:00
Routing Time Step 60.00 sec

*****	Volume	Depth
Runoff Quantity Continuity	acre-feet	inches
*****	-----	-----
Initial LID Storage	0.036	0.070
Total Precipitation	349.839	675.090
Evaporation Loss	44.859	86.566
Infiltration Loss	80.796	155.913
Surface Runoff	21.430	41.355
LID Drainage	208.530	402.404
Final Storage	0.049	0.094
Continuity Error (%)	-1.655	

*****	Volume	Volume
Flow Routing Continuity	acre-feet	10^6 gal
*****	-----	-----
Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	229.960	74.936
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000

SWMM OUTPUT REPORT

POST-PROJECT CONDITION

External Outflow	229.948	74.932
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.000	0.000
Continuity Error (%)	0.005	

Highest Flow Instability Indexes

All links are stable.

Routing Time Step Summary

Minimum Time Step	:	60.00 sec
Average Time Step	:	60.00 sec
Maximum Time Step	:	60.00 sec
% of Time in Steady State	:	0.00
Average Iterations per Step	:	1.00
% of Steps Not Converging	:	0.00

Subcatchment Runoff Summary

Subcatchment	Total Precip in	Total Runon in	Total Evap in	Total Infil in	Imperv Runoff in	Perv Runoff in	Total Runoff in	Total Runoff 10^6 gal	Peak Runoff CFS	Runoff Coeff
DMA-A	675.09	0.00	51.51	144.13	432.16	58.82	490.98	45.22	4.04	0.727
DMA-Z	675.09	0.00	9.31	479.76	0.00	198.15	198.15	0.36	0.08	0.294
BMP-A	675.09	12070.64	1142.58	0.00	0.00	0.00	11602.82	43.47	4.20	0.910
DMA-B	675.09	0.00	47.60	173.12	395.43	70.46	465.89	32.01	3.00	0.690
BMP-B	675.09	16945.01	1217.68	0.00	0.00	0.00	16402.25	30.98	2.87	0.931
DMA-V	675.09	0.00	8.99	477.97	0.00	203.12	203.12	0.12	0.03	0.301

LID Performance Summary

Subcatchment	LID Control	Total Inflow in	Evap Loss in	Infil Loss in	Surface Outflow in	Drain Outflow in	Initial Storage in	Final Storage in	Continuity Error %
BMP-A	BMP-A	12745.73	1142.63	0.00	977.73	10625.52	2.10	2.21	-0.00
BMP-B	BMP-B	17620.10	1217.73	0.00	1502.75	14900.12	2.10	2.24	-0.00

SWMM OUTPUT REPORT

POST-PROJECT CONDITION

Node Depth Summary

Node	Type	Average Depth Feet	Maximum Depth Feet	Maximum HGL Feet	Time of Max Occurrence days hr:min	Reported Max Depth Feet
POC-1	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
POC-2	OUTFALL	0.00	0.00	0.00	0 00:00	0.00
DIV-B	DIVIDER	0.00	0.00	0.00	0 00:00	0.00
DIV-A	DIVIDER	0.00	0.00	0.00	0 00:00	0.00
STOR-B	STORAGE	0.00	0.29	0.29	18857 12:02	0.29
STOR-A	STORAGE	0.00	0.75	0.75	18857 12:16	0.71

Node Inflow Summary

Node	Type	Maximum Lateral Inflow CFS	Maximum Total Inflow CFS	Time of Max Occurrence days hr:min	Lateral Inflow Volume 10^6 gal	Total Inflow Volume 10^6 gal	Flow Balance Error Percent
POC-1	OUTFALL	0.08	4.01	18857 12:16	0.36	43.8	0.000
POC-2	OUTFALL	0.03	2.89	18857 12:01	0.121	31.1	0.000
DIV-B	DIVIDER	2.87	2.87	18857 12:01	31	31	0.000
DIV-A	DIVIDER	4.20	4.20	18857 12:01	43.5	43.5	0.000
STOR-B	STORAGE	0.00	2.65	18857 12:01	0	2.12	0.070
STOR-A	STORAGE	0.00	4.04	18857 12:01	0	3.55	0.072

Node Flooding Summary

No nodes were flooded.

Storage Volume Summary

Storage Unit	Average Volume 1000 ft³	Avg Pcnt Full	Evap Pcnt Loss	Exfil Pcnt Loss	Maximum Volume 1000 ft³	Max Pcnt Full	Time of Max Occurrence days hr:min	Maximum Outflow CFS
STOR-B	0.000	0.0	0.0	0.0	0.893	19.6	18857 12:02	2.64
STOR-A	0.001	0.0	0.0	0.0	4.513	50.1	18857 12:16	3.84

SWMM OUTPUT REPORT

POST-PROJECT CONDITION

Outfall Loading Summary

Outfall Node	Flow Freq Pcnt	Avg Flow CFS	Max Flow CFS	Total Volume 10^6 gal
POC-1	5.23	0.06	4.01	43.826
POC-2	3.95	0.06	2.89	31.100
System	4.59	0.12	6.85	74.926

Link Flow Summary


Link	Type	Maximum Flow CFS	Time of Max Occurrence days hr:min	Maximum Veloc ft/sec	Max/ Full Flow	Max/ Full Depth
BYPASS-B	DUMMY	2.65	18857 12:01			
LOWFLOW-B	DUMMY	0.22	9626 09:44			
LOWFLOW-A	DUMMY	0.16	141 06:58			
BYPASS-A	DUMMY	4.04	18857 12:01			
OUTLET-A	DUMMY	3.84	18857 12:16			
OUTLET-B	DUMMY	2.64	18857 12:02			

Conduit Surcharge Summary

No conduits were surcharged.

Analysis begun on: Fri Jan 5 10:48:06 2024
Analysis ended on: Fri Jan 5 10:49:45 2024
Total elapsed time: 00:01:39

POC-1
SWMM MODEL SCHEMATICS



POC-1 SWMM INPUT

PRE-DEVELOPMENT												
DMA	BMP	Area (ac)	Width (Area/Flow Length) (ft)	% Slope	% Impervious	% "A" Soils	% "B" Soils	% "D" Soils	Weighted Infiltration (in/hr):	Weighted Suction Head (in):	Weighted Initial Deficit:	N-perv ¹
DMA-A	N/A	2.92	560	6.0%	0%	0%	0%	100%	0.025	9.000	0.330	0.08

Total: 2.92

1. Per the Manning's n Values for Overland Flow table (Tory Walker Engineering):
DMA is shrubs and bushes = 0.08

POST-PROJECT												
DMA	BMP	Area (ac)	Width (Area/Flow Length) (ft)	% Impervious	% Slope	% "A" Soils	% "B" Soils	% "D" Soils	Weighted Infiltration (in/hr):	Weighted Suction Head (in):	Weighted Initial Deficit:	N-perv ¹
DMA-A	A	3.392	2081	70%	4%	0%	0%	100%	0.019	9.000	0.330	0.06
BMP-A	A	0.13797	120	0%	0%	0%	0%	100%	0.025	9.000	0.330	0.06
DMA-Z	NA	0.067	117	0%	13%	0%	0%	100%	0.019	9.000	0.330	0.06

Total: 3.60

1. Per the Manning's n Values for Overland Flow table (Tory Walker Engineering):
DMA is a combination of average grass, closely clipped sod and shrubs and bushes = (0.04+0.08)/2 = 0.06

Infiltration:		
D:	0.025	in/hr

Suction Head:		
D:	9	in


Initial Deficit		
D:	0.33	

POC-1

Peak Flow Frequency Summary

Return Period	Pre-project Qpeak (cfs)	Post-project - Mitigated Q (cfs)
LF = 0.1xQ2	0.157	0.103
2-year	1.571	1.033
5-year	1.990	1.607
10-year	2.515	2.199

Peak Flow Frequency Curves POC-1



Low-flow Threshold: 10%

POC-1

0.1xQ2 (Pre): 0.157 cfs

Q10 (Pre): 2.515 cfs

Ordinate #: 100

Incremental Q (Pre): 0.02358 cfs


Total Hourly Data: 497370 hours

The proposed BMP: PASSED

Interval	Pre-project Flow (cfs)	Pre-project Hours	Pre-project % Time Exceeding	Post-project Hours	Post-project % Time Exceeding	Percentage	Pass/Fail
0	0.157	924	1.86E-03	918	1.85E-03	99%	Pass
1	0.181	827	1.66E-03	392	7.88E-04	47%	Pass
2	0.204	745	1.50E-03	316	6.35E-04	42%	Pass
3	0.228	690	1.39E-03	271	5.45E-04	39%	Pass
4	0.251	647	1.30E-03	240	4.83E-04	37%	Pass
5	0.275	605	1.22E-03	212	4.26E-04	35%	Pass
6	0.299	568	1.14E-03	193	3.88E-04	34%	Pass
7	0.322	533	1.07E-03	181	3.64E-04	34%	Pass
8	0.346	504	1.01E-03	157	3.16E-04	31%	Pass
9	0.369	472	9.49E-04	146	2.94E-04	31%	Pass
10	0.393	445	8.95E-04	140	2.81E-04	31%	Pass
11	0.416	413	8.30E-04	132	2.65E-04	32%	Pass
12	0.440	386	7.76E-04	125	2.51E-04	32%	Pass
13	0.464	356	7.16E-04	119	2.39E-04	33%	Pass
14	0.487	334	6.72E-04	110	2.21E-04	33%	Pass
15	0.511	304	6.11E-04	105	2.11E-04	35%	Pass
16	0.534	284	5.71E-04	101	2.03E-04	36%	Pass
17	0.558	272	5.47E-04	96	1.93E-04	35%	Pass
18	0.582	262	5.27E-04	95	1.91E-04	36%	Pass
19	0.605	248	4.99E-04	85	1.71E-04	34%	Pass
20	0.629	233	4.68E-04	82	1.65E-04	35%	Pass
21	0.652	219	4.40E-04	78	1.57E-04	36%	Pass
22	0.676	206	4.14E-04	74	1.49E-04	36%	Pass
23	0.699	197	3.96E-04	70	1.41E-04	36%	Pass
24	0.723	182	3.66E-04	67	1.35E-04	37%	Pass
25	0.747	166	3.34E-04	63	1.27E-04	38%	Pass
26	0.770	146	2.94E-04	60	1.21E-04	41%	Pass
27	0.794	139	2.79E-04	59	1.19E-04	42%	Pass
28	0.817	127	2.55E-04	57	1.15E-04	45%	Pass
29	0.841	122	2.45E-04	54	1.09E-04	44%	Pass
30	0.864	121	2.43E-04	50	1.01E-04	41%	Pass
31	0.888	116	2.33E-04	48	9.65E-05	41%	Pass
32	0.912	112	2.25E-04	48	9.65E-05	43%	Pass
33	0.935	110	2.21E-04	45	9.05E-05	41%	Pass
34	0.959	104	2.09E-04	43	8.65E-05	41%	Pass
35	0.982	96	1.93E-04	42	8.44E-05	44%	Pass
36	1.006	91	1.83E-04	41	8.24E-05	45%	Pass
37	1.030	83	1.67E-04	37	7.44E-05	45%	Pass
38	1.053	77	1.55E-04	33	6.63E-05	43%	Pass
39	1.077	72	1.45E-04	33	6.63E-05	46%	Pass
40	1.100	65	1.31E-04	31	6.23E-05	48%	Pass
41	1.124	63	1.27E-04	30	6.03E-05	48%	Pass
42	1.147	61	1.23E-04	29	5.83E-05	48%	Pass
43	1.171	61	1.23E-04	28	5.63E-05	46%	Pass
44	1.195	57	1.15E-04	28	5.63E-05	49%	Pass
45	1.218	54	1.09E-04	27	5.43E-05	50%	Pass
46	1.242	50	1.01E-04	26	5.23E-05	52%	Pass
47	1.265	48	9.65E-05	25	5.03E-05	52%	Pass
48	1.289	47	9.45E-05	24	4.83E-05	51%	Pass
49	1.313	45	9.05E-05	24	4.83E-05	53%	Pass
50	1.336	43	8.65E-05	21	4.22E-05	49%	Pass
51	1.360	42	8.44E-05	19	3.82E-05	45%	Pass
52	1.383	41	8.24E-05	17	3.42E-05	41%	Pass
53	1.407	41	8.24E-05	17	3.42E-05	41%	Pass
54	1.430	39	7.84E-05	15	3.02E-05	38%	Pass

Interval	Pre-project Flow (cfs)	Pre-project Hours	Pre-project % Time Exceeding	Post-project Hours	Post-project % Time Exceeding	Percentage	Pass/Fail
55	1.454	39	7.84E-05	15	3.02E-05	38%	Pass
56	1.478	36	7.24E-05	15	3.02E-05	42%	Pass
57	1.501	34	6.84E-05	15	3.02E-05	44%	Pass
58	1.525	33	6.63E-05	15	3.02E-05	45%	Pass
59	1.548	33	6.63E-05	14	2.81E-05	42%	Pass
60	1.572	32	6.43E-05	14	2.81E-05	44%	Pass
61	1.595	31	6.23E-05	14	2.81E-05	45%	Pass
62	1.619	29	5.83E-05	14	2.81E-05	48%	Pass
63	1.643	29	5.83E-05	14	2.81E-05	48%	Pass
64	1.666	22	4.42E-05	14	2.81E-05	64%	Pass
65	1.690	22	4.42E-05	13	2.61E-05	59%	Pass
66	1.713	21	4.22E-05	13	2.61E-05	62%	Pass
67	1.737	21	4.22E-05	12	2.41E-05	57%	Pass
68	1.761	21	4.22E-05	12	2.41E-05	57%	Pass
69	1.784	21	4.22E-05	12	2.41E-05	57%	Pass
70	1.808	21	4.22E-05	11	2.21E-05	52%	Pass
71	1.831	21	4.22E-05	11	2.21E-05	52%	Pass
72	1.855	20	4.02E-05	11	2.21E-05	55%	Pass
73	1.878	20	4.02E-05	11	2.21E-05	55%	Pass
74	1.902	18	3.62E-05	10	2.01E-05	56%	Pass
75	1.926	16	3.22E-05	9	1.81E-05	56%	Pass
76	1.949	13	2.61E-05	9	1.81E-05	69%	Pass
77	1.973	12	2.41E-05	9	1.81E-05	75%	Pass
78	1.996	11	2.21E-05	9	1.81E-05	82%	Pass
79	2.020	9	1.81E-05	9	1.81E-05	100%	Pass
80	2.043	9	1.81E-05	9	1.81E-05	100%	Pass
81	2.067	9	1.81E-05	9	1.81E-05	100%	Pass
82	2.091	9	1.81E-05	9	1.81E-05	100%	Pass
83	2.114	9	1.81E-05	8	1.61E-05	89%	Pass
84	2.138	8	1.61E-05	8	1.61E-05	100%	Pass
85	2.161	8	1.61E-05	7	1.41E-05	88%	Pass
86	2.185	7	1.41E-05	6	1.21E-05	86%	Pass
87	2.209	7	1.41E-05	6	1.21E-05	86%	Pass
88	2.232	6	1.21E-05	6	1.21E-05	100%	Pass
89	2.256	6	1.21E-05	6	1.21E-05	100%	Pass
90	2.279	6	1.21E-05	6	1.21E-05	100%	Pass
91	2.303	6	1.21E-05	6	1.21E-05	100%	Pass
92	2.326	6	1.21E-05	6	1.21E-05	100%	Pass
93	2.350	6	1.21E-05	5	1.01E-05	83%	Pass
94	2.374	6	1.21E-05	4	8.04E-06	67%	Pass
95	2.397	6	1.21E-05	4	8.04E-06	67%	Pass
96	2.421	6	1.21E-05	4	8.04E-06	67%	Pass
97	2.444	6	1.21E-05	4	8.04E-06	67%	Pass
98	2.468	6	1.21E-05	4	8.04E-06	67%	Pass
99	2.491	5	1.01E-05	4	8.04E-06	80%	Pass
100	2.515	5	1.01E-05	4	8.04E-06	80%	Pass

**Flow Duration Curve
[Pre vs. Post (Mitigated)]
POC-1**



POC-1

SWMM Model Flow Coefficient Calculation

BMP-A

PARAMETER	ABBREV.	Bio-Retention Cell LID BMP	
Ponding Depth	PD	6	in
Bioretention Soil Layer	S	21	in
Gravel Layer	G	33	in
TOTAL		5.0	ft
		60	in
Orifice Coefficient	C_g	0.6	--
Low Flow Orifice Diameter	D	1.675	in
Drain exponent	n	0.5	--
Flow Rate (volumetric)	Q	0.164	cfs
Ponding Depth Surface Area	A_{PD}	6010	ft ²
Bioretention Surface Area	A_S, A_G	6010	ft ²
	A_S, A_G	0.1380	ac
Porosity of Bioretention Soil		0.40	-
Flow Rate (per unit area)	q	2.940	in/hr
Effective Ponding Depth	PD_{eff}	6.00	in
Flow Coefficient	C	0.1541	--

Summary for Pond 2P: STOR BMP-A Alt 1

Volume	Invert	Avail.Storage	Storage Description		
#1	375.50'	9,015 cf	BMP-A (Conic) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
375.50	6,010	0.00	0	0	6,010
377.00	6,010	100.00	9,015	9,015	6,422
Device	Routing	Invert	Outlet Devices		
#1	Primary	370.50'	18.000" Round Culvert L= 18.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 370.50' / 370.41' S= 0.0050 ' / Cc= 0.900 n= 0.013, Flow Area= 1.77 sf		
#2	Device 1	375.50'	19.000" W x 3.000" H Vert. Orifice X 2.00 C= 0.600 Limited to weir flow at low heads		
#3	Device 1	376.00'	12.000" x 12.000" Horiz. Grate X 0.50 C= 0.600 in 12.000" x 12.000" Grate (100% open area) Limited to weir flow at low heads		
#4	Device 1	376.50'	18.000" x 18.000" Horiz. Grate X 0.50 C= 0.600 in 18.000" x 18.000" Grate (100% open area) Limited to weir flow at low heads		
#5	Device 1	376.50'	24.000" x 24.000" Horiz. Grate X 0.50 C= 0.600 in 24.000" x 24.000" Grate (100% open area) Limited to weir flow at low heads		
#6	Device 1	376.70'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		
#7	Device 1	376.70'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		

Stage-Discharge for Pond 2P: STOR BMP-A Alt 1

Elevation (feet)	Primary (cfs)
375.50	0.00
375.55	0.11
375.60	0.32
375.65	0.59
375.70	0.91
375.75	1.27
375.80	1.56
375.85	1.78
375.90	1.98
375.95	2.16
376.00	2.32
376.05	2.55
376.10	2.83
376.15	3.14
376.20	3.47
376.25	3.83
376.30	4.20
376.35	4.60
376.40	4.87
376.45	5.07
376.50	5.26
376.55	5.70
376.60	6.35
376.65	7.13
376.70	8.01
376.75	9.43
376.80	11.29
376.85	13.46
376.90	15.89
376.95	18.55
377.00	20.40

Drawdown Calculation for BMP

Project Name


A
Staver Melba

Project No

3086

Surface Drawdown Time:	5.2	hr
Total Drawdown Time:	19.4	hr
Surface Area	6010	sq ft
Underdrain Orifice Diameter:	1.675	in
C:	0.6	
Ponding (to invert of lowest discharge opening in outlet structure):	0.5	ft
Amended Soil Depth:	1.75	ft
Gravel Depth:	2.5	ft
Orifice Q =	0.159	cfs
Effective Depth	22.2	in
Flow Rate controlled by orifice	1.145	in/hr

POC-2
SWMM MODEL SCHEMATICS



3086 Staver Melba
1/5/2024

POC-2 SWMM INPUT

PRE-DEVELOPMENT												
DMA	BMP	Area (ac)	Width (Area/Flow Length) (ft)	% Slope	% Impervious	% "A" Soils	% "B" Soils	% "D" Soils	Weighted Infiltration (in/hr):	Weighted Suction Head (in):	Weighted Initial Deficit:	N-perv ¹
DMA-B	N/A	2.60	399	5.5%	0%	0%	0%	100%	0.025	9.000	0.330	0.08

Total: 2.60

1. Per the Manning's n Values for Overland Flow table (Tory Walker Engineering):

DMA is shrubs and bushes = 0.08

POST-PROJECT												
DMA	BMP	Area (ac)	Width (Area/Flow Length) (ft)	% Impervious	% Slope	% "A" Soils	% "B" Soils	% "D" Soils	Weighted Infiltration (in/hr):	Weighted Suction Head (in):	Weighted Initial Deficit:	N-perv ¹
DMA-B	B	2.53	2205	64%	3%	0%	0%	100%	0.019	9.000	0.330	0.06
BMP-B	B	0.06956	61	0%	0%	0%	0%	100%	0.025	9.000	0.330	0.06
DMA-V	NA	0.022	192	0%	50%	0%	0%	100%	0.019	9.000	0.330	0.06

Total: 2.62

1. Per the Manning's n Values for Overland Flow table (Tory Walker Engineering):

DMA is a combination of average grass, closely clipped sod and shrubs and bushes = $(0.04+0.08)/2 = 0.06$

Infiltration:	
D:	0.025 in/hr

Suction Head:	
D:	9 in


Initial Deficit	
D:	0.33

POC-2

Peak Flow Frequency Summary

Return Period	Pre-project Qpeak (cfs)	Post-project - Mitigated Q (cfs)
LF = 0.1xQ2	0.138	0.104
2-year	1.375	1.044
5-year	1.752	1.572
10-year	2.202	2.096

Peak Flow Frequency Curves POC-2



Low-flow Threshold: 10%

POC-2

0.1xQ2 (Pre): 0.138 cfs

Q10 (Pre): 2.202 cfs

Ordinate #: 100

Incremental Q (Pre): 0.02065 cfs


Total Hourly Data: 497370 hours

The proposed BMP: PASSED

Interval	Pre-project Flow (cfs)	Pre-project Hours	Pre-project % Time Exceeding	Post-project Hours	Post-project % Time Exceeding	Percentage	Pass/Fail
0	0.138	912	1.83E-03	863	1.74E-03	95%	Pass
1	0.158	830	1.67E-03	452	9.09E-04	54%	Pass
2	0.179	754	1.52E-03	276	5.55E-04	37%	Pass
3	0.199	681	1.37E-03	224	4.50E-04	33%	Pass
4	0.220	627	1.26E-03	208	4.18E-04	33%	Pass
5	0.241	588	1.18E-03	192	3.86E-04	33%	Pass
6	0.261	554	1.11E-03	180	3.62E-04	32%	Pass
7	0.282	516	1.04E-03	166	3.34E-04	32%	Pass
8	0.303	494	9.93E-04	152	3.06E-04	31%	Pass
9	0.323	464	9.33E-04	137	2.75E-04	30%	Pass
10	0.344	435	8.75E-04	128	2.57E-04	29%	Pass
11	0.365	402	8.08E-04	120	2.41E-04	30%	Pass
12	0.385	379	7.62E-04	116	2.33E-04	31%	Pass
13	0.406	355	7.14E-04	111	2.23E-04	31%	Pass
14	0.427	329	6.61E-04	109	2.19E-04	33%	Pass
15	0.447	297	5.97E-04	102	2.05E-04	34%	Pass
16	0.468	275	5.53E-04	98	1.97E-04	36%	Pass
17	0.489	263	5.29E-04	90	1.81E-04	34%	Pass
18	0.509	256	5.15E-04	88	1.77E-04	34%	Pass
19	0.530	238	4.79E-04	80	1.61E-04	34%	Pass
20	0.550	224	4.50E-04	77	1.55E-04	34%	Pass
21	0.571	212	4.26E-04	75	1.51E-04	35%	Pass
22	0.592	202	4.06E-04	72	1.45E-04	36%	Pass
23	0.612	192	3.86E-04	69	1.39E-04	36%	Pass
24	0.633	176	3.54E-04	67	1.35E-04	38%	Pass
25	0.654	162	3.26E-04	65	1.31E-04	40%	Pass
26	0.674	143	2.88E-04	61	1.23E-04	43%	Pass
27	0.695	137	2.75E-04	60	1.21E-04	44%	Pass
28	0.716	128	2.57E-04	56	1.13E-04	44%	Pass
29	0.736	123	2.47E-04	55	1.11E-04	45%	Pass
30	0.757	117	2.35E-04	54	1.09E-04	46%	Pass
31	0.778	114	2.29E-04	52	1.05E-04	46%	Pass
32	0.798	112	2.25E-04	50	1.01E-04	45%	Pass
33	0.819	108	2.17E-04	46	9.25E-05	43%	Pass
34	0.840	100	2.01E-04	45	9.05E-05	45%	Pass
35	0.860	94	1.89E-04	43	8.65E-05	46%	Pass
36	0.881	90	1.81E-04	41	8.24E-05	46%	Pass
37	0.901	82	1.65E-04	39	7.84E-05	48%	Pass
38	0.922	76	1.53E-04	39	7.84E-05	51%	Pass
39	0.943	68	1.37E-04	39	7.84E-05	57%	Pass
40	0.963	67	1.35E-04	38	7.64E-05	57%	Pass
41	0.984	63	1.27E-04	35	7.04E-05	56%	Pass
42	1.005	62	1.25E-04	33	6.63E-05	53%	Pass
43	1.025	59	1.19E-04	33	6.63E-05	56%	Pass
44	1.046	58	1.17E-04	32	6.43E-05	55%	Pass
45	1.067	55	1.11E-04	31	6.23E-05	56%	Pass
46	1.087	52	1.05E-04	30	6.03E-05	58%	Pass
47	1.108	48	9.65E-05	29	5.83E-05	60%	Pass
48	1.129	47	9.45E-05	28	5.63E-05	60%	Pass
49	1.149	47	9.45E-05	28	5.63E-05	60%	Pass
50	1.170	43	8.65E-05	27	5.43E-05	63%	Pass
51	1.191	42	8.44E-05	27	5.43E-05	64%	Pass
52	1.211	42	8.44E-05	26	5.23E-05	62%	Pass
53	1.232	40	8.04E-05	26	5.23E-05	65%	Pass
54	1.253	39	7.84E-05	26	5.23E-05	67%	Pass

Interval	Pre-project Flow (cfs)	Pre-project Hours	Pre-project % Time Exceeding	Post-project Hours	Post-project % Time Exceeding	Percentage	Pass/Fail
55	1.273	37	7.44E-05	25	5.03E-05	68%	Pass
56	1.294	37	7.44E-05	23	4.62E-05	62%	Pass
57	1.314	34	6.84E-05	21	4.22E-05	62%	Pass
58	1.335	33	6.63E-05	21	4.22E-05	64%	Pass
59	1.356	33	6.63E-05	21	4.22E-05	64%	Pass
60	1.376	32	6.43E-05	21	4.22E-05	66%	Pass
61	1.397	31	6.23E-05	20	4.02E-05	65%	Pass
62	1.418	29	5.83E-05	20	4.02E-05	69%	Pass
63	1.438	29	5.83E-05	17	3.42E-05	59%	Pass
64	1.459	26	5.23E-05	17	3.42E-05	65%	Pass
65	1.480	22	4.42E-05	17	3.42E-05	77%	Pass
66	1.500	21	4.22E-05	17	3.42E-05	81%	Pass
67	1.521	21	4.22E-05	15	3.02E-05	71%	Pass
68	1.542	21	4.22E-05	14	2.81E-05	67%	Pass
69	1.562	21	4.22E-05	12	2.41E-05	57%	Pass
70	1.583	21	4.22E-05	12	2.41E-05	57%	Pass
71	1.604	21	4.22E-05	11	2.21E-05	52%	Pass
72	1.624	20	4.02E-05	11	2.21E-05	55%	Pass
73	1.645	20	4.02E-05	11	2.21E-05	55%	Pass
74	1.665	20	4.02E-05	10	2.01E-05	50%	Pass
75	1.686	18	3.62E-05	10	2.01E-05	56%	Pass
76	1.707	15	3.02E-05	9	1.81E-05	60%	Pass
77	1.727	14	2.81E-05	9	1.81E-05	64%	Pass
78	1.748	11	2.21E-05	8	1.61E-05	73%	Pass
79	1.769	10	2.01E-05	7	1.41E-05	70%	Pass
80	1.789	9	1.81E-05	7	1.41E-05	78%	Pass
81	1.810	9	1.81E-05	7	1.41E-05	78%	Pass
82	1.831	9	1.81E-05	7	1.41E-05	78%	Pass
83	1.851	9	1.81E-05	7	1.41E-05	78%	Pass
84	1.872	9	1.81E-05	7	1.41E-05	78%	Pass
85	1.893	9	1.81E-05	6	1.21E-05	67%	Pass
86	1.913	8	1.61E-05	6	1.21E-05	75%	Pass
87	1.934	7	1.41E-05	6	1.21E-05	86%	Pass
88	1.955	7	1.41E-05	6	1.21E-05	86%	Pass
89	1.975	6	1.21E-05	6	1.21E-05	100%	Pass
90	1.996	6	1.21E-05	6	1.21E-05	100%	Pass
91	2.017	6	1.21E-05	6	1.21E-05	100%	Pass
92	2.037	6	1.21E-05	6	1.21E-05	100%	Pass
93	2.058	6	1.21E-05	5	1.01E-05	83%	Pass
94	2.078	6	1.21E-05	5	1.01E-05	83%	Pass
95	2.099	6	1.21E-05	5	1.01E-05	83%	Pass
96	2.120	6	1.21E-05	5	1.01E-05	83%	Pass
97	2.140	6	1.21E-05	5	1.01E-05	83%	Pass
98	2.161	6	1.21E-05	5	1.01E-05	83%	Pass
99	2.182	5	1.01E-05	5	1.01E-05	100%	Pass
100	2.202	5	1.01E-05	5	1.01E-05	100%	Pass

Flow Duration Curve [Pre vs. Post (Mitigated)] POC-2



POC-2

SWMM Model Flow Coefficient Calculation

BMP-B

PARAMETER	ABBREV.	Bio-Retention Cell LID BMP	
Ponding Depth	PD	6	in
Bioretention Soil Layer	S	21	in
Permavoid Layer	G	78	in
TOTAL		8.8	ft
		105	in
Orifice Coefficient	C_g	0.6	--
Low Flow Orifice Diameter	D	1.7	in
Drain exponent	n	0.5	--
Flow Rate (volumetric)	Q	0.224	cfs
Ponding Depth Surface Area	A_{PD}	3030	ft ²
Bioretention Surface Area	A_S, A_G	3030	ft ²
	A_S, A_G	0.0696	ac
Porosity of Bioretention Soil		0.40	-
Flow Rate (per unit area)	q	7.970	in/hr
Effective Ponding Depth	PD_{eff}	6.00	in
Flow Coefficient	C	0.3148	--

Summary for Pond 11P: STOR BMP-B Alt 1

Volume	Invert	Avail.Storage	Storage Description		
#1	382.00'	4,545 cf	BMP-B (Conic) Listed below (Recalc)		
Elevation (feet)	Surf.Area (sq-ft)	Voids (%)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)	Wet.Area (sq-ft)
382.00	3,030	0.00	0	0	3,030
383.50	3,030	100.00	4,545	4,545	3,323
Device	Routing	Invert	Outlet Devices		
#1	Secondary	373.50'	6.000" Round 6" Culvert L= 18.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 373.50' / 373.32' S= 0.0100 '/' Cc= 0.900 n= 0.013, Flow Area= 0.20 sf		
#2	Device 1	382.00'	23.000" W x 3.000" H Vert. Midflow Orifice X 3.00 C= 0.600 Limited to weir flow at low heads		
#3	Device 1	383.00'	24.000" x 24.000" Horiz. Grate X 0.50 C= 0.600 in 24.000" x 24.000" Grate (100% open area) Limited to weir flow at low heads		
#4	Secondary	373.25'	18.000" Round 18" Culvert L= 10.0' RCP, square edge headwall, Ke= 0.500 Inlet / Outlet Invert= 373.25' / 373.15' S= 0.0100 '/' Cc= 0.900 n= 0.013, Flow Area= 1.77 sf		
#5	Device 4	383.25'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		
#6	Device 4	383.25'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		
#7	Device 4	383.25'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		
#8	Device 4	383.25'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		
#9	Device 4	383.25'	36.000" x 36.000" Horiz. Grate X 0.50 C= 0.600 in 36.000" x 36.000" Grate (100% open area) Limited to weir flow at low heads		

Stage-Discharge for Pond 11P: STOR BMP-B Alt 1

<u>Elevation</u> <u>(feet)</u>	<u>Secondary</u> <u>(cfs)</u>
382.00	0.00
382.05	0.21
382.10	0.58
382.15	1.07
382.20	1.65
382.25	2.31
382.30	2.68
382.35	2.69
382.40	2.70
382.45	2.71
382.50	2.71
382.55	2.72
382.60	2.73
382.65	2.74
382.70	2.75
382.75	2.75
382.80	2.76
382.85	2.77
382.90	2.78
382.95	2.78
383.00	2.79
383.05	2.80
383.10	2.81
383.15	2.81
383.20	2.82
383.25	2.83
383.30	3.93
383.35	5.95
383.40	8.55
383.45	11.63
383.50	15.13

Drawdown Calculation for BMP

B

Project Name

Staver Melba

Project No

3086

Surface Drawdown Time:	1.9	hr
Total Drawdown Time:	12.8	hr
Surface Area	3030	sq ft
Underdrain Orifice Diameter:	1.7	in
C:	0.6	
Ponding (to invert of lowest discharge opening in outlet structure):	0.5	ft
Amended Soil Depth:	1.75	ft
Permavoid Depth:	6.25	ft
Orifice Q =	0.220	cfs
Effective Depth	81.45	in
Flow Rate controlled by orifice	3.140	in/hr



Manning's n Values for Overland Flow¹

The BMP Design Manuals within the County of San Diego allow for a land surface description other than short prairie grass to be used for hydromodification BMP design only if documentation provided is consistent with Table A.6 of the SWMM 5 User's Manual.

In January 2016, the EPA released the SWMM Reference Manual Volume I – Hydrology (SWMM Hydrology Reference Manual). The SWMM Hydrology Reference Manual complements the SWMM 5 User's Manual by providing an in-depth description of the program's hydrologic components. Table 3-5 of the SWMM Hydrology Reference Manual expounds upon Table A.6 of the SWMM 5 User's Manual by providing Manning's n values for additional overland flow surfaces. Therefore, in order to provide SWMM users with a wider range of land surfaces suitable for local application and to provide Copermittees with confidence in the design parameters, we recommend using the values published by Yen and Chow in Table 3-5 of the EPA SWMM Reference Manual Volume I – Hydrology. The values are provided in the table below:

Overland Surface	Manning value (n)
Smooth asphalt pavement	0.010
Smooth impervious surface	0.011
Tar and sand pavement	0.012
Concrete pavement	0.014
Rough impervious surface	0.015
Smooth bare packed soil	0.017
Moderate bare packed soil	0.025
Rough bare packed soil	0.032
Gravel soil	0.025
Mowed poor grass	0.030
Average grass, closely clipped sod	0.040
Pasture	0.040
Timberland	0.060
Dense grass	0.060
Shrubs and bushes	0.080
Land Use	
Business	0.014
Semibusiness	0.022
Industrial	0.020
Dense residential	0.025
Suburban residential	0.030
Parks and lawns	0.040

¹Content summarized from *Improving Accuracy in Continuous Simulation Modeling: Guidance for Selecting Pervious Overland Flow Manning's n Values in the San Diego Region* (TRWE, 2016).

Appendix G: Guidance for Continuous Simulation and Hydromodification Management Sizing Factors




Figure G.1-2: California Irrigation Management Information System "Reference Evapotranspiration Zones"

Appendix G: Guidance for Continuous Simulation and Hydromodification Management Sizing Factors

**Table G.1-1: Monthly Average Reference Evapotranspiration by ETo Zone
(inches/month and inches/day) for use in SWMM Models for Hydromodification Management Studies in San Diego County
CIMIS Zones 1, 4, 6, 9, and 16 (See CIMIS ETo Zone Map)**

	January	February	March	April	May	June	July	August	September	October	November	December
Zone	in/month	in/month	in/month	in/month	in/month	in/month	in/month	in/month	in/month	in/month	in/month	in/month
1	0.93	1.4	2.48	3.3	4.03	4.5	4.65	4.03	3.3	2.48	1.2	0.62
4	1.86	2.24	3.41	4.5	5.27	5.7	5.89	5.58	4.5	3.41	2.4	1.86
6	1.86	2.24	3.41	4.8	5.58	6.3	6.51	6.2	4.8	3.72	2.4	1.86
9	2.17	2.8	4.03	5.1	5.89	6.6	7.44	6.82	5.7	4.03	2.7	1.86
16	1.55	2.52	4.03	5.7	7.75	8.7	9.3	8.37	6.3	4.34	2.4	1.55
	January	February	March	April	May	June	July	August	September	October	November	December
Days	31	28	31	30	31	30	31	31	30	31	30	31
Zone	in/day	in/day	in/day	in/day	in/day	in/day	in/day	in/day	in/day	in/day	in/day	in/day
1	0.030	0.050	0.080	0.110	0.130	0.150	0.150	0.130	0.110	0.080	0.040	0.020
4	0.060	0.080	0.110	0.150	0.170	0.190	0.190	0.180	0.150	0.110	0.080	0.060
6	0.060	0.080	0.110	0.160	0.180	0.210	0.210	0.200	0.160	0.120	0.080	0.060
9	0.070	0.100	0.130	0.170	0.190	0.220	0.240	0.220	0.190	0.130	0.090	0.060
16	0.050	0.090	0.130	0.190	0.250	0.290	0.300	0.270	0.210	0.140	0.080	0.050

ATTACHMENT 3 - STRUCTURAL BMP MAINTENANCE INFORMATION

This is the cover sheet for Attachment 3.

Indicate which items are included behind this cover sheet:

Attachment	Contents	Checklist
Attachment 3a	Structural BMP Maintenance Thresholds and Actions (Required)	☒ Included See Structural BMP Maintenance Information Checklist on the back of this Attachment cover sheet.
Attachment 3b	Draft Maintenance Agreement (when applicable)	☐ Included ☐ Not Applicable

Use this checklist to ensure the required information has been included in the Structural BMP Maintenance Information Attachment:

☐ **Preliminary Design / Planning / CEQA level submittal:**

Attachment 3a must identify:

- ☐ Typical maintenance indicators and actions for proposed structural BMP(s) based on Section 7.7 of the BMP Design Manual

Attachment 3b is not required for preliminary design / planning / CEQA level submittal.

☐ **Final Design level submittal:**

Attachment 3a must identify:

- ☐ Specific maintenance indicators and actions for proposed structural BMP(s). This shall be based on Section 7.7 of the BMP Design Manual and enhanced to reflect actual proposed components of the structural BMP(s)
- ☐ How to access the structural BMP(s) to inspect and perform maintenance
- ☐ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
- ☐ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
- ☐ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
- ☐ Recommended equipment to perform maintenance
- ☐ When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management

Attachment 3b: For private entity operation and maintenance, Attachment 3b shall include a draft maintenance agreement in the local jurisdiction's standard format (PDP applicant to contact the City Engineer to obtain the current maintenance agreement forms).

APPENDIX 3a
BMP MAINTENANCE THRESHOLDS

BMP DESCRIPTION

BIOFILTRATION (6,010 SF)	STORM WATER MANAGEMENT AND DISCHARGE CONTROL MAINTENANCE AGREEMENT APPROVAL NO: _____ O&M RESPONSIBLE PARTY DESIGNEE: TORREY PACIFIC CORPORATION	
POST-CONSTRUCTION PERMANENT BMP OPERATION & MAINTENANCE PROCEDURE DETAILS		
MAINTENANCE INDICATORS		MAINTENANCE ACTION
ACCUMULATION OF SEDIMENT, LITTER, OR DEBRIS		REMOVE AND PROPERLY DISPOSE OF ACCUMULATED MATERIALS, WITHOUT DAMAGE TO THE VEGETATION
POOR VEGETATION ESTABLISHMENT		RE-SEED, RE-PLANT, OR RE-ESTABLISH VEGETATION PER ORIGINAL PLANS
OVERGROWN VEGETATION		MOW OR TRIM AS APPROPRIATE, BUT NOT LESS THAT THE DESIGN HEIGHT OF THE VEGETATION PER ORIGINAL PLANS.
EROSION DUE TO CONCENTRATED IRRIGATION FLOW		REPAIR/RE-SEED/RE-PLANT ERODED AREAS AND ADJUST THE IRRIGATION SYSTEM
EROSION DUE TO CONCENTRATED STORM WATER RUNOFF FLOW		REPAIR/RE-SEED/RE-PLANT ERODED AREAS AND MAKE APPROPRIATE CORRECTIVE MEASURES SUCH AS ADDING STONE AT FLOW ENTRY POINTS OR MINOR RE-GRADING TO RESTORE PROPER DRAINAGE ACCORDING TO THE ORIGINAL PLAN.
STANDING WATER IN BIOFILTRATION AREAS		MAKE APPROPRIATE CORRECTIVE MEASURES SUCH AS ADJUSTING IRRIGATION SYSTEM, REMOVING OBSTRUCTION OF DEBRIS OR INVASIVE VEGETATION, OR CLEANING UNDERDRAINS
OBSTRUCTED INLET OR OUTLET STRUCTURE		CLEAR OBSTRUCTIONS
DAMAGE TO INLET OR OUTLET STRUCTURE		REPAIR OR REPLACE AS APPLICABLE

MAINTENANCE EQUIPMENT AND ACCESS

USE LANDSCAPE EQUIPMENT FOR MAINTENANCE; ACCESS BMP FROM PRIVATE ROAD SERVING THE SUBJECT PROPERTY OFF OF MELBA ROAD

INSPECTION FACILITATION

INSTALL A 1' x 1', 1.5' x 1.5', 2' x 2' AND TWO 3' X 3' OUTLET RISER STRUCTURE TO PROVIDE OBSERVATION ACCESS FOR INSPECTION OF MAINTENANCE THRESHOLDS WITHIN EACH BMP; MARKING TO BE PROVIDED ON BMP COMPONENTS TO DETERMINE HOW FULL BMP IS.

APPENDIX 3a
BMP MAINTENANCE THRESHOLDS

BMP DESCRIPTION

BIOFILTRATION (3,030 SF)	STORM WATER MANAGEMENT AND DISCHARGE CONTROL MAINTENANCE AGREEMENT APPROVAL NO: _____ O&M RESPONSIBLE PARTY DESIGNEE: TORREY PACIFIC CORPORATION	
POST-CONSTRUCTION PERMANENT BMP OPERATION & MAINTENANCE PROCEDURE DETAILS		
MAINTENANCE INDICATORS		MAINTENANCE ACTION
ACCUMULATION OF SEDIMENT, LITTER, OR DEBRIS		REMOVE AND PROPERLY DISPOSE OF ACCUMULATED MATERIALS, WITHOUT DAMAGE TO THE VEGETATION
POOR VEGETATION ESTABLISHMENT		RE-SEED, RE-PLANT, OR RE-ESTABLISH VEGETATION PER ORIGINAL PLANS
OVERGROWN VEGETATION		MOW OR TRIM AS APPROPRIATE, BUT NOT LESS THAT THE DESIGN HEIGHT OF THE VEGETATION PER ORIGINAL PLANS.
EROSION DUE TO CONCENTRATED IRRIGATION FLOW		REPAIR/RE-SEED/RE-PLANT ERODED AREAS AND ADJUST THE IRRIGATION SYSTEM
EROSION DUE TO CONCENTRATED STORM WATER RUNOFF FLOW		REPAIR/RE-SEED/RE-PLANT ERODED AREAS AND MAKE APPROPRIATE CORRECTIVE MEASURES SUCH AS ADDING STONE AT FLOW ENTRY POINTS OR MINOR RE-GRADING TO RESTORE PROPER DRAINAGE ACCORDING TO THE ORIGINAL PLAN.
STANDING WATER IN BIOFILTRATION AREAS		MAKE APPROPRIATE CORRECTIVE MEASURES SUCH AS ADJUSTING IRRIGATION SYSTEM, REMOVING OBSTRUCTION OF DEBRIS OR INVASIVE VEGETATION, OR CLEANING UNDERDRAINS
OBSTRUCTED INLET OR OUTLET STRUCTURE		CLEAR OBSTRUCTIONS
DAMAGE TO INLET OR OUTLET STRUCTURE		REPAIR OR REPLACE AS APPLICABLE

MAINTENANCE EQUIPMENT AND ACCESS
USE LANDSCAPE EQUIPMENT FOR MAINTENANCE; ACCESS BMP FROM LOT 19 WITH IN THE PROPOSED DEVELOPMENT

INSPECTION FACILITATION
INSTALL 2' X 2' AND 5-3' X 3' OUTLET RISER STRUCTURE TO PROVIDE OBSERVATION ACCESS FOR INSPECTION OF MAINTENANCE THRESHOLDS WITHIN EACH BMP; MARKING TO BE PROVIDED ON BMP COMPONENTS TO DETERMINE HOW FULL BMP IS.

BF-1

Biofiltration

BMP MAINTENANCE FACT SHEET FOR STRUCTURAL BMP BF-1 BIOFILTRATION

Biofiltration facilities are vegetated surface water systems that filter water through vegetation, and soil or engineered media prior to discharge via underdrain or overflow to the downstream conveyance system. Biofiltration facilities have limited or no infiltration. They are typically designed to provide enough hydraulic head to move flows through the underdrain connection to the storm drain system. Typical biofiltration components include:

- Inflow distribution mechanisms (e.g., perimeter flow spreader or filter strips)
- Energy dissipation mechanism for concentrated inflows (e.g., splash blocks or riprap)
- Shallow surface ponding for captured flows
- Side slope and basin bottom vegetation selected based on climate and ponding depth
- Non-floating mulch layer
- Media layer (planting mix or engineered media) capable of supporting vegetation growth
- Filter course layer consisting of aggregate to prevent the migration of fines into uncompacted native soils or the aggregate storage layer
- Aggregate storage layer with underdrain(s)
- Impermeable liner or uncompacted native soils at the bottom of the facility
- Overflow structure

Normal Expected Maintenance

Biofiltration requires routine maintenance to: remove accumulated materials such as sediment, trash or debris; maintain vegetation health; maintain infiltration capacity of the media layer; replenish mulch; and maintain integrity of side slopes, inlets, energy dissipators, and outlets. A summary table of standard inspection and maintenance indicators is provided within this Fact Sheet.

Non-Standard Maintenance or BMP Failure

If any of the following scenarios are observed, the BMP is not performing as intended to protect downstream waterways from pollution and/or erosion. Corrective maintenance, increased inspection and maintenance, BMP replacement, or a different BMP type will be required.

- The BMP is not drained between storm events. Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health, and surface ponding longer than approximately 96 hours following a storm event poses a risk of vector (mosquito) breeding. Poor drainage can result from clogging of the media layer, filter course, aggregate storage layer, underdrain, or outlet structure. The specific cause of the drainage issue must be determined and corrected.
- Sediment, trash, or debris accumulation greater than 25% of the surface ponding volume within one month. This means the load from the tributary drainage area is too high, reducing BMP function or clogging the BMP. This would require pretreatment measures within the tributary area draining to the BMP to intercept the materials. Pretreatment components, especially for sediment, will extend the life of components that are more expensive to replace such as media, filter course, and aggregate layers.
- Erosion due to concentrated storm water runoff flow that is not readily corrected by adding erosion control blankets, adding stone at flow entry points, or minor re-grading to restore proper drainage according to the original plan. If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction.

BF-1

Biofiltration

Other Special Considerations

Biofiltration is a vegetated structural BMP. Vegetated structural BMPs that are constructed in the vicinity of, or connected to, an existing jurisdictional water or wetland could inadvertently result in creation of expanded waters or wetlands. As such, vegetated structural BMPs have the potential to come under the jurisdiction of the United States Army Corps of Engineers, SDRWQCB, California Department of Fish and Wildlife, or the United States Fish and Wildlife Service. This could result in the need for specific resource agency permits and costly mitigation to perform maintenance of the structural BMP. Along with proper placement of a structural BMP, routine maintenance is key to preventing this scenario.

DRAFT

BF-1

Biofiltration

SUMMARY OF STANDARD INSPECTION AND MAINTENANCE FOR BF-1 BIOFILTRATION

The property owner is responsible to ensure inspection, operation and maintenance of permanent BMPs on their property unless responsibility has been formally transferred to an agency, community facilities district, homeowners association, property owners association, or other special district.

Maintenance frequencies listed in this table are average/typical frequencies. Actual maintenance needs are site-specific, and maintenance may be required more frequently. Maintenance must be performed whenever needed, based on maintenance indicators presented in this table. The BMP owner is responsible for conducting regular inspections to see when maintenance is needed based on the maintenance indicators. During the first year of operation of a structural BMP, inspection is recommended at least once prior to August 31 and then monthly from September through May. Inspection during a storm event is also recommended. After the initial period of frequent inspections, the minimum inspection and maintenance frequency can be determined based on the results of the first year inspections.

Threshold/Indicator	Maintenance Action	Typical Maintenance Frequency
Accumulation of sediment, litter, or debris	Remove and properly dispose of accumulated materials, without damage to the vegetation or compaction of the media layer.	- Inspect monthly. If the BMP is 25% full* or more in one month, increase inspection frequency to monthly plus after every 0.1-inch or larger storm event. - Remove any accumulated materials found at each inspection.
Obstructed inlet or outlet structure	Clear blockage.	- Inspect monthly and after every 0.5-inch or larger storm event. - Remove any accumulated materials found at each inspection.
Damage to structural components such as weirs, inlet or outlet structures	Repair or replace as applicable	- Inspect annually. - Maintenance when needed.
Poor vegetation establishment	Re-seed, re-plant, or re-establish vegetation per original plans.	- Inspect monthly. - Maintenance when needed.
Dead or diseased vegetation	Remove dead or diseased vegetation, re-seed, re-plant, or re-establish vegetation per original plans.	- Inspect monthly. - Maintenance when needed.
Overgrown vegetation	Mow or trim as appropriate.	- Inspect monthly. - Maintenance when needed.
2/3 of mulch has decomposed, or mulch has been removed	Remove decomposed fraction and top off with fresh mulch to a total depth of 3 inches.	- Inspect monthly. - Replenish mulch annually, or more frequently when needed based on inspection.

*"25% full" is defined as $\frac{1}{4}$ of the depth from the design bottom elevation to the crest of the outflow structure (e.g., if the height to the outflow opening is 12 inches from the bottom elevation, then the materials must be removed when there is 3 inches of accumulation – this should be marked on the outflow structure).

BF-1

Biofiltration

SUMMARY OF STANDARD INSPECTION AND MAINTENANCE FOR BF-1 BIOFILTRATION (Continued from previous page)		
Threshold/Indicator	Maintenance Action	Typical Maintenance Frequency
Erosion due to concentrated irrigation flow	Repair/re-seed/re-plant eroded areas and adjust the irrigation system.	- Inspect monthly. - Maintenance when needed.
Erosion due to concentrated storm water runoff flow	Repair/re-seed/re-plant eroded areas, and make appropriate corrective measures such as adding erosion control blankets, adding stone at flow entry points, or minor re-grading to restore proper drainage according to the original plan. If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction.	- Inspect after every 0.5-inch or larger storm event. If erosion due to storm water flow has been observed, increase inspection frequency to after every 0.1-inch or larger storm event. - Maintenance when needed. If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction.
Standing water in BMP for longer than 24 hours following a storm event Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health	Make appropriate corrective measures such as adjusting irrigation system, removing obstructions of debris or invasive vegetation, clearing underdrains, or repairing/replacing clogged or compacted soils.	- Inspect monthly and after every 0.5-inch or larger storm event. If standing water is observed, increase inspection frequency to after every 0.1-inch or larger storm event. - Maintenance when needed.
Presence of mosquitos/larvae For images of egg rafts, larva, pupa, and adult mosquitos, see http://www.mosquito.org/biology	If mosquitos/larvae are observed: first, immediately remove any standing water by dispersing to nearby landscaping; second, make corrective measures as applicable to restore BMP drainage to prevent standing water. If mosquitos persist following corrective measures to remove standing water, or if the BMP design does not meet the 96-hour drawdown criteria due to release rates controlled by an orifice installed on the underdrain, the [City Engineer] shall be contacted to determine a solution. A different BMP type, or a Vector Management Plan prepared with concurrence from the County of San Diego Department of Environmental Health, may be required.	- Inspect monthly and after every 0.5-inch or larger storm event. If mosquitos are observed, increase inspection frequency to after every 0.1-inch or larger storm event. - Maintenance when needed.
Underdrain clogged	Clear blockage.	- Inspect if standing water is observed for longer than 24-96 hours following a storm event. - Maintenance when needed.

BF-1

Biofiltration

References

- American Mosquito Control Association.
<http://www.mosquito.org/>
- California Storm Water Quality Association (CASQA). 2003. Municipal BMP Handbook.
<https://www.casqa.org/resources/bmp-handbooks/municipal-bmp-handbook>
- County of San Diego. 2014. Low Impact Development Handbook.
<http://www.sandiegocounty.gov/content/sdc/dpw/watersheds/susmp/lid.html>
- San Diego County Copermittees. 2016. Model BMP Design Manual, Appendix E, Fact Sheet BF-1.
http://www.projectcleanwater.org/index.php?option=com_content&view=article&id=250&Itemid=220

BF-1

Biofiltration

Page Intentionally Blank for Double-Sided Printing

DRAFT

BF-1

Biofiltration

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	
Property / Development Name:		Responsible Party Name and Phone Number:
Property Address of BMP:		Responsible Party Address:

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 1 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Accumulation of sediment, litter, or debris Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Remove and properly dispose of accumulated materials, without damage to the vegetation ☐ If sediment, litter, or debris accumulation exceeds 25% of the surface ponding volume within one month (25% full*), add a forebay or other pre-treatment measures within the tributary area draining to the BMP to intercept the materials. ☐ Other / Comments:		
Poor vegetation establishment Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Re-seed, re-plant, or re-establish vegetation per original plans ☐ Other / Comments:		

*"25% full" is defined as $\frac{1}{4}$ of the depth from the design bottom elevation to the crest of the outflow structure (e.g., if the height to the outflow opening is 12 inches from the bottom elevation, then the materials must be removed when there is 3 inches of accumulation – this should be marked on the outflow structure).

BF-1

Biofiltration

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 2 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Dead or diseased vegetation Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Remove dead or diseased vegetation, re-seed, re-plant, or re-establish vegetation per original plans ☐ Other / Comments:		
Overgrown vegetation Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Mow or trim as appropriate ☐ Other / Comments:		
2/3 of mulch has decomposed, or mulch has been removed Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Remove decomposed fraction and top off with fresh mulch to a total depth of 3 inches ☐ Other / Comments:		

BF-1

Biofiltration

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 3 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Erosion due to concentrated irrigation flow Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Repair/re-seed/re-plant eroded areas and adjust the irrigation system ☐ Other / Comments:		
Erosion due to concentrated storm water runoff flow Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Repair/re-seed/re-plant eroded areas, and make appropriate corrective measures such as adding erosion control blankets, adding stone at flow entry points, or minor re-grading to restore proper drainage according to the original plan ☐ If the issue is not corrected by restoring the BMP to the original plan and grade, the [City Engineer] shall be contacted prior to any additional repairs or reconstruction ☐ Other / Comments:		

BF-1

Biofiltration

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 4 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Obstructed inlet or outlet structure Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Clear blockage ☐ Other / Comments:		
Underdrain clogged (inspect underdrain if standing water is observed for longer than 24-96 hours following a storm event) Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Clear blockage ☐ Other / Comments:		
Damage to structural components such as weirs, inlet or outlet structures Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Repair or replace as applicable ☐ Other / Comments:		

BF-1

Biofiltration

Date:	Inspector:	BMP ID No.:
Permit No.:	APN(s):	

INSPECTION AND MAINTENANCE CHECKLIST FOR BF-1 BIOFILTRATION PAGE 5 of 5			
Threshold/Indicator	Maintenance Recommendation	Date	Description of Maintenance Conducted
Standing water in BMP for longer than 24-96 hours following a storm event* Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Make appropriate corrective measures such as adjusting irrigation system, removing obstructions of debris or invasive vegetation, clearing underdrains, or repairing/replacing clogged or compacted soils ☐ Other / Comments:		
Presence of mosquitos/larvae For images of egg rafts, larva, pupa, and adult mosquitos, see http://www.mosquito.org/biology Maintenance Needed? ☐ YES ☐ NO ☐ N/A	☐ Apply corrective measures to remove standing water in BMP when standing water occurs for longer than 24-96 hours following a storm event. ** ☐ Other / Comments:		

*Surface ponding longer than approximately 24 hours following a storm event may be detrimental to vegetation health, and surface ponding longer than approximately 96 hours following a storm event poses a risk of vector (mosquito) breeding. Poor drainage can result from clogging of the media layer, filter course, aggregate storage layer, underdrain, or outlet structure. The specific cause of the drainage issue must be determined and corrected.

**If mosquitos persist following corrective measures to remove standing water, or if the BMP design does not meet the 96-hour drawdown criteria due to release rates controlled by an orifice installed on the underdrain, the [City Engineer] shall be contacted to determine a solution. A different BMP type, or a Vector Management Plan prepared with concurrence from the County of San Diego Department of Environmental Health, may be required.

ATTACHMENT 4 - COPY OF PLAN SHEETS SHOWING PERMANENT STORM WATER BMPS

This is the cover sheet for Attachment 4.

Use this checklist to ensure the required information has been included on the plans:

The plans must identify:

- ☐ Structural BMP(s) with ID numbers matching Form I-6 Summary of PDP Structural BMPs
- ☐ The grading and drainage design shown on the plans must be consistent with the delineation of DMAs shown on the DMA exhibit
- ☐ Details and specifications for construction of structural BMP(s)
- ☐ Signage indicating the location and boundary of structural BMP(s) as required by the [City Engineer]
- ☐ How to access the structural BMP(s) to inspect and perform maintenance
- ☐ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
- ☐ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
- ☐ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
- ☐ Recommended equipment to perform maintenance
- ☐ When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management
- ☐ Include landscaping plan sheets showing vegetation requirements for vegetated structural BMP(s)
- ☐ All BMPs must be fully dimensioned on the plans
- ☐ When proprietary BMPs are used, site-specific cross section with outflow, inflow, and model number shall be provided. Photocopies of general brochures are not acceptable.

SEE CONTINUATION SHEET 5

SITE NOTES

- ALL UTILITIES SHOWN HEREON PER BEST AVAILABLE RECORD INFORMATION. FOR PROPOSED PUBLIC WATER AND SEWER UTILITIES, SEE SHEET 7 FOR PRELIMINARY UTILITY PLAN
- ALL EXISTING ONSITE STRUCTURES TO BE DEMOLISHED UNLESS OTHERWISE NOTED.
- ALL EXISTING ONSITE TREES TO BE REMOVED UNLESS OTHERWISE NOTED.
- HARDSCAPE SHALL DRAIN AWAY FROM PROPOSED STRUCTURES AT A MINIMUM OF 2.0% FOR 10 FEET, AND LANDSCAPE FOR A MINIMUM OF 5.0% IN ACCORDANCE WITH THE 2016 CALIFORNIA BUILDING CODE SECTION 1804.4.


*EMRA NOTE: EMRA WILL BE REQUIRED FOR ALL NON-STANDARD PRIVATE IMPROVEMENTS IN THE RIGHT OF WAY DURING FINAL ENGINEERING

LEGEND

EXISTING SUBDIVISION BOUNDARY (PL)	---
CENTERLINE OF ROAD	---
RIGHT-OF-WAY	---
PROPOSED SUBDIVISION BOUNDARY (AFTER DEDICATION)	---
ADJACENT PROPERTY LINE	---
SETBACK LINE	---
EXISTING CONTOUR LINE	---
PROPOSED CONTOUR LINE	---
PROPOSED FLOWLINE	---
PROPOSED DIRECTION OF FLOW	---
PROPOSED SAWCUT OF EXISTING AC PAVEMENT	---
PROPOSED FENCE (PER SEPARATE LANDSCAPE PLANS)	---
PROPOSED 6" STORM DRAIN @ 1.0% MIN	---
PROPOSED 12" AREA DRAIN	---
PROPOSED 6" STORM DRAIN CLEANOUT	---
PROPOSED 18" PVC STORM DRAIN @ 1.0% MIN	---
PROPOSED TYPE-B CURB INLET PER SDRSD D-2	---
PROPOSED TYPE A-4 STORM DRAIN CLEANOUT PER SDRSD D-9	---
PROPOSED LIMIT OF GRADING	---
PROPOSED 6" PCC CURB & GUTTER PER SDRSD G-2	---
PROPOSED PCC PAVEMENT	---
PROPOSED AC PAVEMENT (4" AC OVER 6" CLASS II AB MIN OR PER GEOTECH RECOMMENDATION)	---
PROPOSED 6" GRAVEL DRAINAGE DITCH	---
PROPOSED BMP BIOFILTRATION BASIN PER DETAIL SHEET 9	---
PROPOSED MASONRY RETAINING WALL	---
PROPOSED 6"x16" FLUSH CURB	---
EXISTING CITY INVENTORIED STREET TREE IN CURRENT PUBLIC RIGHT-OF-WAY	---
EXISTING TREE	---
LIMIT OF TREE PROTECTION ZONE (TPZ) PER ARBORIST REPORT	---
*DIAMETER AT BREAST HEIGHT (DBH) MEASURED AT 54" ABOVE NATURAL GRADE	---
PROPOSED FINISHED SURFACE CALLOUT	---
EXISTING FINISHED SURFACE CALLOUT	---
PROPOSED FILL SLOPE	---
PROPOSED CUT SLOPE	---
SHEET MATCHLINE	---

CONSTRUCTION NOTES

- EXISTING SURVEY MONUMENT SHALL BE PROTECTED IN PLACE. MONUMENT SHALL BE REPLACED BY A LICENSED LAND SURVEYOR WHO SHALL FILE A CORNER RECORD WITH THE COUNTY IF DISTURBED OR DESTROYED
- PROPOSED 12" X 12" AREA DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED 6" TRAFFIC RATED PRIVATE STORM DRAIN CLEANOUT BY NDS OR APPROVED EQUAL
- PROPOSED PCC CROSS-GUTTER PER SDRSD G-12
- PROPOSED 6" PCC CURB PER SDRSD G-1
- PROPOSED 6" PCC CURB AND GUTTER PER SDRSD G-2
- PROPOSED PCC DRIVEWAY APRON PER SDRSD G-14A
- PROPOSED PCC DRIVEWAY APRON PER SDRSD G-14C
- PROPOSED PCC SIDEWALK PER SDRSD G-7
- SAWCUT EXISTING AC PAVEMENT; SEE DETAIL ON SHEET 9
- PROPOSED BMP OUTLET STRUCTURES SEE SHEET 10 FOR BMP DETAILS
- PROPOSED 12" TRENCH DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED TYPE B STORM DRAIN CURB INLET PER SDRSD D-02
- OUTLET STORM DRAIN THROUGH RETAINING WALL; PROPOSED 4" X 4" ROCK RIP RAP ENERGY DISSIPATOR; 1.1" THICK, NO. 2 BACKING PER SDRSD D-34, D-40
- PROPOSED MASONRY RETAINING WALL PER SDRSD C-03
- PROPOSED TRENCH DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED CLEANOUT PER SDRSD D-08 WITH CURB OUTLET PER SDRSD D-25
- EXISTING TREE TO REMAIN; SEE STREET TREE NOTE 1 BELOW AND SHEET 13 FOR ADDITIONAL INFORMATION
- PROPOSED FREE-STANDING MASONRY WALL (NON-RETAINING) (NOT USED THIS SHEET)
- PROPOSED 6" X 16" PCC FLUSH CURB



ABBREVIATIONS

*SEE SHEET 1 FOR ABBREVIATION LEGEND

PROPOSED EASEMENTS / DEDICATIONS

*SEE SHEET 2 FOR PROPOSED EASEMENTS AND DEDICATIONS

UG NOTES




- EXISTING OVERHEAD UTILITIES TO BE REMOVED ALONG WESTERN PL BETWEEN POLE P121824J AND P120556 AND ON NORTHERN PL OF 1210 MELBA ROAD BETWEEN P120556 AND P120555. NEW UNDERGROUND SERVICE VIA PROJECT TO P120559 AND P120558 TO BE ADDED; OVERHEAD SERVICE FROM P120559 TO 1210 MELBA ROAD BARN TO REMAIN AND OVERHEAD SERVICE FROM P120559 TO 1210 MELBA RESIDENCE TO REMAIN.

PLAN VIEW - PRELIMINARY GRADING PLAN


SCALE: 1" = 20' HORIZONTAL

STREET TREE NOTE

- SEE SHEET 13 FOR MELBA ROAD FRONTAGE OPTION "A". TREES 106, 107, 108, 109, X15 AND X16 TO BE REMOVED FROM MELBA ROAD FRONTAGE OPTION "A". REFER TO SEPARATE ARBORIST REPORT FOR RECOMMENDATIONS WITHIN THE TREE PROTECTION ZONE (TPZ) FOR THE EXISTING TREES ON PRIVATE PROPERTY AND ALONG PROPERTY BOUNDARY TO BE PROTECTED IN PLACE



MATCHLINE: SEE SHEET 6



TO BALOUR DRIVE
PLAN VIEW - PRELIMINARY GRADING PLAN
SCALE: 1" = 20' HORIZONTAL

PROPOSED EASEMENTS / DEDICATIONS

*SEE SHEET 2 FOR PROPOSED EASEMENTS AND DEDICATIONS

SITE NOTES

- ALL UTILITIES SHOWN HEREON PER BEST AVAILABLE RECORD INFORMATION. FOR PROPOSED PUBLIC WATER AND SEWER UTILITIES, SEE SHEET 7 FOR PRELIMINARY UTILITY PLAN
- ALL EXISTING ONSITE STRUCTURES TO BE DEMOLISHED UNLESS OTHERWISE NOTED.
- ALL EXISTING ONSITE TREES TO BE REMOVED UNLESS OTHERWISE NOTED.
- HARDSCAPE SHALL DRAIN AWAY FROM PROPOSED STRUCTURES AT A MINIMUM OF 2.0% FOR 10 FEET, AND LANDSCAPE FOR A MINIMUM OF 5.0% IN ACCORDANCE WITH THE 2016 CALIFORNIA BUILDING CODE SECTION 1804.4.

LEGEND

EXISTING SUBDIVISION BOUNDARY (PL)	
CENTERLINE OF ROAD	
RIGHT-OF-WAY	
PROPOSED SUBDIVISION BOUNDARY (AFTER DEDICATION)	
ADJACENT PROPERTY LINE	
SETBACK LINE	
EXISTING CONTOUR LINE	
PROPOSED CONTOUR LINE	
PROPOSED FLOWLINE	
PROPOSED DIRECTION OF FLOW	
PROPOSED SAWCUT OF EXISTING AC PAVEMENT	
PROPOSED FENCE (PER SEPARATE LANDSCAPE PLANS)	
PROPOSED 6" STORM DRAIN @ 1.0% MIN	
PROPOSED 12" AREA DRAIN	
PROPOSED 6" STORM DRAIN CLEANOUT	
PROPOSED 18" PVC STORM DRAIN @ 1.0% MIN	
PROPOSED TYPE-B CURB INLET PER SDSRSD D-2	
PROPOSED TYPE A-4 STORM DRAIN CLEANOUT PER SDSRSD D-9	
PROPOSED LIMIT OF GRADING	
PROPOSED 6" PCC CURB & GUTTER PER SDSRSD G-2	
PROPOSED PCC PAVEMENT	
PROPOSED AC PAVEMENT (4" AC OVER 6" CLASS II AB MIN OR PER GEOTECH RECOMMENDATION)	
PROPOSED 6" GRAVEL DRAINAGE DITCH	
PROPOSED BMP BIOFILTRATION BASIN PER DETAIL SHEET 9	
PROPOSED MASONRY RETAINING WALL	
PROPOSED 6"x16" FLUSH CURB	
EXISTING CITY INVENTORIED STREET TREE IN CURRENT PUBLIC RIGHT-OF-WAY	
EXISTING TREE	
LIMIT OF TREE PROTECTION ZONE (TPZ) PER ARBORIST REPORT	
*DIAMETER AT BREAST HEIGHT (DBH) MEASURED AT 54" ABOVE NATURAL GRADE	
PROPOSED FINISHED SURFACE CALLOUT	
EXISTING FINISHED SURFACE CALLOUT	
PROPOSED FILL SLOPE	
PROPOSED CUT SLOPE	
SHEET MATCHLINE	

CONSTRUCTION NOTES

- EXISTING SURVEY MONUMENT SHALL BE PROTECTED IN PLACE. MONUMENT SHALL BE REPLACED BY A LICENSED LAND SURVEYOR WHO SHALL FILE A CORNER RECORD WITH THE COUNTY IF DISTURBED OR DESTROYED
- PROPOSED 12" X 12" AREA DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED 6" TRAFFIC RATED PRIVATE STORM DRAIN CLEANOUT BY NDS OR APPROVED EQUAL
- PROPOSED PCC CROSS-GUTTER PER SDSRSD G-12 (NOT USED THIS SHEET)
- PROPOSED 6" PCC CURB PER SDSRSD G-1
- PROPOSED 6" PCC CURB AND GUTTER PER SDSRSD G-2
- PROPOSED PCC DRIVEWAY APRON PER SDSRSD G-14A
- PROPOSED PCC DRIVEWAY APRON PER SDSRSD G-14C
- PROPOSED PCC SIDEWALK PER SDSRSD G-7
- SAWCUT EXISTING AC PAVEMENT; SEE DETAIL ON SHEET 9 (NOT USED THIS SHEET)
- PROPOSED BMP OUTLET STRUCTURES SEE SHEET 10 FOR BMP DETAILS (NOT USED THIS SHEET)
- PROPOSED 12" TRENCH DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED TYPE B STORM DRAIN CURB INLET PER SDSRSD D-02
- OUTLET STORM DRAIN THROUGH RETAINING WALL; PROPOSED 4" X 4" ROCK RIP RAP ENERGY DISSIPATER; 1.1" THICK, NO. 2 BACKING PER SDSRSD D-34, D-40 (NOT USED THIS SHEET)
- PROPOSED MASONRY RETAINING WALL PER SDSRSD C-03
- PROPOSED TRENCH DRAIN BY NDS OR APPROVED EQUAL (NOT USED THIS SHEET)
- PROPOSED CLEANOUT PER SDSRSD D-09 WITH CURB OUTLET PER SDSRSD D-25 (NOT USED THIS SHEET)
- EXISTING TREE TO REMAIN; SEE STREET TREE NOTE 1 BELOW AND SHEET 13 FOR ADDITIONAL INFORMATION
- PROPOSED FREE-STANDING MASONRY WALL (NON-RETAINING) (NOT USED THIS SHEET)
- PROPOSED 6" X 16" PCC FLUSH CURB



PLSA
ENGINEERING, INC.
PLSAENGINEERING.COM

LEGEND

EXISTING SUBDIVISION BOUNDARY (PL)	
CENTERLINE OF ROAD	
RIGHT-OF-WAY	
PROPOSED SUBDIVISION BOUNDARY (AFTER DEDICATION)	
ADJACENT PROPERTY LINE	
SETBACK LINE	
EXISTING CONTOUR LINE	
PROPOSED CONTOUR LINE	
PROPOSED FLOWLINE	
PROPOSED DIRECTION OF FLOW	
PROPOSED FENCE (PER SEPARATE LANDSCAPE PLANS)	
PROPOSED 6" STORM DRAIN @ 1.0% MIN	
PROPOSED 12" AREA DRAIN	
PROPOSED 6" STORM DRAIN CLEANOUT	
PROPOSED 18" PVC STORM DRAIN @ 1.0% MIN	
PROPOSED TYPE-B CURB INLET PER SDRSD D-2	
PROPOSED TYPE A-4 STORM DRAIN CLEANOUT PER SDRSD D-9	
PROPOSED LIMIT OF GRADING	
PROPOSED 6" PCC CURB & GUTTER PER SDRSD G-2	
PROPOSED PCC PAVEMENT	
PROPOSED AC PAVEMENT (4" AC OVER 6" CLASS II AB MIN OR PER GEOTECH RECOMMENDATION)	
PROPOSED 6" GRAVEL DRAINAGE DITCH	
PROPOSED BMP BIOFILTRATION BASIN PER DETAIL SHEET 9	
PROPOSED MASONRY RETAINING WALL	
PROPOSED 6"X16" FLUSH CURB	
EXISTING CITY INVENTORIED STREET TREE IN CURRENT PUBLIC RIGHT-OF-WAY	
EXISTING TREE	
LIMIT OF TREE PROTECTION ZONE (TPZ) PER ARBORIST REPORT	
*DIAMETER AT BREAST HEIGHT (DBH) MEASURED AT 54" ABOVE NATURAL GRADE	
PROPOSED FINISHED SURFACE CALLOUT	
EXISTING FINISHED SURFACE CALLOUT	
PROPOSED FILL SLOPE	
PROPOSED CUT SLOPE	
SHEET MATCHLINE	

CONSTRUCTION NOTES

- EXISTING SURVEY MONUMENT SHALL BE PROTECTED IN PLACE. MONUMENT SHALL BE REPLACED BY A LICENSED LAND SURVEYOR WHO SHALL FILE A CORNER RECORD WITH THE COUNTY IF DISTURBED OR DESTROYED
- PROPOSED 12" X 12" AREA DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED 6" TRAFFIC RATED PRIVATE STORM DRAIN CLEANOUT BY NDS OR APPROVED EQUAL
- PROPOSED PCC CROSS-GUTTER PER SDRSD G-12 (NOT USED THIS SHEET)
- PROPOSED 6" PCC CURB PER SDRSD G-1
- PROPOSED 6" PCC CURB AND GUTTER PER SDRSD G-2
- PROPOSED PCC DRIVEWAY APRON PER SDRSD G-14A
- PROPOSED PCC DRIVEWAY APRON PER SDRSD G-14C
- PROPOSED PCC SIDEWALK PER SDRSD G-7
- SAWCUT EXISTING AC PAVEMENT; SEE DETAIL ON SHEET 9 (NOT USED THIS SHEET)
- PROPOSED BMP OUTLET STRUCTURES SEE SHEET 10 FOR BMP DETAILS
- PROPOSED 12" TRENCH DRAIN BY NDS OR APPROVED EQUAL
- PROPOSED TYPE B STORM DRAIN CURB INLET PER SDRSD D-02
- OUTLET STORM DRAIN THROUGH RETAINING WALL; PROPOSED 4" X 4" ROCK RIP RAP ENERGY DISSIPATER; 1.1" THICK, NO. 2 BACKING PER SDRSD D-34, D-40 (NOT USED THIS SHEET)
- PROPOSED MASONRY RETAINING WALL PER SDRSD C-03
- PROPOSED TRENCH DRAIN BY NDS OR APPROVED EQUAL (NOT USED THIS SHEET)
- PROPOSED CLEANOUT PER SDRSD D-09 WITH CURB OUTLET PER SDRSD D-25 (NOT USED THIS SHEET)
- EXISTING TREE TO REMAIN; SEE STREET TREE NOTE 1 BELOW AND SHEET 13 FOR ADDITIONAL INFORMATION
- PROPOSED FREE-STANDING MASONRY WALL (NON-RETAINING) (NOT USED THIS SHEET)
- PROPOSED 6" X 16" PCC FLUSH CURB

SEE CONTINUATION SHEET 5



SEE CONTINUATION SHEET 4

PROPOSED EASEMENTS / DEDICATIONS











*SEE SHEET 2 FOR PROPOSED EASEMENTS AND DEDICATIONS

PLAN VIEW - PRELIMINARY GRADING PLAN


SCALE: 1" = 20' HORIZONTAL



PLSA
PLSAENGINEERING.COM





NOTE: BUILDING HEIGHT TO BE MEASURED FROM THE LOWER OF EXISTING OR PROPOSED FINISHED GRADES



PLAN VIEW - BMP B OFFSITE DRAINAGE PLAN

SCALE: 1" = 30' HORIZONTAL



TYPICAL SECTION - BIOFILTRATION BASIN B


NOT TO SCALE

PROPOSED EASEMENT INFORMATION

14) PROPOSED DRAINAGE EASEMENT (ON LOT 80) FOR THE BENEFIT OF THE PROPOSED DEVELOPMENT

CONSTRUCTION NOTES


- 1) PROPOSED 18" HDPE STORM DRAIN OUTLET PIPE FROM BMP, WATER TIGHT JOINTS
- 2) PROPOSED 24" X 24" BROOKS BOX CLEANOUT W/ INTERLOCKING LID
- 3) PROPOSED TYPE A CLEANOUT PER SDRSD D-9
- 4) PROPOSED BMP STRUCTURES SEE DETAIL THIS SHEET
- 5) EXISTING FENCE TO BE REMOVED AND REPLACED AS NECESSARY
- 6) EXISTING TREE PREVIOUSLY REMOVED
- 7) CONNECT 18" HDPE STORM DRAIN TO SDRSD D-09 CLEANOUT
- 8) PROPOSED WOODEN SURFACE PLANTER BOX
- 9) EXISTING TREE TO BE REMOVED PER SEPARATE AGREEMENT WITH OWNER
- 10) EXISTING TREE (X29) TO BE PROTECTED IN PLACE; NO TREE ROOTS TO BE CUT WITHIN 15-FT OF TRUNK OF TREE



TYPICAL SECTION - BIOFILTRATION BASIN A


NOT TO SCALE

"BIOFILTRATION" "ENGINEERED SOIL" LAYER SHALL BE EVENLY MIXED COMPOSITION OF WASHED SAND, SANDY LOAM TOPSOIL, AND HUMIC COMPOST. THE MIX SHALL CONTAIN 65% SAND, 20% TOPSOIL, AND 15% COMPOST OR HARDWOOD MULCH IN ACCORDANCE WITH COUNTY OF SAN DIEGO LID BIOSWALE MEDIA



TYPICAL DETAIL - FLOW CONTROL ORIFICE PLATE

NOT TO SCALE



DETAIL - BIOFILTRATION BASIN A OUTLET STRUCTURES

SCALE: 1" = 10'

